	WATER WELL RE	CORD F	orm WW	C-5 K	SA 82a-1212				
1 LOCATION OF WATER WELL: FRACTION			SECTION NUMBER				RANGE NUMBER		
- Sedgwick	NW 1/4 SE	1/4 <b>SE</b>	1/4	27	Т 27	S	R 1E	C E/W	
Distance and direction from nearest town or city st 2620 E. Sennett St.	Wichita, Kan								
	RGE, Dennis	343							
RR#,ST. ADDRESS,BOX #: 2620 E. Sennett St.									
	ita, Kansas			CODE: 6	7211 A	pplication Num	nber:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	EPTH OF COMPACED WE	ELL: 28	ft.		ELEVATION:				
N Dept	th of groundwater Encounter		ft.			ft.		ft.	
WEI	LL'S STATIC WATER LEVE			W LAND SU	JRFACE MEASUR				
NW - NE	Pump test data Est. Yield: apm	<ul> <li>a: Well wate</li> <li>Well wate</li> </ul>			ft. after ft. after		of pumping @ of pumping @	gpm	
₩ E Bo	Est. Yield: gpm re Hole Diameter	in.	to	ft.		in.	to	gpm ft.	
-   WEI	LL WATER TO SE USED A	S:				9. Dewateri		ction well	
	SW SE 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 12. Other (Specify below)								
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well  Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample									
	mitted	inple submitted to De	epartment:	YES Was V	Vater Well Disinfed			NO	
5 TYPE OF CASING USED:	5. Wrought Iron	7. Fiberglass	9. Ott	her (Specify	below) CASIN	G JOINTS:	Glued	Threaded	
1. Steel 3. RPM (SR) Welded Clamped									
2. PVC 4. ABS Blank casing diameter 1 1/4 in			in.	to	ft., Di		in. to	ft.	
	20				,			14.	
Casing height below and surface: 30 in., Weight: Ibs. / ft. Wall thickness or gauge No.  TYPE OF SCREEN OR PERFORATION MATERIAL:									
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) N/A									
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None ( open hole						open hole)			
2. Louvered shutter 4. Key pu	nched 6. Wire wrapp	ped	8. <b>Sa</b> v	w cut	10. Other	(specify) N	/A		
SCREEN - PERFORATION INTERVAL	From	ft. to		ft.,	From	ft.	to	ft.	
	From	ft. to		ft.,	From	ft.	to	ft.	
GRAVEL PACK INTERVALS:	From	ft. to		ft.,	From	ft.	to	ft.	
	From	ft. to		ft.,	From	ft.	to	ft.	
6 GROUT MATERIALS: 1. Neat c	ement 2. Cem	ent Grout	3	. Bentonite	, 0	ther bent	onite hole pl	ug	
Grout Intervals: From ft. to ft., From ft. to ft., From 3 ft. to 23 ft.							23 ft.		
What is the nearest source of possible contamination:  1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well						Gas well			
1. Septic tank 4. Lateral lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well					water well	16. Other (sp	pecify below)		
3. Watertight sewer line 6. Seepag	0 F	<b>d</b> 1:	2. Fertilizer	storage			None Ap	parent	
Direction from well?					How man				
From To L	ITHOLOGIC LOG		From	То			GIC LOG		
			3	23	compacted topsoil bentonite hole plug				
			23	28	chlorinated v			77/11	
								70.4	
							71.0		
Contractor's or Landowner's Certification: This water well was 1, constructed 2, reconstructed or 3, plugged under my jurisdiction and									
was completed on (mo/day/year) 7/17/2009 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No. 236  This water well record was completed on (mo/day/year)  7/20/2009									
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp									