Form WWC-5 WATER WELL RECORD KSA 82a-1212 1 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER NWSedgwick SE 27 1/4 21 Т 1E1/4 S R E/W Distance and direction from nearest town or city street address of well if located within city? Washington & Lewis Intersection, 200 feet East Wichita, Kansas WATER WELL OWNER: WICHITA, CITY OF Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX # 455 N. Main Wichita, Kansas 20090189 CITY, STATE: ZIP CODE Application Number: 40 4 DEPTH OF COMPLETED WELL: LOCATE WELL'S LOCATION **ELEVATION:** ft. WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered ft. ft. ft. WELL'S STATIC WATER LEVEL 15 7/29/09 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data: Well water was ft. after hours of pumping @ gpm - NW NE hours of pumping @ Mile Est. Yield: gpm Well water was ft. after gpm 12 40 Bore Hole Diameter and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering SW SE 7. Lawn and garden only 3. Feedlot 5. Public water supply 1. Domestic 12. Other (Specify below) 8. Air conditioning 10. Monitoring well 2. Irrigation 4. Industrial 6. Oil field water supply ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO submitted Was Water Well Disinfected? (YES) 5 TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: Glued Threaded 5. Wrought Iron 7. Fiberglass 3. RPM (SR) 1. Steel Welded Clamped SDR-26 8. Concrete tile 6. Asbestos-Cement 2. PVC 4. ABS Blank casing diameter 8 20 Dia. in ft., Dia ft. in. to 5.52 Casing height above land surface: in Weight: lbs. / ft Wall thickness or gauge No. .332 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 9 ABS 1. Steel 3. Stainless Steel 5. Fiberglass 8. RMP (SR) 2. Brass 4. Galvanized 6. Concrete Tile 10. Asbestos-Cement 12. None used (open hole) SCREEN OR PERFORATION OPENINGS ARE 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched Wire wrapped 8. Saw cut 10. Other (specify) SCREEN - PERFORATION INTERVAL 20 40 From ft., From ft ft to ft. From to ft., From ft. ft. to 20 GRAVEL PACK INTERVALS: ft. to 40 From ft., From to ft. ft. From to ft.. From ft. to ft. **GROUT MATERIALS:** Other 6 1. Neat cement 2. Cement Grout 3. Bentonite bentonite hole plug 20 Grout Intervals: From From ft. to ft.. From to ft. What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 4. Lateral lines 1. Septic tank 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 2. Sewer lines 5. Cess Pool None Apparent 12. Fertilizer storage 9. Feed yard 6. Seepage pit 3. Watertight sewer line Direction from well? How many feet? From Τо LITHOLOGIC LOG From Τo LITHOLOGIC LOG 3 topsoil 3 11 clay 11 27 fine to medium sand 27 40 medium sand Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. under my jurisdiction and 7/29/2009 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 7/31/2009 Todd S. Harb under the business name of Harp Well and Pump Service by (signature)