		WATER	WFII RE	CORD F	orm WV	/C-5 K	SA 82a-12	912		
1 LOCATION OF WATE	ER WELL:	FRACTION	***************************************	-OORD 1		TION NUMBER	_	IP NUMBER	RANGE NU	MBER
Sedgwick			/4 NW	1/4 NW	1/4	29	1	27 s	R 1E	Ε/W
Distance and direction from	om nearest town or ci	ity street address of	well if located v	vithin city?			•			
419 S. Osage	Wichit	a, Kansas								
2 WATER WELL		GWELL, Ka	ithy					Board of Agri	culture, Division of Wa	atar Pasauras
RR#,ST. ADDRESS		S. Osage						Board of Agri	culture, Division of W	ater resource
		chita, Kansa			_	P CODE:		Application Num	nber:	
3 LOCATE WELL'S L	OCATION 4	DEPTH OF CO	MPLETED W	/ELL: 4	0 ft.		ELEVATION:			
N N		epth of groundwa	ater Encounte		ft.			ft.		ft.
	V	WELL'S STATIC	WATER LEV	EL 10	FT. BELO	W LAND SU	JRFACE MEAS	SURED ON mo/o	lay/yr: 8/4/	09
NW	NE		Pump test da				ft. after		of pumping @	gpm
w W		Est. Yield: Bore Hole Diame	gpm eter 12	Well wa 2 in.	ter was to 4	10 ft.	ft. after		of pumping @ to	gpm ft.
7 w	·	WELL WATER TO			10 -	it.	and	in.	44 Into	tion well
sw	sE	1. Domestic	3. Feedlot		ter supply	7. Lawn a	nd garden on	9. Dewateri	ng 12. Other (Sp	
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well										
S		Was a chemical/ba	cteriological sa	mple submitted to I	Department?	YES	NO		what mo/day/yr w	
= = = = = = = = = = = = = = = = = = = =		submitted					Vater Well Disi		=	10
5 TYPE OF CA 1. Steel	SING USED: 3. RPM (5. Wrou	ght Iron	Fiberglass	9. O	ther (Specify	below) CA	ASING JOINTS: (Glued	Threaded
2. PVC	3. KFW (stos-Cement	8. Concrete t	ile SD	R-26			Welded	Clamped
Blank casing diame		in. to	30 ft.	, Dia.	in.	to	ft.,	Dia.	in. to	ft.
Casing height abov		12 in.		Weight:		os. / ft.				
" "				weight.	2.33	DS. / II.	waii	thickness or gaug	ge No214	
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)										
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)										
SCREEN OR PERF	ORATION OPENII	NGS ARE:								
1. Continuous slo			5. Gauzed w	rapped	7. To	rch cut	9. Dr	illed holes	11. None (o	pen hole)
2. Louvered shutt					(8 Sa	w cut	10. Ot	her (specify)		
1								or (opcolly)		
SCREEN - PERFOR	ATION INTERVAL		30	ft. to		ft.,	From	ft.	to	ft.
		From	•	ft. to		ft.,	From	ft.	to	ft.
GRAVEL PA	ACK INTERVALS:	From	24	ft. to	40	ft.,	From	ft.	to	ft.
		From		ft. to)	ft.,	From	ft.	to	ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout								Other bent	onite hole plu	ıg
Grout Intervals:			to 24	ft., From	ft.	to	ft.,	From	ft. to	ft.
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil w								15. Oil well/G	as well	
1. Septic tank			8. Sewage		11. Fuel sto	rage		don water well	16. Other (sp	ecify below)
2. Sewer lines	5. Cess		_			•	i T. Awai	don water wen		-
Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage Direction from well? North 12. Fertilizer storage How many feet? 10 ft. plus										
From To	1	LITHOLOG	SIC LOG		From	То	110111		GIC LOG	
0 3	topsoil	2	<u> </u>		1	, ,				
3 8	clay									
8 12	sandy clay				.					
12 20	fine sand									
20 39	medium sar	nd			—					
39 40	gray shale				-					
	1									
		·								
	-									
	-									
					1					
7 Contractor's or	Landowner's Cert	tification: This wa	ter well was	1. Constructe	d) 2 re	constructed	d or 3.	plugged	under my jurisdicti	on and
was completed or		8/4/200		and this record						
was completed of	· (IIIO/day/year)	0,7,200		and and record	.3 46 10 111	o book of fifty	omouge all	- Jonol.		

This water well record was completed on (mo/day/year) Kansas Water Well Contractor's License No. 236

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harp