			ER WELL RECORD		-5 KSA 82a		
1 LOCATION OF V		Fraction	, NISS	1 '	ction Number	Township Number	Range Number
	tion from nearest to	SE 3	4 NW ¼ N t address of well if locat	E 1/4 ed within city	<u>21</u> /?	T 27 S	R 1 E/V
329 N. Indiana							
2 WATER WELL	1000 0	W Jackson St., Su	rite 410			5	· · · · · · · · · · · · · · · · · · ·
RR#, St. Address, Box# 1000 SW Jackson St., Suite 410 Topeka, KS 66612-1367					Board of Agriculture, Division of Water Resources Application Number:		
3 LOCATE WELL	SECTION BOY.						
- WITH AN "X" IN	N						. 3 ft.
A							//yr
, w	I X _{IE} I I		•				umping gpm
			•				umping gpm
W M	E						in. to ft.
-			TO BE USED AS: 5			8 Air conditioning 11 9 Dewatering 12	Injection well
. sw	SE	1 Domestic					(Specify below)
1		2 Irrigation Was a chemic	al/bacteriological sampl	e submitted t	o Department	YesNo V; If ye	
<u>Y</u>	S	submitted	ar bactoriological campi	o oubmittou i	•	ter Well Disinfectea? Yes	No √
5 TYPE OF BLAN	K CASING USED:		5 Wrought iron	8 Conc	rete tile	CASING JOINTS: Glu	ed Clamped
1 Steel	3 RMP (SF	(8)	6 Asbestos-Cement		(specify below		elded
2 PVC	4 ABS	,	7 Fiberglass			Thr	eaded. 🗸
Blank casing diame	ter	. in. to	8 ft., Dia	in.	to	ft., Dia	in. to ft.
Casing height above	e land surface		. in., weight			t. Wall thickness or gauge	No Sch. 40
TYPE OF SCREEN	OR PERFORATION	N MATERIAL		(7)PV	/C	10 Asbestos-ce	ment
1 Steel	3 Stainless	steel	5 Fiberglass	8 RN	/IP (SR)	11 Other (speci-	fy)
2 Brass	4 Galvanize	ed steel	6 Concrete tile	9 AE	BS	12 None used (open hole)
SCREEN OR PERF	ORATION OPENING			ed wrapped		8 Saw cut	11 None (open hole)
1 Continuous			6 Wire	wrapped		9 Drilled holes	
2 Louvered s		ey punched	7 Torch			10 Other (specify)	
SCREEN-PERFOR	ATED INTERVALS:						t. to
CDAVEL I	DACK INTERVALE.						t. toft. t. toft.
GRAVEL	PACK INTERVALS:						t. to
ODOLETAATED	Al. A North		2 Cement grout				
6 GROUT MATER					to 7		ft. to ft.
What is the neares				IL			Abandoned water well
1 Septic tank	4 Later		7 Pit privy		11 Fuel:		Oil well/Gas well
2 Sewer lines	5 Cess		8 Sewage lag	oon			Other (specify below)
3 Watertight se		•	9 Feedyard			ticide storage	,
Direction from well?			•		How man	y feet?	
FROM TO		LITHOLOGIC	LOG	FROM	TO	PLUGGING	INTERVALS
0 3	Clay, silty, sar	ndy, Dark Bi	own				
3 5	Clay, silty, sar	ndy, Brown					
5 8.5	Sand (vf-c), L	t. Brown					
8.5 13	Sand (vf-c) w/	clayey silt st	ringers, Lt. Brown				
13 23	Sand (f-c) w/t	r. f gravel, B	rown				
	-						
							<u>·</u>
							
					A	MW5, Flushmount	
							-
				as (1) constr		onstructed, or (3) plugged	
and was completed						cord is true to the best of r	
				s Water We		completed on (mo/day/yr)	5/28/2009
under the business	name of	G	eoCore, Inc.	17.4	by (signat	ure) Chu Ker	<u> </u>
	lee typewriter or half noi	nt pen. PLEASE P	RESS FIRMLY and PRINT c	learly. Please fi	ill in blanks, under	line or circle the correct answers. to WATER WELL OWNER and r	Send top three copies to Kansas