PMW-2

WAILI	CANEI	L RECORD	FORM W	WC-3			r Resources App. N			
		OF WATER WELL:	Fraction SE ¼ SE ¼ SE	1/4 1,	Secti	on Number 13	Township No. T 27 S	Range Number R 1		
County: Sedqwick SE 1/4 SE 1/4 SE 1/4 SE 1/4 Street/Rural Address of Well Location; if unknown, distance & direction						Global Positioning System (GPS) information:				
	from nearest town or intersection: If at owner's address, check here						Latitude: (in decimal degrees)			
	511 N. Woodlawn						Longitude: (in decimal degrees)			
Wichita, KS					Eleva	Elevation:				
						<u>Datum</u> : ☐ WGS 84, ☐ NAD 83, ☐ NAD 27				
2 WATER WELL OWNER: KDHE						Collection Method:				
RR#, Street Address, Box #: 1000 SW Jackson St						GPS unit (Make/Model:)				
City, State, ZIP Code : Topeka, KS 66612			KS 66612			☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m				
3 LOCATE WELL										
	WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 27.5 ft.									
	SECTION BOX: Depth(s) Groundwater Encountered (1), 12.5 ft. (2) ft. (3) ft.									
	N WELL'S STATIC WATER LEVEL. 12.58 ft. below land surface measured on mo/day/yr									
	Pump test data: Well water wasft. after hours pumping									
NW	N		gpm. Well water							
w		E Bore Hole Diam	eterin. to							
<del></del>	_	· I I —	TO BE USED AS:					njection well		
SWSE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)										
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☑ Monitoring well										
was a chemical/bacteriological sample submitted to Department?										
S If yes, mo/day/yr sample was submitted										
water went distincted: 1 10										
		ASING USED:   Stee				•••••				
		rs: Glued  Clan				0 5				
Casing diameter .2										
Casing height above land surface. Flush in., Weight										
TYPE OF SCREEN OR PERFORATION MATERIAL:  ☐ Steel ☐ Stainless Steel										
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)										
SCREEN OR PERFORATION OPENINGS ARE:										
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)										
Louvered shutter    Key punched    Wire wrapped    Saw cut    Other (specify)										
SCREEN-PERFORATED INTERVALS: From										
GRAVEL PACK INTERVALS: From. 4 ft. to27.5 ft., From ft. to ft.										
From										
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other										
Grout In		From ft. to								
What is the nearest source of possible contamination:										
Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)										
✓ Sewer lines       Cesspool       Sewage lagoon       Fuel storage       Abandoned water well         ✓ Watertight sewer lines       Seepage pit       Feedyard       Fertilizer storage       Oil well/gas well										
_	_		it recayata							
FROM	TO	LITHOLOG		FROM	TO			GGING INTERVALS		
	1'	Asphalt-4", Fill-8"		20'	27.5'	Sandy Clay				
	6.5'	Clay					<del></del>			
6.5'	7.5'	Clayey Sand								
7.5'	8'	Caliche								
8'	10'	Sandy Clay								
10'	12.5'	Clay								
12.5'	13.5'	Sand								
	16'	Clay								
16'	18'	Sand								
18'	20'	Clay								
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was   ✓ constructed, ☐ reconstructed, or ☐ plugged										
under my jurisdiction and was completed on (mo/day/year)8/13/09 and this record is true to the best of my knowledge and belief.										
Kansas Water Well Contractor's License No										
under the business name of										
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.										
Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at										
http://www.kdheks.gov/waterwell/index.html.										
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy										