	WATER WE	ELL RECORD	Form W	WC-5 K	SA 82a-12	12			
1 LOCATION OF WATER WELL:	FRACTION		CTION NUMBER	l		RANGE NUMBER			
Sedgwick  Distance and direction from nearest town or city	NW 1/4	SW 1/4 S	E 1/4	18	T 2	7 s	R 1E	E/W	
1800 W. Museum Blvd.		ichita, Kansas							
	CHITA, CITY								
RR#,ST. ADDRESS,BOX #: 455 N. Main  Board of Agriculture, Division of Water Resource									
CITY, STATE: Wicl	hita, Kansas			ZIP CODE:		Application Num	nber:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	DEPTH OF COMPL	ETED WELL:	<b>40</b> f		ELEVATION:				
N De	pth of groundwater	Encountered:		ft.		ft.		ft.	
WI WI	ELL'S STATIC WAT	TER LEVEL 12	FT. BEL	OW LAND SU	JRFACE MEAS	URED ON mo/d	lay/yr: 10/15	/09	
NW NE		•	water was		ft. after		of pumping @	gpm	
W W E B	Est. Yield:	VI 1.5	I water was	<b>40</b> ft.	ft. after		of pumping @	gpm	
1 1 1	Bore Hole Diameter ELL WATER TO BE		to	<b>40</b> ft.	. and	in.	to 11. injec	ft.	
	5. Dewatering								
	2. Irrigation 4. I	ndustrial 6. Oil fie	ld water supp	ly 8. Air cor	nditioning	10. Monitorir	ng well		
· · · · · · · · · · · · · · · · · · ·	Was a chemical/bacterion	ological sample submitted	d to Department		NO Water Well Disin		vhat mo/day/yr wa		
5 TYPE OF CASING USED:	,								
1. Steel 3. RPM (SR)  5. Wrought Iron 7. Fiberglass 9. Other (Specify below) CASING JOINTS: Glued Threaded Welded Clamped									
2. PVC 4. ABS	<ol><li>Asbestos-</li></ol>	Cement 8. Concre	ete tile					Ciampou	
Blank casing diameter 8	in. to 2	20 ft., Dia.	in.	to	ft.,	Dia.	in. to	ft.	
Casing height above land surface:	12 in.,	Weight:	5.52	lbs. / ft.	Wall th	nickness or gaug	ge No332		
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)									
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)								Jen noie,	
2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)									
SCREEN - PERFORATION INTERVAL	From	<b>20</b> ft.	to <b>40</b>	ft.,	From	ft.	to	ft.	
	From	ft.	to	ft.,	From	ft.	to	ft.	
GRAVEL PACK INTERVALS:	From	<b>20</b> ft.	to <b>40</b>	ft.,	From	ft.	to	ft.	
	From	ft.	to	ft.,	From	ft.	to	ft.	
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug									
Grout Intervals: From 0 ft. to 20 ft., From			m	ft. to		From	ft. to	ft.	
What is the nearest source of possible contamination:  1. Septic tank  4. Lateral lines  7. Pit privy			10. Livest	0. Livestock pens		13. Insecticide storage		15. Oil well/Gas well	
,			11. Fuel s	1. Fuel storage		14. Abandon water well		16. Other (specify below)	
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage None Apparent							parent		
Direction from well?					How m	any feet?			
From To	LITHOLOGIC	LOG	From	То		LITHOLC	GIC LOG		
0 3 topsoil				-					
3 7 clay 7 12 sandy clay					<u> </u>				
12 20 fine sand									
20 40 medium sand	i								
			_	+					
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and									
was completed on (mo/day/year)	10-15-2009	and this red	cord is true to	he best of my	knowledge and	belief.			
Kansas Water Well Contractor's Licen	ise No. 236	This water	er well record	vas completed	d on (mo/day/ye	ar) 10/19	9/2009		
under the business name of Harp Well and Pump Service by (signature)  Todd S. Harb									