					WELL REC	ORD Form		KSA 82a							
	ON OF WATER	l l		Section Number			•			Range Number					
County:	Sedç	Wick	NE.	1/4	NE ½	NE	1/4	8	1	r :	27	<u> </u>	R	1	E
istance and 21st and E	d direction from Broadway,	n nearest to: Wichita	wn or city stre	eet addr	ess of well i	f located wit	hin city?								
	WELL OWNE		f Wichita												
	dress, Box #	-			1_13				c	and of	A aria.	there Div	inian of IA	latar Dass	
	ZIP Code				1-10						-	ulture, Div	ISION OF W	aler Rest	ources
LOCATE	WELL'S LOC	ATON WITH	1 4							Application					-
) AN "X <u>" IN</u>	SECTION B	OX:	DEPTH		MPLETED										
1		X	Depth(s) G	roundwa	ater Encoun	tered 1	15	<u> </u>	ft. 2		. 	ft.	3		ft.
	NW -	NE	WELL'S ST	TATIC V	VATER LEV	EL	ft.	below land	surfac	e meas	ured o	n mo/day	/yr		
0	i 1	į			est data:										
§ W —		┿┩╒	Est. Yield		gpm:	Well water v	vas		ft. afte	er		hours p	oumping		gpm
ī l			Bore Hole I	Diamete	er 8	in. to	24	,	ft. a	nd		ir	n. to		ft.
│ ├	sw	SE	VVELL VVA	IEK IO	BE OSED	45: 5 Put	nic water si	ıppıy	,	Airco	naition	iing 1	1 Injectio	n well	
↓ I			1 Dor	mestic	3 Feed lo	6 Oil	field water	supply	6	Dewat	tering	1	2 Other	(Specify I	below)
' 	S				4 Industria										
	•			mical/ba	acteriologica	l sample su	bmitted to [was
			submitted									d? Yes			
	BLANK CAS				5 Wrough	t Iron	8 Concr	ete tile	(CASING	NIOL 6	ITS: Glue	:d	Clampe	d
***************************************	el		(SR)		6 Asbesto	s-Cement	9 Other	(specify be	low)	_	•	Weld			
2 PV	0	4 ABS			7 Fibergla	ISS						Threa	ded	Flus	h
3lank casing	diameter	2	in. to	22	ft., Dia								in. to		ft.
Casing heigh	ht above land	surface	0	in	., weight	0.	703	lbs./f	t. Wall	thickne	ss or o	gauge No		SCH. 40	0
	CREEN OR P				, ,		7	PVC							
1 Stee	el	3 Stain	less steel		5 Fibergla	ISS		RMP (SR)							
2 Bras	SS	4 Galva	anized steel		5 Fibergla6 Concret	e tile	9	ABS		12	None	used (op	en hole)		
SCREEN OF	R PERFORAT	ION OPENI	NGS ARE:			5 Gauzeo			8	Saw cu	ıt		11 Nor	ie (open h	ole)
1 Cor	ntinuous slot	3	Mill slot			6 Wire w	apped			Drilled I					
2 Lou	vered shutter	4	Key punche			7 Torch o			10	Other (speci	fy)			
SCREEN-PE	ERFORATED	INTERVALS	S: From		22 f	t. to	24	ft.	From			ft.	to		ft.
			From		f	t. to		ft.	From			ft.	to		ft.
GRA	AVEL PACK I	ITERVALS:	From		20 f	t. to	24	ft.	From			ft.	to		ft.
						t. to									
6 GROUT	MATERIAL:	1 Neat	cement	2 (Cement grou	ut	3 Ben	tonite	4 C	ther B	ento	nite G	rout		
— Grout Interva	als From	0.5	ft. to	20	ft. From										
What is the	nearest source	of possible	contamination	on:	••							14 Ab			
1 Sep	otic tank	•	4 Lateral	lines	7	Pit privy		11 Fue	el stora	ge		15 Oi	well/ Ga	s well	
2 Sev	ver lines	5 Cess po	goon			zer storage 16 Other (specify b									
3 Wat	tertight sewer	lines	6 Seepag	ge pit	9	Feedyard		13 Ins	ecticide	storage	е				
Direction fro	m well?							How mai	ny feet	?					
FROM	ТО	CODE			GIC LOG		FROM	ТО			PLU	IGGING I	NTERVA	_S	
0.0	7.0		and, tan, m			grained			-						
7.0	8.0		ilty Sand,					-							
8.0	24.0		and, tan to ained, with			coarse									
0.0	27.0	91	airieu, witti	some ;	graver										
								-							
			***************************************					1							
							L								
_	ACTOR'S OR					er well was									
	n (mo/day/yr)			01/12				is record is							
															0/4/0
Vater Well (Contractor's L	cense No.	 -		531			Vater Well			mplet	on (mo	/day/yr)	01/28	5/ I U
nder the bu	Contractor's Lusiness name JCTIONS: Ple n St., Ste. 420,	of	Geotec	hnica	al Servic	es Inc.	b)	(signature	e) //~	1/		4			