GSI Job No. 097412 SVE-5 WATER WELL RECORD Form WWC-5 KSA 82a-1212 ID No. 1 LOCATION OF WATER WELL: Fraction Section Number Township Number Range Number Sedgwick NE 1/4 NE 1/4 27 1 Ε Distance and direction from nearest town or city street address of well if located within city? 21st and Broadway, Wichita 2 WATER WELL OWNER: City of Wichita RR#, St. Address, Box # : 455 N. Main St., MS 1-13 Board of Agriculture, Division of Water Resources City, State, ZIP Code : Wichita, KS 67202 Application Number: LOCATE WELL'S LOCATON WITH 4 DEPTH OF COMPLETED WELL 20 ft. ELEVATION: Depth(s) Groundwater Encountered 1 19 ft. 2 ft. 3 ft.

WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr --- NE --Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 10 in. to 20 ft. and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well Soil Vapor Extraction W SW - SE -Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was Water Well Disinfected? Yes No X 5 TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 4 ABS 7 Fiberglass Threaded ______ Blank casing diameter 4 in. to 10 ft., Dia in. to ft., Dia in. to ft. Dia in. to ft. Casing height above land surface 0 in., weight 0.703 lbs./ft. Wall thickness or gauge No. SCH. 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 5 Fiberglass 8 RMP (SR) 11 Other (specify)
6 Concrete tile 9 ABS 12 None used (open hole)
5 Gauzed wrapped 8 Saw cut 11 None (open hole) Stainless steel 1 Steel 5 Fiberglass 2 Brass 4 Galvanized steel SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 10 Other (specify) 2 Louvered shutter 4 Key punched 7 Torch cut SCREEN-PERFORATED INTERVALS: From 10 ft. to 20 ft. From ft. to ft.
 From
 ft. to
 ft. From
 ft. to
 ft.

 From
 8
 ft. to
 20
 ft. From
 ft. to
 ft.
 GRAVEL PACK INTERVALS:
 ft. From
 ft. to
 ft.

 3 Bentonite
 4 Other

 6 GROUT MATERIAL:
 1 Neat cement
 2 Cement grout
 3 Bentonite
 4 Other

 Grout Intervals
 From
 8 ft. From
 ft. to
 ft. From
 ft. from
 ft. ft.
 10 Livestock pens What is the nearest source of possible contamination: 14 Abandoned water well 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/ Gas well 12 Fertilizer storage 16 Other (specify below) 2 Sewer lines 5 Cess pool 8 Sewage lagoon 13 Insecticide storage 3 Watertight sewer lines 6 Seepage pit 9 Feedyard Direction from well? How many feet? LITHOLOGIC LOG FROM PLUGGING INTERVALS FROM CODE TO TO 0.0 0.3 Asphalt 0.3 0.6 Fill, Rock Fill, Sand, brown, medium to coarse 7.0 0.6 grained, 3-4" thick brick layer at 6.5' Sand, light brown, fine grained, coarsening with depth, trace gravel at 7.0 20.0 SP 7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/yr)

01/14/10

and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 01/28/10 under the business name of Geotechnical Services Inc. by (signature) INSTRUCTIONS:. Please fill in blanks and circle the correct answers. Send three copies to Kansas Department of Flealth and Environment, Bureau of Water, 1000 S W Jackson St., Ste. 420, Topeka, Kansas 66612-1367. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.