WATER WELL RE	SENW Form W	Division of Wate	er Resources App. N	o.			
1 LOCATION OF WA	TER WELL	Fraction A	To was	Section Number	Township No.		
County:	guela	1/4	1/4	7	T 27 S	R ∕ ØE □W	
Street/Rural Address	of Well Location;	if unknown, distance	& direction	Global Positioning			
from nearest town or intersection: If at owner's address, check here . Latitude: (in decimal degrees)							
2155 Bell-usta				Longitude: (in decimal degrees)			
	Lavery	Elevation:	Elevation:				
2 WATER WELL OWNER: m Sulve Collection Method:						NAD 27	
RR#, Street Address,	FR DO	GPS unit (Mal	GPS unit (Make/Model:)				
City, State, ZIP Code : Wishit Ha 67203				☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
	Wide	uto Ko	67293	Est. Accuracy:	3 m, 3-5 m, 3	5-15 m,  >15 m	
3 LOCATE WELL	A DEPTH OF	COMPLETED ME	. 40	<i>o</i>			
WITH AN "X" IN SECTION BOX:	Devile Comme	COMPLETED WEI	ULZE	π.	Φ (	2) &	
N SECTION BOX:	"IN Depth of COMPLETED WELL ft. Depth(s) Groundwater Encountered (1) ft. (2) ft. (3) ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr.						
	Pump test data: Well water wasft. after						
w NW <sub>2</sub> NE	WNWNE E EST. YIELDgpm. Well water wasft. after hours pumpinggpm  Bore Hole Diameterin. toft., andft.						
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well							
SWSE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)							
☐ Irrigation ☐ Industrial ☑ Domestic-lawn & garden ☐ Monitoring well							
Was a chemical/bacteriological sample submitted to Department?  Yes  No							
S If yes, mo/day/yr sample was submitted							
1 mile  Water well disinfected?							
5 TYPE OF CASING USED: Steel PVC Other							
CASING JOINTS:  Glued  Clamped  Welded  Threaded							
Casing diameter							
Casing height above land surface							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
Steel Stainless Steel PVC Other (Specify)							
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)  SCREEN OR PERFORATION OPENINGS ARE:							
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)							
Louvered shutter Key punched Wire wrapped Saw cut, Other (specify)							
SCREEN-PERFORATED INTERVALS: From 30 ft. to 40 ft., From ft. to ft.							
From ft. to ft., From ft. to ft.							
GRAVEL PACK INTERVALS: From							
From							
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other							
Grout Intervals: From							
What is the nearest source	e of possible conta	mination:				( '0 ! ! )	
☐ Septic tank       ☐ Lateral lines       ☐ Pit privy       ☐ Livestock pens       ☐ Insecticide storage       ☐ Other (specify below)         ☐ Sewer lines       ☐ Cesspool       ☐ Sewage lagoon       ☐ Fuel storage       ☐ Abandoned water well							
Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well							
Direction from well							
FROM TO	LITHOLOG		FROM	TO LITHO. LO	OG (cont.) or PLU	GGING INTERVALS	
090	Top S	ore o					
9 22	ing I	an sand					
22 40 0	arse -	tan sa					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was a constructed, $\square$ reconstructed, or $\square$ plugged							
under my jurisdiction and was completed on (mo/day/year)							
Kansas Water Well Contractor's License No. 7. 7 This Water Well Redon Was completed on (mo/day/year)							
under the business name of Dan Pull by (signature) (si							
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.							
Telephone 785-296-5522. Se	nd one copy to WAT	ER WELL OWNER and	retain one for y	our records. Include fee	of \$5.00 for each co	onstructed well. Visit us at	
http://www.kdheks.gov/waterwell/index.html.							
KSA 82a-1212							