WATER WELL RECORD			Form WW	C-5	Division of Water I			
1 LOCATION OF WATER WELL: County: Sedgwick			Fraction NW 1/4 SE 1/4 SE 1/4				Range Number R 1 ☑ E □W	
			if unknown, distance & d	irection (5 T 27 S R 1 ZE W Global Positioning System (GPS) information:			
			owner's address, check he		Latitude: (in decimal degrees)			
	6 W 21st		• · · · · · · · · · · · · · · · · · · ·		Longitude: (in decimal degrees)			
Wichita, KS					Elevation:			
					<u>Datum</u> : ☐ WGS 84, ☐ NAD 83, ☐ NAD 27			
		- Galok	Frip Corporation		Collection Method:		,	
Ch Ch . ZID C 1.			outh West St.		☐ GPS unit (Make/Model:) ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
	, o.a.c, 2	. Wichita	, KS 67213		Est. Accuracy: \square <3:			
3 LOCATE WELL								
II .	WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 40							
SEC	SECTION BOX: Depth(s) Groundwater Encountered (I).13. ft. (2). ft. (3). ft. WELL'S STATIC WATER LEVEL. 13. ft. below land surface measured on mo/day/yr.6/14/11.							
	WELL'S STATIC WATER LEVELtt. below land surface measured on mo/day/yrg/l.4/.U Pump test data: Well water wasft. afterhours pumpingg							
		FOT VIELD 2						
W NW NE E ST. YIELD. 25gpm. Well water wasft. after						······	ft	
''	WELL WATER TO BE USED AS: Public water supply Geothermal Injection well							
8	□ Domestic □ Feedlot □ Oil field water supply □ Dewatering □ Other (Specify below)							
	Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No							
S If yes, mo/day/yr sample was submitted								
water werr distributed and the second								
		SING USED: Stee	l 🗹 PVC 🗌 Oth	ier				
CASIN	IG JOINT	S: M Glued ☐ Cla	mped Welded	Threaded	2 71			
Casing diameter .5 in. to .20 ft., Diameter in. to ft., Diameter in. to ft.								
Casing height above land surface12								
Steel Stainless Steel PVC Other (Specify)								
Brass Galvanized Steel None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)								
Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From								
From								
GRAVEL PACK INTERVALS: From 20 ft. to 40 ft., From ft. to ft.								
From ft. to ft., From ft. to ft.								
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout								
Grout Intervals: From .3								
What is the nearest source of possible contamination:								
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below) ✓ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well								
Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well								
Dire	ction fron	well west						
FROM		LITHOLOG	GIC LOG	FROM 1	O LITHO. LOC	G (cont.) or PLU	GGING INTERVALS	
0	3	Top Soil						
3	8	Clay				···		
8	39	Medium Sand						
39	40	Clay						
	 							
	 							
	† †							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged								
under my jurisdiction and was completed on (mo/day/year) .6/14/.11 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No238 This Water Well Record was completed of moday/year) 6/15/11								
under the business name of Premier Pump and Well Service, Inc. by (signature)								
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.								
Telephon	e 785-296-5	522. Send one copy to WAT	ER WELL OWNER and retain	in one for your	records. Include fee of	on 51., Suite 420, 1 f \$5.00 for each co	onstructed well. Visit us at	
http://www.kdheks.gov/waterweil/index.html.								
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy								