GSI Job	No. 0970	21										PZ-06
				WATE	ER WELL F	RECORD F	orm WWC-5	KSA 82	a-1212 ID No			
	ION OF WATE							tion Numb	er Township N	lumber	Range No	umber
	Sed							15	⊤ 27	s	R 1	E
	nd direction fro											
	de of Murd					PW-04) - \	<u> Vichita</u>					
	R WELL OWN											1
City State	ddress, Box # ZIP Code	· On	aha. NE						Board of Agri Application N		on of Water F	Resources
LOCATE	E WELL'S LO	CATON V	/ITH ,			ED WELL	27.	.5 ft. El	EVATION:		33 (TOC)	
T I		į	Depth(s) Ground	lwater End	ountered 1	1	5	ft. 2	ft. 3		ft
	NW	NE	WELL'S	STATIC	WATER	LEVEL	ft.	below TO	C measured on mo/	dav/vr		1
	i	INE							ft. after		mnina	
. w L	<u> </u>	į	E Est. Yie	id	anm	· Well wate	r was		ft after	hours nu	mnina	
7		1	Bore Ho	le Diame	eter 8 .	25 in to	27	.5	ft. and	in	יייים אייילייי	9piii
-	X-W	s'E	WELL V	VATER T	O BE US	ED AS: 5 P	ublic water s	upply	ft. and 8 Air condition 9 Dewatering	oning 11	Injection well	ft.
	į .	į	1	Domestic	3 Fee	d lot 6 C	il field water	supply	9 Dewatering	12	Other (Specif	fy below)
*	S	!	2	rrigation	4 Indu	istrial 7 L	awn and gar	den (domes	stic) 10 Monitorin	g well		
			1		bacteriolog	gical sample :	submitted to		nt? Yes No 🕽			
			submitte	ed					Water Well Disinfecte			
	OF BLANK CAS					ught Iron				NTS: Glued	Clam	ped
			MP (SR)			estos-Cemen				Welder		
2 PV		4 A	_			rglass				Threade	d Flu	ısh
Blank casin	ng diameter	2	in. to	17	ft.,	Dia	in.	to	ft., Dia	iı	n. to	ft.
Casing heig	ght above land	surface	0		in., weigh	t	0.703	lbs./f	ft. Wall thickness or	gauge No.	SCH.	40
TYPE OF S	SCREEN OR F	PERFORA	TION MATER									
1 Ste	eel		tainless steel		5 Fibe	rglass	8	RMP (SR)) 11 Othe	er (specify)		
2 Bra			alvanized ste	el	6 Con	crete tile	9	ABS	12 Non	e used (open	hole)	1
	OR PERFORA					5 Gauz			8 Saw cut		1 None (ope	n hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes												
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 17 ft. to 27 ft. From ft								ify)				
SCREEN-P	PERFORATED	INTERV	ALS: Fron	۱	1/	_ ft. to	27	ft.	From	ft. to		ft.
			Fron	۱		_ ft. to		ft.	From	ft. to		ft.
GR	RAVEL PACK I	NTERVA	LS: Fron	۱	13.5	ft. to	27.5	ft.	From	ft. to		ft.
			Fron	1		ft. to		ft.	From			
	MATERIAL:							ntonite				
Grout Intervals From 1 ft. to 13.5 ft. From ft. to ft. From								ft. to	ft.			
What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned wat												
1 Se	ptic tank		4 Late	ral lines		7 Pit privy			el storage		ell/ Gas well	
2 Set	wer lines		5 Cess	pool		8 Sewage	lagoon	12 Fer	tilizer storage	16 Othe	(specify belo	w)
3 Wa	atertight sewer	lines	6 Seep	page pit		9 Feedyar	d	13 Inse	ecticide storage			
Direction fro								How man	ny feet?			
FROM	ТО	CODE	677		OGIC LO		FROM	ТО	G	PS COORDI	NATES	
_	40					nd below 10	' ,					
0	12		dark brown			ad b		+				
12	27		Sand, fine with pebble		rse grain	ea, prown,						
27	27.5		Shale					+	+			
								,				

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was

07/08/11 completed on (mo/day/yr) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 07/27/11 Geotechnical Services Inc.

under the business name of

by (signature) Laudhu INSTRUCTIONS: Please fill in blanks and circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, 1000 S W Jackson St., Ste. 420, Topeka, Kansas 66612-1367. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.