LOCATION OF WATER	R WELL:	Fraction			Secti	ion Number	Township Number		Range Number_	
ounty: Sedg	ywick	SE 1/4	NW 1/4	SW ½	i	16	⊤ 27	s	R	1 (E)
stance and direction fror					city?					
lorth of Murdock be		-rancis and	Santa Fe St	- Wichita						
WATER WELL OWNER		Al lankaan	C4 C4- 440							_
R#, St. Address, Box # ity, State, ZIP Code	: 1000 SV	V Jackson	St., Ste. 410				Board of Agri		sion of Water	r Resource:
ty, State, ZIP Code LOCATE WELL'S LOC	TOPEKA	, NO 00012					Application N	umber:		
AN "X" IN SECTION BO	DX:	4 DEPTH OF	COMPLETED WI	ELL	25	ft. ELE	VATION:	1302	.42 (TOC)
	!	 Depth(s) Groun	COMPLETED Wildwater Encounte	red 1	15.4	l8 ft	. 2	ft.	3	ft
NW	NE	WELL'S STATI	C WATER LEVEL	15.4	8 ft. 1	below TOC	measured on mo/	day/yr	06/	29/11
;	;		np test data: We							
W	E	Est. Yield	apm: We	ell water was		1	t after	hours p	umpina	anm
x.l.		Bore Hole Diam	neter 8.25 TO BE USED AS ic 3 Feed lot	in, to	25		ft. and	in	. to	ft
sw	SE	WELL WATER	TO BE USED AS	: 5 Public	water su	ipply	8 Air condition	oning 11	Injection w	ell
		1 Domest	ic 3 Feed lot	6 Oil fiel	d water s	supply	9 Dewaterin	g 12	! Other (Spe	cify below)
S	necessaria de la constanta	2 Irrigation	n 4 Industrial	7 Lawn a	and gard	en (domesti	c) 10 Monitorin	g well		
3	,	Was a chemica	l/bacteriological s	ample subm	itted to D	epartment?	Yes No 2	(If yes,	mo/day/yr sa	ample was
		submitted					iter Well Disinfect			X
TYPE OF BLANK CAS	ING USED:		5 Wrought In	ron 8	Concre	ete tile	CASING JOI	NTS: Glued	JCl	amped
1 Steel	3 RMP (S	SR)	6 Asbestos-	Cement 9	Other (specify belo	traiscontraction from	Welde	electronic control of the control of	ENGICECTICATION NAMED COMMON CONTRACT
2 PVC	4 ABS		7 Fiberglass					Thread	led F	Flush
ank casing diameter	2	in. to	0 ft., Dia							
asing height above land	surface	0	in., weight	0.70	3	lbs./ft.	Wall thickness of	r gauge No.	SC	H. 40
PE OF SCREEN OR PI					7	PVC	10 Ast	estos-ceme	nt	
1 Steel	3 Stainles	ss steel	5 Fiberglass	3	8	RMP (SR)				
2 Brass	4 Galvani	ized steel	6 Concrete t	tile	9	ABS .		ne used (ope		
CREEN OR PERFORAT	Hartest action in	utionalism undräddess visitest Ettérato (Octobroscovic	CONTRACTOR OF STREET STREET, STREET STREET, ST	Gauzed w			8 Saw cut		11 None (o	pen hole)
1 Continuous slot		Mill slot		Wire wrap			9 Drilled hole:			
2 Louvered shutter		Key punched		Torch cut			10 Other (spe	cify)		***
CREEN-PERFORATED	INTERVALS:		10 ft. t							
		From	ft. t	0	0.5	ft. l	From	ft. to	0	ft
GRAVEL PACK IN		From	12 ft. t	0	25	ft. I	=rom	ft. to	0	ft
GROUT MATERIAL:		From	ft. t	0	- Paracental and a second	ft. I	-rom	ft. to	0	ft
GROUT MATERIAL:	1 Neat ce	ement	2 Cement grout		3 Bent	onite	4 Other			
rout Intervals From	f	t. to 12	ft. From		ft. te	0	ft. From		ft. to	ft
hat is the nearest source	•					10 Lives	tock pens		andoned wat	
1 Septic tank		4 Lateral lines					storage			
2 Sewer lines					on			16 Oth	er (specity b	elow)
3 Watertight sewer	iines	6 Seepage pi	1 9 1	Feedyard			cticide storage			
rection from well? FROM TO	CODE	LITHO	LOGIC LOG	T	FROM	How many		UGGING IN	ITERVALS	······
0 0.5		halt	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		110111		1 1	.000110111	TERMILO	
0.5 5	Cla									
5 25	Sar	1 <mark>d,</mark> medium t	o coarse graine	d						

		***************************************								***************************************
						-			····	***************************************
						 				
			**************************************			·	Coordinates	(from SE	corner o	f Sec. 16
							Northing: 1689.20			
							Westing: 40		`	
				Jan.	Karlinius (1968-1907-oct					
CONTRACTOR'S OR	LANDOWNER			well was (1)	construc	ted, (2) reco	onstructed, or (3) p	lugged unde	er my jurisdict	ion and wa
ompleted on (mo/day/yr)		07/	23/11		_ and thi	is record is t	rue to the best of	my knowled	ge and belie	f. Kansas
ater Well Contractor's L	icense No.		531	~~~~			ecord were comple	eted of (mo/	day/yr) [7/28/11
der the business name	of	Geotechn	ical Services		by	(signature)		Mod		
INSTRUCTIONS: Ple	ase fill in blanks	and circle the co	orrect answers. Sei	nd three copie	s to Kans	as Departme	nt of Health and En	virdament, Bu	reau of Water	r, 1000 S W