WATER WELL RECORD Form WWC-5 KSA 82a-1212 ID No. 0046859

1 LOCATION OF WATER WELL:			Fraction	SF	NW			Secti	on Number	r T	ownsh	ip Number		Range Nun		ber	l
	Sedg	gwick	8000	1/4	体 E				16	т	2	27	s	R	1	(E)w	
Distance and	d direction from	m nearest town					within ci	ity?								9	
		f St. Francis	and Mu	rdock	St V	Vichita											-
	WELL OWNE			٠.	٥.	440											
RR#, St. Ad	dress, Box #	: 1000 SV	V Jacks	on St	., Ste.	410						·		sion of W	ater Re	sources	
LOCATE	ZIP Code	: Topeka	, KS 66	612						Apı	plicatio	n Numl	per:				1
3 AN "X" IN	NELL'S LOC	OX:	4 DEPTH	OF CO	MPLETE	D WELL		25	ft. ELE	VATION	۷:		1303	.78 (T	DC)		
A		į c	— Depth(s) G	roundwa	ater Enco	ountered	1	16	1	ft. 2			ft.	3		ft.	유
	Nw -I					EVEL									06/29/		OFFICE
		INE				Well water										apm	m
₩ W		EE	Est. Yield			Well water											USE
-	j.,		Bore Hole	Diamete	r 8.2	25 in. to		25		ft. and	 I		in	. to		ft.	ONLY
 	sw	· se	WELL WA	TER TO	BE USE	DAS: 5 F lot 6 C	ublic w	ater su	pply	8 /	Air con	ditionin	g 1	1 Injection	n well		₹
	i	i	1 Doi	nestic	3 Feed	lot 6 C	Oil field v	water s	upply	9 1	Dewate	ering	12	2 Other (Specify	below)	İ
▼ ∟	<u>'</u> S		2 Irriç	gation	4 Indus	strial 7 L	awn an	d garde	en (domest	tic) 10	Monit	oring w	ell				
	3	Įv	Was a che	mical/ba	cteriolog	ical sample	submitte	ed to D	epartment [*]	? Yes	N	6 X	If yes,	mo/day/	yr sampl	e was	
		s	submitted						w	ater Wel	II Disin	fected?	Yes		No X		
5 TYPE OF	F BLANK CAS	ING USED:			5 Wrou	ight Iron	8 (Concre	te tile	CA	ASING	JOINTS	S: Glue	d	Clamp	ed	
1 Ste	el	3 RMP(S	R)		6 Asbe	stos-Cemen	t 9 (Other (:	specify bel	ow)	_		Weld	ed			
2 PV	С	4 ABS			7 Fiber	glass					L		Thread	ded	Flus	sh	i
Blank casing	diameter	2	in. to	10	ft., [ĺ
		surface								. Wall th	nicknes	s or ga	uge No.		SCH. 4	10	
		ERFORATION						7	PVC		10	Asbest	s-ceme	nt			
1 Ste	el	3 Stainles	s steel		5 Fiber	glass		8 1	RMP (SR)								
2 Bra		4 Galvaniz				rete tile		9 /	ABS		12	None u	sed (ope	en hole)			¬
		TION OPENING				5 Gauz		•						11 Non	e (open	hole)	
	ntinuous slot		Aill slot			6 Wire				9 D							
	vered shutter		• •			7 Torci			_	10 O	ther (s	pecify)					
SCREEN-PI	ERFORATED	INTERVALS:				ft. to											
			From ₋			ft. to			ft.	From _			ft. t	0		ft.	ᇒ
GRA	AVEL PACK I	NTERVALS:				ft. to											
													ft. t	0		ft.	1
6 GROUT	MATERIAL:	1 Neat ce	ment	2 C	ement g	rout	L	3 Bente	onite	4 Oth	er						
Grout Interv	als From	ft	. to	12	ft. Fro	m		. ft. to	•	f	ft. Fro	m		ft. to		ft.	
		e of possible co							10 Live:					andoned		ell	
	otic tank		4 Lateral	1		7 Pit privy			11 Fuel	-				well/ Gas			
	ver lines tertight sewer		5 Cess po 6 Seepag			8 Sewage 9 Feedya		1	12 Ferti				16 Oth	er (speci	ty below)	1
Direction fro	•	ines (o Seepay	e pii		э геецуа	Iu		How man		torage						
FROM	TO	CODE	Li	THOLOG	GIC LOG)	FF	ROM	TO	y ieet:		PLUG	GING IN	TERVAL	S	·	
0	0.5		halt							 							
		Clay	y, dark b	rown to	black,	some fine											SEC
0.5	9	sand															
9	25	San	d, mediu	m to co	oarse gi	rained											
							+			ļ	·····						
				-									••				
•										 							
										 							
							-to-		Coordinates (from SE corner of Se					r of Se	c. 16)		
									Northing: 1578.27 Westing: 3928.11								
										West	ing:	<u> 3928.</u>	11				1
7 00: 7	OTORIO OS	LANDOMANIES	o oppre	IOATIO!	N. T-!-		2 (4) =		-d (0)			O\! :			41.41		-
		LANDOWNER'				vater well wa											
	on (mo/day/yr)			v/123/	17				s record is						_		
		icense No.			53 I				ater Well R			npleted	or (mo/	day/yr)	07/2	8/11 د	
	usiness name	of ease fill in blanks				ices Inc.	conice 4		(signature)			Envir	Ta de	FOOU 2514	otos 100	0.6.144	
INSTRI		ase till in blanks :													ater, 100	U 3 VV	