County: Sectywick Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here
from nearest town or intersection: If at owner's address, check here \[\] 2048 S. OLIVER STREET, WICHITA, KS \[\] 2 WATER WELL OWNER: KDHE-BER RR#, Street Address, Box #: 1000 SW JACKSON STREET City, State, ZIP Code \[\] 1000 SW JACKSON STREET City, State, Z
2 WATER WELL OWNER: KDHE-BER RR#, Street Address, Box #: 1000 SW JACKSON STREET City, State, ZIP Code : TOPEKA, KS 66612-1367 □ igital Map/Photo, □ Topographic Map, ☑ Land Survey Est. Accuracy: □ <3 m, □ 3-5 m, □ 5-15 m, □ >15 m 3 LOCATE WELL WITH AN "X" IN SECTION BOX: N □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □
WITH AN "X" IN SECTION BOX: N SECTION BOX: N WELL'S STATIC WATER LEVEL. 25.68 ft. below land surface measured on mo/day/yr. Pump test data: Well water was. ft. after hours pumping. gpm Bore Hole Diameter in. to ft., and in. to ft. WELL WATER TO BE USED AS: Public water supply Geothermal Injection well Domestic Feedlot Oil field water supply Dewatering Other (Specify below according to Domestic lawn & garden Monitoring well MW7R. S S TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Molecular Threaded Casing diameter 2 in. to 29. ft., Diameter in. to ft., Diameter in. to ft. Weight Molecular ft. (2). ft. (2). ft. (2). ft. (2). ft. (3). ft. (3). ft. (3). ft. (3). ft. (4). ft. (2). ft. (2). ft. (3). ft. (3). ft. (4). ft. (2). ft. (3). ft. (3). ft. (4). ft. (2). ft. (3). ft. (4). ft. (4)
5 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded Casing diameter .2 in. to .20 ft., Diameter in. to
TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel PVC Other (Specify) Brass Galvanized Steel None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole) Louvered shutter Key punched Wire wrapped Saw cut Other (specify) SCREEN-PERFORATED INTERVALS: From 20. ft. to .40. ft., From ft. to GRAVEL PACK INTERVALS: From 18. ft. to 40. ft., From ft. to From ft. to ft., From ft. to
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☐ Other ☐ Othe
35 40 Weathered shale MW7R
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, ☐ reconstructed, or ☐ plugged under my jurisdiction and was completed on (mo/day/year) .2/1.4/2.9.12
under the business name ofCoranco Great Plains, Inc