1 LOCATIO	ON OF WATE	R WELL:	Fraction				Se	ction Number	Towr	nship Numb	er R	ange Numbe	er
		gwick			SW	14 NW	L	21	Т		l l	1	E
Distance and	d direction from	m nearest tow								-			
250 N. St		R: The Co	leman C	omna	ny Inc								
		: 3600 N			iiy, iiic	•			D		a Dhileina Ai	14/-4 D	
HH#, 51. A00	aress, box #	: Wichita	. Hydiad 2 KS 67	21Q							re, Division of	water Heso	urces
LICCATE	WELL'S LOC	ATON WITH								ation Numbe			
3 AN "X" IN	SECTION B	OX:	4 DEPTH	OF CO	MPLETED	WELL	3	8 ft. ELE	VATION:		1299.55 (1	FOC)	
↑ [Depth(s) Gi	oundwa	ter Encou	intered 1 _		f	t. 2		ft. 3		ft.
ļ .	- NW	NE	WELL'S ST	ATIC W	ATER LE	VEL 17	.34 f	t. below TOC	measured o	on mo/day/y	r	03/02/12	2
	x i	i		Pump te	est data:	Well water w	as		ft. after	h	nours pumping		gpm
<u>≅</u> W <u></u>		╅	Est. Yield		gpm:	Well water w	as		ft. after	t	nours pumping		gpm
ì l		i I I	Rore Hole [)iam <i>e</i> toi	- 8.2!	5 in to	4	Ю	ft and		in to		ft
	- sw	SE	WELL WAT	ER TO	BE USED	AS: 5 Pub	lic water ield wate	supply r supply	8 Air (conditioning	11 Inject 12 Other	tion well r (Specify by	olow)
↓ L				etion	4 Industr	del 7 Law	n and an	rdon (domost	io\ 10 M	nitoring wel		(Opecity be	310W)
	S		2 Irrig										
				nicai/bac	ctenologic	aı sample suc	militea to				If yes, mo/day		was
E TYPE OF	F BLANK CAS		submitted		E \A/	ht Iron	0 0				Yes		
			CD)		_					NG JOIN 15:	Glued	Clamped	'
1 Ste			SR)			tos-Cement					Welded	ElL	
2 PV		4 ABS			7 Fiberg	•				4	Threaded		
Blank casing	g diameter	2	in. to	28	ft., Di	ia	in.	. to	ft., Dia		in. to	COII 40	
Casing heig	ht above land	surface	U	in.	, weight	U.	/U3 T=	lbs./ft.	Wall thick	ness or gau	ge No.	SCH. 40	<u>'</u>
		ERFORATION						PVC					
1 Ste 2 Bra		3 Stainle	ess steel nized steel	;	5 Fiberg	ıass ete tile	8	ABS			oecify) ed (open hole)		
		TION OPENIN		,	o Conci	5 Gauzed			8 Saw		eu (open noie) 11 No		ole)
	ntinuous slot		Mill slot			6 Wire wr				d holes		(0 p 0	J.,
2 Lou	vered shutter		Key punche			ı 7 Torch cı			10 Othe	r (specify)			
		INTERVALS:	• •		8	ft. to	38	ft.	From	(-1,	ft. to		ft.
											ft. to		
GRA	AVEL PACK II	NTERVALS:	From	2	6	ft. to	40	ft.	From		ft. to		ft.
						ft. to							ft.
6 GROUT	MATERIAL:	1 Neat o	ement	2 C	ement ar	out	3 Be	entonite	4 Other				
 Grout Interv	als From	1	ft. to	26	ft. Fron	n	ft.	to	ft.	From	ft. to		ft.
		e of possible of			- 111 1 101	``			stock pens		14 Abandone		
1 Sep	ptic tank	•	4 Lateral	lines		7 Pit privy			storage		15 Oil well/ G	as well	
2 Sev	wer lines		5 Cess po								16 Other (spe	ecify below)	
3 Wa	itertight sewer	lines	6 Seepag	e pit		9 Feedyard		13 Inse	cticide stora	age			
Direction fro							,	How man	y feet?				
FROM	TO	CODE	ncrete	ITHOLO	GIC LOG		FROM	и то		PLUGG	ING INTERV	ALS	
0 0.5	0.5 2.5		i, dark bro	wn eoil			-						
2.5	3		an Clay,				+						
			nd, fine to										
3	32.5					el below 15'							
00.5	40	, ,	ale, orang	-									
32.5	40	mp	ced w/ sand	layers	Detwee	n 35' & 37.5'			 	 			
	 								 				
· · · · · · · · · · · · · · · · · · ·	 						 						
									GPS:				
									Northin	ıg: 16874	19.19		
										: 165047			
7 CONTRA	ACTOR'S OR	LANDOWNER				ater well was	(1) constr	ructed, (2) rec	onstructed,	or (3) plugge	ed under my ju	risdiction an	d was
	on (mo/day/yr)			03/13/						,, .	nowledge and		
Water Well	Contractor's L	icense No.			531		This	Water Well F	Record was	completed o	on (mo/day/yr)	03/26	/12
under the bu	usiness name	of	Geotec	hnica		ces Inc.		by (signature)					
											nent, Bureau of		sw