GSI Job I	No. 12706	63	14/4		D E		K04 00- 4				MW- 1	150S
1 LOOATIC		D LACE L .					Number	212 ID N	o. ship Number			
	ON OF WATE			OW	N334/				- -		ige Numb	-
County:	Sea	gwick	NE 1/4	SW 1/4	NW 1/4		21	Т	27 S	<u> </u>	1	E
Distance and 250 N. St .		m neares	town or city street a	address of well IT loc	cated within	спу?						
		B. The	Coleman Cor	npany, Inc.								
			0 N. Hydraulic					Poard o	f Agriculture, [Nivinian of M	lator Door	
171#, 31. AU	JIESS, BUX #	. Wic	hita, KS 6721	Q					•		aler nesu	uices
U OCATE	WELL'S LOC	CATON W		3				Applica	tion Number:			
3 AN "X" IN	SECTION B	OX:	4 DEPTH OF	COMPLETED WE	LL	20	ft. ELEV	ATION:	12	99.55 (TC	DC)	l
T T		l l	Depth(s) Grou	ndwater Encountere	ed 1		ft	. 2	ft.	3		ft.
	NW		WELL'S STAT	IC WATER LEVEL	17.3	5 ft.b	elow TOC I	neasured or	n mo/dav/vr		03/02/1	2
	X			mp test data: Wel								
₩ W			E Fet Vield	gpm: Wel	ll water was			t after	hour			dom.
-			Bora Hola Dia	gpin. Wei	in to	20	••••••	ft and		in to		gpin #
I	- sw	i SE	WELL WATER	neter 8.25 i TO BE USED AS: tic 3 Feed lot	5 Public	water sui	vla	8 Air c	onditionina	11 Injectio	n well	¹ L
	1	i	1 Domes	tic 3 Feed lot	6 Oil field	water s	uppiy	9 Dewa	atering	12 Other (Specify b	elow)
* L		į	2 Irrigatio	on 4 Industrial	7 Lawn a	ind garde	en (domesti	c) 10 Moi	nitoring well			
	S			al/bacteriological sa								
			submitted	an Daoronionogicali ca					infected? Yes		No X	Wus
	BLANK CAS			5 Wrought Iro		Conord			G JOINTS: GI			
	el			-							_ Clamped	
				6 Asbestos-C						elded		
2 PV0		4 AI		7 Fiberglass					Thr	eaded	Flusi	<u> </u>
Blank casing	diameter	2	in. to1	0 ft., Dia		in. to		ft., Dia		in. to		ft.
Casing heigl	ht above land	surface	0	in., weight	0.70	3	lbs./ft.	Wall thickn	ess or dauge N	lo. S	SCH. 40)
TYPE OF SC	CREEN OR P	PERFORA	TION MATERIAL:			7 F	PVC	10) Asbestos-ce	ment		
1 Ste	el	3 S1	ainless steel	5 Fiberglass 6 Concrete til		8 F	RMP (SR)	11	Other (speci	fy)		
2 Bra:			alvanized steel	6 Concrete til	ie	94	4B2	12	2 None usea (open nole)		
			NINGS ARE:	5				8 Saw c	ut	11 Non	e (open h	ole)
1 Cor	ntinuous slot		3 Mill slot					9 Drilled				
	ivered shutter		4 Key punched					10 Other	(specify)			
SCREEN-PE	ERFORATED	INTERV	ALS: From	10 ft. to		20	ft. I	From		ft. to		ft.
			From	ft. to			ft. I	From		it. to		ft.
GR/	VEL PACK I	NTERVA	.S: From	8 ft. to		20	ft. I	From		ft. to		ft.
										ft. to		
6 GROUT	MATERIAL:	1 N	eat cement	2 Cement grout		3 Bento	onite	4 Other				
Grout Interv	als From	1	ft. to 8	ft From		ft to				ft to		
			ble contamination:			1. 10	10 lives	tock pens	14	Abandoned	water wel	¹ Li
	ntic tank		4 Lateral line		it privy		11 Fuel			Oil well/ Gas		
•	ver lines		5 Cess pool		ewage lago	on		izer storage		Other (speci		
	tertight sewer	lines	6 Seepage p		eedyard			ticide stora			,	
Direction fro					,		How many					
FROM	ТО	CODE	LITH	OLOGIC LOG		FROM	то		PLUGGING		S	
0	0.5		Concrete									
0.5	2.5		Fill, dark brown									
2.5	3		Lean Clay, sil									
				barse grained, lig								
3	20	ļ	brown to dark br	own, w/ gravel be	elow 15'							
		 										
		 										
	· · · · · ·	<u> </u>										
								GPS:		<u></u>		
	L								g: 168751.	54		
		+							: 1650471.			
			NER'S CERTIFICA			oonete :	od (2) more				diation	
completed o	m (mo/day/yr)		03	E04					est of my know			
). 	531					ompleted on (r	no/day/yr)	03/26	V12
	usiness name			ical Services		by	(signature)	M				
Jackson	n St., Ste. 420,	ease fill in l Topeka, K	blanks and circle the c ansas 66612-1367. T	elephone: 913-296-5	5545. Send c	ne to WA	TER WELL	DWNER and	retain one for yo	, Bureau of W our records.	vater, 1000	SW

SEC