WATER WELL RECORD Form WWC-5 KSA 82a-1212 ID No.

1 LOCATION OF WATER WELL:			Fractio	n				Sec	tion Number	То	Township Number		Range Number		
	Sed								21	Т	27	s	R	1	E
	d direction fro														
	WELL OWNE	D. The Co	oleman	Comr	any Ir	<u> </u>									
	dress, Box#				any, n	IC.				Dage		Dis	:-:4 14	/ D	
City State 7	ZIP Code	· Wichit	a KS 6	7219									ision of W	ater Resou	ırces
LOCATE	WELL'S LOC	ATON WITH	a, No u	7213						Аррі	ication Nur	noer:			
3 AN "X" IN	SECTION B	OX:	DEPT	H OF C	OMPLETI	ED WELL		40	ft. ELE	VATION:		1299	9.48 (TC	OC)	
₹		Ţ	Depth (s) Groundwater Encountered 1 ft. 2 ft. 3										ft.		
L	- NW	. NE	WELL'S	STATIC	WATER I	LEVEL	17.82	ft.	below TOC	measure	d on mo/da	v/vr		03/02/12	ft.
	X	;													anm
₩ W		_ <u>.</u> E	Fet Vield		anm	· Well wate	ar was		1	ft after		houre r	numping		apm
-			Bore Hole	Diame	er 8	25 in to	or was	40	' D	ft and	••••	ii	outiping o to	•••	gpm gpm ft.
 	- sw	SE	WELL W	ATER TO	O BE USE	ED AS: 5	Public w	ater s	0 upply supply	R Ai	ir condition		1 Injection	on well	ا ۱۰۰۰
	i	i	1 D	omestic	3 Feed	d lot 6	Oil field	water	supply	9 D	ewatering	1	2 Other ((Specify be	low)
† <u>L</u>	_ii	لسل	2 lm	igation	4 Indu	strial 7	Lawn an	d gard	den (domesti	ic) 10 I	Monitorina	well			.
	S								Department?						vae
			submitted			giodi odiripio	000				Disinfected				-us
5 TYPE OF	BLANK CAS	ING USED:	1000		5 Wro	ught Iron	8	Concr			SING JOIN				$\neg \neg$
1 Ste		3 RMP	(CD)						(specify belo			Weld		Ciampeu	
		_	(OH)							•				Elizab	
2 PV		4 ABS			7 Fibe	•						Threa	ded	Flush	
Blank casing	g diameter	2	in. to	30	ft.,	Dia		in. 1	to	ft., Dia	a 		_in. to		ft.
Casing heigh	ht above land	surface	0	ا ـ ـ ـ ـ ـ ـ أ	n., weigh	t	0.703	- -	lbs./ft.	Wall thic	kness or g	auge No.		SCH. 40	
TYPE OF SO	CREEN OR P	ERFORATIO	N MATERI	AL:				7	PVC		10 Asbes	stos-ceme	ent		- 1
1 Ste	el	3 Stainle			5 Fibe	erglass		8	RMP (SR)		11 Other	(specify)			
2 Bra			nized steel		6 Con	crete tile		9	ABS		12 None	used (op	en hole)		
	R PERFORAT												11 Non	ne (open ho	le)
	ntinuous slot	-				6 Wire					lled holes				
	vered shutter					7 Tord				10 Ott	her (specif	y)			
SCREEN-PE	ERFORATED	INTERVALS							ft.						
			From			ft. to			ft. I	From		ft. 1	to		ft.
GR/	AVEL PACK II	NTERVALS:	From		28	ft. to		40	ft. (From		ft. 1	to		ft.
									ft. i						ft.
6 GROUT	MATERIAL: als From	1 Neat	cement	2	Cement (grout		3 Ber	ntonite	4 Othe	r				
Grout Interva	als From	1	ft. to	28	ft. Fr	om	_	ft.	to	ft.	. From		ft. to		ft.
	nearest sourc								10 Lives					water well	
1 Sep	otic tank	•	4 Latera	al lines		7 Pit priv	у		11 Fuel	storage		15 Oil	well/ Gas	s well	
2 Sev	ver lines		5 Cess	pool			-		12 Ferti	-			her (spec	ify below)	
3 Wat	tertight sewer	lines	6 Seepa	age pit		9 Feedya	ard		13 Insec	cticide sto	orage			•	
Direction fro	m well?								How many	feet?					
FROM	TO	CODE		LITHOL	OGIC LO	G		ROM	ТО		L	THOLOG	SIC LOG		
0	0.5		oncrete					39	40	Shale	, black				
0.5	4		ay, dark												
4	_		-	ium gra	ained, w	ell sorted,									
<u>4</u> 5	5 6		ay, silty												
5 6	9		ay, sirty I nd , med	ium an	ained	oli eostad			-	ļ					
9	10		ay, brow		airied, W	eli sorted	-								
-	10		ind, fine		se grain	ed well	+		-						
10	30		rted	coal	Je graili										
30	31		nale, oliv	e						<u> </u>					
31	35		ınd, coar		ned to a	ravel				GPS:					
35	36.5					blue & bla	ck				ing: 168	6546.8	8		
36.5	39	Sa	ind, coar	se grai	ned, pod	orly sorted				Eastir	ng: 1650	467.91			
	CTOR'S OR							onstru	cted, (2) reco					sdiction and	was
	n (mo/day/yr)			03/1:	3/12				nis record is t						
		iconce Ne		557 10	531										
	Contractor's L	icense No.			- 33 I	ilaga Inc			Vater Well R		s complete	a on (mo	/day/yr)	U3/20/	14
	usiness name UCTIONS:. Ple					ices Inc.			y (signature)		h and 5-1	onmant P		later 4000	2 141
	n St., Ste. 420.													valer, 1000 S	5 VV