GSI Job No. 127063

LOCATION OF WATER WELL: Fraction Section Number Township Number	Range Number
punty: Sedgwick NE ¼ SW ¼ NW ¼ 21 T 27 S	<u>R 1 E</u>
stance and direction from nearest town or city street address of well if located within city? 50 N. St. Francis	
WATER WELL OWNER: The Coleman Company, Inc.	
R#, St. Address, Box # : 3600 N. Hydraulic Board of Agriculture, Divis	ion of Water Resources
ity State ZIP Code • Wichita, KS 67219 Application Number:	
LOCATE WELL'S LOCATON WITH	94 (TOC)
AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL 38 ft. ELEVATION: 1298.	
Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 WELL'S STATIC WATER LEVEL 16.83 ft. below TOC measured on mo/day/yr	
X Pump test data: Well water was ft. after hours pump test data: W E Est. Yield gpm: Well water was ft. after hours pump test data:	
Bore Hole Diameter 8,25 in to 40 ft and in	to ft.
Bore Hole Diameter 8.25 in. to 40 ft. and in. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12	Injection well
1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12	Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well	
S Was a chemical/bacteriological sample submitted to Department? Yes No X If yes,	mo/day/yr sample was
submitted Water Well Disinfected? Yes	No X
TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued	Clamped
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welde	¥d
2 PVC 4 ABS 7 Fiberglass Thread	ed Flush
Blank casing diameter 2 in. to 28 ft., Dia in. to ft., Dia	
casing height above land surface 0 in., weight 0.703 lbs./ft. Wall thickness or gauge No.	SCH. 40
YPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cemer	nt
1 Steel 3 Stainless steel 5 Fiberolass 8 RMP (SR) 11 Other (specify)	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (ope	n hole)
CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut	11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes	
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)	
CREEN-PERFORATED INTERVALS: From 28 ft. to 38 ft. From ft. to)ft.
From ft. to ft. From ft. to	۵tt.
GRAVEL PACK INTERVALS: From 26 ft. to 40 ft. From ft. to	
From ft. to ft. From ft. to	
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other	
arout Intervals From 1 ft. to 26 ft. From ft. to ft. From	ft. to ft.
Vhat is the nearest source of possible contamination: 10 Livestock pens 14 Aba 1 Outline table 11 Final statement 15 Oil	
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Oth	vel/ Gas well er (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage	er (specily below)
Direction from well?	
FROM TO CODE LITHOLOGIC LOG FROM TO PLUGGING IN	TERVALS
0 0.5 Concrete	
Fill, dark brown soll, medium grained	
0.5 2.5 Fill, dark brown soll, medium grained sand	
Fill, dark brown soll, medium grained 0.5 2.5 2.5 5 Lean Clay, silty	
0.5 2.5 Fill, dark brown soil, medium grained sand 2.5 5 Lean Clay, silty Sand, medium to coarse grained, well	
0.5 2.5 Fill, dark brown soll, medium grained sand 2.5 5 Lean Clay, silty 5 14 to mixed sorted	
0.5 2.5 Fill, dark brown soll, medium grained sand 2.5 5 Lean Clay, silty 5 14 Sand, medium to coarse grained, well to mixed sorted 14 15 Clay, brown Sand, fine to coarse grained, with Sand, with	
0.5 2.5 Fill, dark brown soll, medium grained sand 2.5 5 Lean Clay, silty 5 14 to mixed sorted 14 15 Clay, brown 5 25 Sand, fine to coarse grained, well to mixed sorted 15 25 gravel between 19' and 22'	
0.5 2.5 Sand 2.5 5 Lean Clay, silty 2.5 5 Lean Clay, silty 5 14 to mixed sorted 14 15 Clay, brown 5 25 gravel between 19' and 22' 25 33 Sand, coarse grained, poorly sorted	
0.52.5Fill, dark brown soll, medium grained sand2.52.5Sand2.55Lean Clay, silty514to mixed sorted1415Clay, brown1525gravel between 19' and 22'2533Sand, coarse grained, poorly sorted3334Shale, olive	
0.52.5Fill, dark brown soll, medium grained sand2.52.5Sand, silty2.55Lean Clay, silty514to mixed sorted1415Clay, brown1525gravel between 19' and 22'2533Sand, coarse grained, poorly sorted3334Shale, olive3436.5Sand, fine to medium grained	
0.52.5Fill, dark brown soll, medium grained sand2.55Lean Clay, silty2.55Lean Clay, silty514to mixed sorted1415Clay, brown1525gravel between 19' and 22'2533Sand, coarse grained, poorly sorted3334Shale, olive3436.5Sand, fine to medium grained2540Shale, olive to black	
0.5 2.5 sand 2.5 5 Lean Clay, silty 5 14 to mixed sorted 14 15 Clay, brown 15 25 gravel between 19' and 22' 25 33 Sand, coarse grained, poorly sorted 33 34 Shale, olive 34 36.5 Sand, fine to medium grained 26.5 40 Shale, olive to black	er my jurisdiction and was
0.5 2.5 sand 2.5 5 Lean Clay, silty 5 14 to mixed sorted 14 15 Clay, brown 15 25 gravel between 19' and 22' 25 33 Sand, coarse grained, poorly sorted 33 34 Shale, olive 36.5 40 Shale, olive to black 7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, or (3) plugged unde completed on (mo/day/yr)	er my jurisdiction and was ge and belief. Kansas
0.5 2.5 sand 2.5 5 Lean Clay, silty 2.5 5 Lean Clay, silty 5 14 to mixed sorted 14 15 Clay, brown 15 25 gravel between 19' and 22' 25 33 Sand, coarse grained, poorly sorted 33 34 Shale, olive 34 36.5 Sand, fine to medium grained 36.5 40 Shale, olive to black 7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, or (3) plugged under the source of the	er my jurisdiction and was ge and belief. Kansas