WATER WELL RECORD	Form	wWC-5	Division of Wate	r Resources App. No	).
1 LOCATION OF WATER WELL!  County: Suggestion	Fraction 1/ SW1/	NE1/4 NU/4	Section Number	Township No.	Range Number R
Street/Rural Address of Well Location	if unknown, distar	nce & direction	Global Positioning	System (GPS) in	formation:
from nearest town or intersection: If at owner's address, check here . Latitude:					
2027 WZ	Elevation:				
2 WATER WELL OWNER: 7702	Datum: WGS 84, NAD 83, NAD 27 Collection Method:				
2 WATER WELL OWNER: AND Killings RR#, Street Address, Box #: 2027 w 27 the			GPS unit (Make/Model:)  Digital Map/Photo, Topographic Map, Land Survey		
City, State, ZIP Code : w.j.	hit Ks	67204	Est. Accuracy:  <	3 m, 3-5 m,	5-15 m,  >15 m
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF	COMPLETED V	vell 3	<b>E</b> ft.		
WITH AN "X" IN SECTION BOX:  N  Depth(s) Groundwater Encountered (1) ft. (2) ft. (3) ft. (3) ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr. 7.72					
WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr					
EST. YIELDgpm. Well water wasft. after hours pumping					
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well					
Sw Sp Domestic Feedlot Oil field water supply Dewatering Other (Specify below)					
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well					
S If yes, mo/day/yr sample was submitted					
	infected?  Yes	/\			
5 TYPE OF CASING USED: Steel Y PVC Other O					
CASING JOINTS: A Glued Clamped Welded Threaded Casing diameter in. to ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface in., Weight libs./ft., Wall thickness or gauge No.					
Casing height above land surface					
Steel Stainless Steel X PVC Other (Specify)					
Brass Galvanized Steel None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:					
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole) Louvered shutter Key punched Wire wrapped Saw cut SCREEN-PERFORATED INTERVALS: From ft. to ft., From ft. to ft.					
SCREEN-PERFORATED INTERVALS	: From	Saw cur	ft., From	ft.	to ft.
	From	ft. to		ft.	to ft.
GRAVEL PACK INTERVALS	From	ft. to	ft., From	ft.	to ft.
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other					
Grout Intervals: From					
☐ Septic tank ☐ Lateral	lines   Pit privy	oon Livestock j		e storage	ner (specify below)
Sewer lines Cesspoor Watertight sewer lines Seepage		Fertilizer s	torage 🗖 Oil well/g	as well	
Direction from well LITHOLO	GIC LQG/2	Distance FROM		OG (cont.) or PLI	JGGING INTERVALS
FROM TO LITHOLO	Seel 0	1 KOW	10 Ellino. E	00 (cont.) <u>or</u> 1 2 c	OGING INTERVALIS
9 18 Fine 1		nd /			
18 36 Earse_	lay se				
7 CONTRACTOR'S OR LANDOWN	ER'S CERTIFICA	TION: This wat	er well was <b>X</b> const	ructed, [] reconst	ructed, or  plugged
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was X constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) and this record is true to the best of my knowledge and belief.  Kansas Water Well Contractor Dicense No This Water Well Record was completed on (mo/day/year)					
under the business name of					
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.					
Telephone 785-296-5524. Send one copy to W	ATER WELL OWNER	R and retain one for	your records. Include fe	ee of \$5.00 for each	constructed well. Visit us at
http://www.kdheks.gov/waterwell/index.html. KSA 82a-1212					