WATER WELL RECORD F	orm WWC-5 K	SA 82a-1212	
1 LOCATION OF WATER WELL: FRACTION	SECTION NUMBER		RANGE NUMBER
Sedgwick NW 1/4 SE 1/4 SW	1/4 29	T 27 S	R 1E E/W
Distance and direction from nearest town or city street address of well if located within city?  1317 S. Osage  Wichita, Kansas			
2 WATER WELL OWNER: BETZEN TRENCHING			
RR#,ST. ADDRESS,BOX #: 1410 S. Walnut		Board of Ag	riculture, Division of Water Resource
CITY, STATE: Wichita, Kansas	ZIP CODE:	Application Nu	mber:
3 LOCATE WELL'S LOCATION 4 DEPTH OF COMPLETED WELL:	8 ft.	ELEVATION:	
WITH AN "X" IN SECTION BOX: N Depth of groundwater Encountered:	ft.	ft.	ft.
WELL'S STATIC WATER LEVEL 15	FT. BELOW LAND SU	JRFACE MEASURED ON mo/	/day/yr: 5/2/12
Pump test data: Well wat	ter was	ft. after hour	s of pumping @ gpm
Est. Yield: gpm Well wa			rs of pumping @ gpm
Bore Hole Diameter 12 in.  WELL WATER TO BE USED AS:	to 38 ft.		to ft. ing 11. Injection well
	ter supply 7. Lawn a	and garden only 9. Dewater	12. Other (Specify below)
2. Irrigation 4. Industrial 6. Oil field w	ater supply 8. Air cor		ing well
S Was a chemical/bacteriological sample submitted to I submitted		NO ; If yes, Vater Well Disinfected?	what mo/day/yr was sample YES NO
5 TYPE OF CASING USED:	9. Other (Specify		Glued Threaded
1. Steel 3. RPM (SR)	SDD 36	DEIDH) CASING SOINTS.	Welded Clamped
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete to	ile SDR-20		
Blank casing diameter 5 in. to 25 ft., Dia.	in. to	ft., Dia.	in. to ft.
Casing height above land surface: 12 in., Weight:	2.35 lbs. / ft.	Wall thickness or gau	ige No214
TYPE OF SCREEN OR PERFORATION MATERIAL:  1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC	9. ABS	11. Other (specify)	
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR)	10. Asbestos-Cer		ı hole)
SCREEN OR PERFORATION OPENINGS ARE:			,
1. Continuous slot 3. Mill slot 5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None ( open hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped	8. Saw cut	10. Other (specify)	, , , , , , , , , , , , , , , , , , , ,
		_	
SCREEN - PERFORATION INTERVAL From 25 ft. to		From ft.	to ft.
GRAVEL PACK INTERVALS: From 24 ft. to		From ft. From ft.	to ft.
From ft. to	,	_	to ft.
	,		to ft.
GROUT MATERIALS: 1. Neat cement 2. Cement Grout Grout Intervals: From 4 ft. to 24 ft., From	3. Bentonite ft. to		tonite hole plug  ft. to ft.
What is the nearest source of possible contamination:	-	ft., From	
1. Septic tank 4. Lateral lines	0. Livestock pens	13. Insecticide storage	15. Oil well/Gas well
2. Sewer lines 5. Seas 1 Sol	11. Fuel storage	14. Abandon water well	16. Other (specify below)
Watertight sewer line 6. Seepage plt 9. Feed yard     Direction from well? West	12. Fertilizer storage	How many feet? 10	ft plus
From To LITHOLOGIC LOG	From To		OGIC LOG
0 3 topsoil		2111102	<u> </u>
3 8 clay			
8 15 fine sand			
15 35 medium sand 35 38 grey shale			
35 Jo gity man.			
7 Contractor's or Landowner's Certification: This water well was 1. constructed	2. reconstructed	or 3. plugged	under my jurisdiction and
was completed on (mo/day/year)  5/2/2012  and this record is true to the best of my knowledge and belief.			
Kansas Water Well Contractor's License No. 236  This water well record was completed on (mo/day/year)  5/4/2012			
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp			