	WATER WELL	RECORD F	form WV	VC-5 P	(SA 82a-121	2		
1 LOCATION OF WATER WELL:	FRACTION		1	TION NUMBE			RANGE N	
Sedgwick	NW 1/4 NE	.,.	1/4	14	T 33		R 11	E/W
Distance and direction from nearest town or city 3701 E. 13th N.					2	.7		
	Wichita, Kar TON CONSTRUC							
	S. West					Board of Agric	ulture, Division of V	Vater Resource
	iita, Kansas		ZI	P CODE:		Application Numl	ber:	
3 LOCATE WELL'S LOCATION 4	DEPTH OF PANIL 990	ELL: 10			ELEVATION:			
WITH AN A IN SECTION BOX:	oth of groundwater Encou	•	ft.			ft.		ft.
	ELL'S STATIC WATER LE		FT. BELO	W LAND S	URFACE MEASU	RED ON mo/da	ay/yr: 10/1	
NWNE	Pump test	data: Well wat			ft. after		of pumping @	gpn
₩ W E B	Est. Yield: gpi	m Well wa	ter was		ft. after	hours	of pumping @	gpm
	ore Hole Diameter	in.	to	f	and	in.	to	ft.
	ELL WATER <b>USS</b> USEI . <b>Domestic</b> 3. Feedlo		ter sunniv	7. Lawn	and garden only	> 9. Dewaterin	9	ction well
	Irrigation 4. Indust					10. Monitoring	12. Other (S g well	pecify below
_	/as a chemical/bacteriological			YES	NO		hat mo/day/yr v	•
	bmitted			Was	Water Well Disinfo	ected?	YES	<b>NO</b>
5 TYPE OF CASING USED: 1. Steel 3. RPM (SF	5. Wrought Iron	7. Fiberglass	9. O	her (Specif	y below) CAS	ING JOINTS:	Glued	Threaded
2. PVC 4. ABS	6. Asbestos-Ceme	nt 8. Concrete ti	le				Welded	Clamped
	in. to	ft., Dia.	in.	to	ft., [	Dia. ir	ı, to	ft.
Casing height and surface:	36 in.,	Weight:		os. / ft.		ckness or gauge		ι.
TYPE OF SCREEN OR PERFORATION	111.1	weight.	"	JS. / IL.	waii iiii	ckness or gauge	e No.	
Steel 3. Stainless Steel	5. Fiberglass	7. PVC	9. A	BS	11. Oth	er (specify) N	//A	
2. Brass 4. Galvanized	6. Concrete Tile	8. RMP (SR)	10. A	sbestos-Ce	ment 12. No	ne used (open h	nole)	
SCREEN OR PERFORATION OPENING	SS ARE:							
1. Continuous slot 3. Mill slo	ot 5. Gauzed	wrapped	7. <b>To</b>	rch cut	9. Drille	ed holes	11. None ( d	pen hole)
2. Louvered shutter 4. Key pu	unched 6. Wire wr	apped	8. <b>Sa</b>	w cut	10. Othe	r (specify) N/	A	
SCREEN - PERFORATION INTERVAL	From	ft. to		ft.,	From	ft.	to	ft.
	From	ft. to		ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS:	From	ft. to	1	ft.,	From	ft.	to	ft.
	From	ft. to		ft.,	From	ft.	to	
6 GROUT MATERIALS: 1. Neat of		ement Grout				Other	10	ft.
Grout Intervals: From 3	ft. to 23	ft., From	ft.	Bentonite	ft.,	From	ft. to	ft.
What is the nearest source of possible co	ntamination:				•			
1. Septic tank 4. Lateral		•	0. Livestoc	•		ide storage	15. Oil well/0	
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 17			1. Fuel storage		14. Abandon water well		16. Other (specify below) None Apparent	
3. Watertight sewer line 6. Seepag	ge pit 9 Feed y	/ard 1	2. Fertilizer	storage			None Ap	parent
Direction from well?  From To	LITHOLOGIC LOC		From	To	How ma	<u> </u>	CICLOC	
FIGHT 10	LITHOLOGIC LOC	3	From	<u>To</u>	topsoil comp	LITHOLO	GIC LOG	
			3	23	bentonite ho			
			23	100	chlorinated			
			ļ					
			<b>†</b>		-			
			<del> </del>					
7 Contractor's or Landowner's Certific	cation: This water well wa	s 1. constructed	2. re	constructe	d or 3. C	lugged u	nder my jurisdict	ion and
was completed on (mo/day/year)	10/17/2012	and this record	is true to the	best of my	knowledge and b	elief.		
Kansas Water Well Contractor's Licens	se No. 236	This water we	ell record wa	s complete	d on (mo/day/year	10/18/	/2012	
under the business name of Harp Well and Pump Service by (signature)  Todd S. Harb								