

1	LOCATION OF WATER WELL: <b>Sedgwick</b>	FRACTION <b>NW 1/4 SE 1/4 NE 1/4</b>	SECTION NUMBER <b>34</b>	TOWNSHIP NUMBER <b>T 27 S</b>	RANGE NUMBER <b>R 1E E/W</b>
---	--	---	-----------------------------	----------------------------------	---------------------------------

2	WATER WELL OWNER:	<b>HERMANN, Richard</b>	
	RR#,ST. ADDRESS,BOX #:	<b>2105 S. Chautauqua</b>	Board of Agriculture, Division of Water Resource
	CITY, STATE:	<b>Wichita, Kansas</b>	Application Number:
		ZIP CODE:	

4 DEPTH OF COMPLETED WELL: 37 ft. ELEVATION:

Depth of groundwater Encountered: ft. ft. ft.

WELL'S STATIC WATER LEVEL 10 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr. 3/25/13

Pump test data: Well water was ft. after hours of pumping @ gpm

Est. Yield: gpm Well water was ft. after hours of pumping @ gpm

Bore Hole Diameter 12 in. to 37 ft. and in. to ft.

WELL WATER TO BE USED AS:

1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 9. Dewatering 11. Injection well

2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 12. Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted

Was Water Well Disinfected? YES NO

5	TYPE OF CASING USED:			5. Wrought Iron	7. Fiberglass	9. Other (Specify below)	CASING JOINTS:	Threaded
	1. Steel	3. RPM (SR)					Glued	
	2. PVC	4. ABS	6. Asbestos-Cement	8. Concrete tile	SDR-26		Welded	Clamped
	Blank casing diameter		5 in.	to 24 ft.,	Dia.	in.	to ft.,	Dia. in. to ft.
	Casing height above land surface:		12 in.,	Weight:	2.35 lbs. / ft.	Wall thickness or gauge No.		.214
	TYPE OF SCREEN OR PERFORATION MATERIAL:							
	1. Steel	3. Stainless Steel	5. Fiberglass	7. PVC	9. ABS	11. Other (specify)		
	2. Brass	4. Galvanized	6. Concrete Tile	8. RMP (SR)	10. Asbestos-Cement	12. None used (open hole)		

SCREEN OR PERFORATION OPENINGS ARE:											
1. Continuous slot		3. Mill slot		5. Gauzed wrapped		7. Torch cut		9. Drilled holes		11. None ( open hole)	
2. Louvered shutter		4. Key punched		6. Wire wrapped		8. Saw cut		10. Other (specify)			
SCREEN - PERFORATION INTERVAL		From	24	ft.	to	37	ft.,	From	ft.	to	ft.
		From		ft.	to		ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS:		From	24	ft.	to	37	ft.,	From	ft.	to	ft.
		From		ft.	to		ft.,	From	ft.	to	ft.

6	GROUT MATERIALS:										
	1. Neat cement		2. Cement Grout		3. Bentonite		Other <b>bentonite hole plug</b>				
	Grout Intervals:	From <b>4</b> ft.	to <b>24</b> ft.,	From	ft.	to	ft.,	From	ft.	to	ft.
	What is the nearest source of possible contamination:										
	1. Septic tank		4. Lateral lines		7. Pit privy		10. Livestock pens		13. Insecticide storage		15. Oil well/Gas well
	2. Sewer lines		5. Cess Pool		8. Sewage lagoon		11. Fuel storage		14. Abandon water well		16. Other (specify below)
	3. Watertight sewer line		6. Seepage pit		9. Feed yard		12. Fertilizer storage				
	Direction from well? <b>West</b>					How many feet? <b>10 ft. plus</b>					

[illegible]

*Todd S. Harp*