WATER WELL RECORD Form WWC-5 KSA 82a-1212 LOCATION OF WATER WELL: SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER FRACTION SW 1E Sedgwick 1/4 NW1/4 NW 1/4 26 27 S E/W Distance and direction from nearest town or city street address of well if located within city? 630 S. Hillside Wichita, Kansas ZEDICK CARTIOLOGY WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 630 S. Hillside Wichita, Kansas CITY, STATE: Application Number: ZIP CODE: LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 37 4 DEPTH OF COMPLETED WELL: ft. **ELEVATION:** ft. ft. ft. Depth of groundwater Encountered: WELL'S STATIC WATER LEVEL 15 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 5/22/13 Pump test data: Well water was ft. after hours of pumping @ gpm NE NW Est. Yield: Well water was ft. after hours of pumping @ gpm Mile gpm 12 to 37 Bore Hole Diameter ft. and in. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE-1. Domestic 3. Feedlot 12. Other (Specify below) 10. Monitoring well 6. Oil field water supply 8. Air conditioning 2. Irrigation 4. Industrial ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? NO (YES) NO submitted Was Water Well Disinfected? 5 TYPE OF CASING USED: CASING JOINTS: Glued Threaded 9. Other (Specify below) 5. Wrought Iron 7. Fiberglass 3. RPM (SR) 1. Steel Welded Clamped SDR-26 6. Asbestos-Cement 8. Concrete tile 4. ABS 2. PVC 5 ft., 23 Dia. Blank casing diameter in. to ft., in. to Dia in. to ft. Casing height above land surface: 12 Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 9. ABS Stainless Steel 5. Fiberglass 1 Steel 12. None used (open hole) 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 2. Brass 4. Galvanized SCREEN OR PERFORATION OPENINGS ARE 11. None (open hole) 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 1. Continuous slot 8. Saw cut 10. Other (specify) 2. Louvered shutter 4. Key punched 6. Wire wrapped 23 SCREEN - PERFORATION INTERVAL ft 37 From to ft., From ft. to ft. tó ft., From From ft ft. to 23 GRAVEL PACK INTERVALS: ft. to 37 ft., From ft From to fť. From ft. to ft., From to ft. **GROUT MATERIALS:** Other bentonite hole plug 6 1. Neat cement 2. Cement Grout 3. Bentonite Grout Intervals: From ft. 24 ft.. From ft From ft. to ft... What is the nearest source of possible contamination: 10. Livestock pens 15. Oil well/Gas well 7. Pit privy 13. Insecticide storage 4. Lateral lines 1. Septic tank 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 5 Cess Pool 2. Sewer lines 3. Watertight sewer line 6
Direction from well? East 9. Feed yard 12. Fertilizer storage 6. Seepage pit How many feet? 10 ft. plus Direction from well? LITHOLOGIC LOG LITHOLOGIC LOG From From Τо Tο 0 3 topsoil 3 20 clay 20 55 medium sand 25 37 gray shale under my jurisdiction and Contractor's or Landowner's Certification: This water well was 1. Constructed 2. reconstructed plugged

5/22/2013 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. This water well record was completed on (mo/day/year) 5/28/2013 Kansas Water Well Contractor's License No. 236 Todd S. Harp under the business name of Harp Well and Pump Service by (signature)