L. L. CONTION OF WATER WATER		LL RECORD	Lect	<del></del>	TOWNSHIP		RANGE NUM	ARED 1
1 LOCATION OF WATER WELL:	FRACTION STE	SW 1/4 NE	l l	ON NUMBER	TOWNSHIP T <b>27</b>			
Sedgwick  Distance and direction from nearest town or city	SE 1/4		1/4	6	T 27	S	R 1E	E/W
1		f located within city?						
	ichita, Kansas							<u> </u>
151	NNING, Mac					Board of Agri	culture, Division of Wa	ter Resource
1	2 N. Porter					Dodina or rigin	001010101010101	
CITY, STATE: Wic	hita, Kansas	تنجا شخط واسلوار فهار والوارد التركي وأرسانه		CODE:		Application Nun	nber:	
	DEPTH OF COMPL	ETED WELL:	<b>40</b> ft.		ELEVATION:			
WITH AN "X" IN SECTION BOX:	epth of groundwater	Encountered:	ft:			ft.		ft,
	ELL'S STATIC WAT	TER LEVEL 14	FT. BELOV	N LAND SUF	RFACE MEASU	RED ON mo/o	day/yr: 6/1/1	.3
NWNE			vater was		ft. after		of pumping @	gpm
	Est. Yield:	The state of the s	vater was		ft, after		of pumping @	gpm
W W W	Bore Hole Diameter	12 in.	to 4	<b>0</b> ft.	and	in.	to	ft.
	ELL WATER TO BE	USED AS:				9. Dewateri	na 11. Inject	ion well
	1. Domestic 3. I	Feedlot 5. Public v	water supply	7. Lawn ar	nd garden only	> 5000000000000000000000000000000000000	12. Other (Spe	cify below)
	2. Irrigation 4. I	ndustrial 6. Oil field	water supply	8. Air cond	litioning	10. Monitorin	ng well	,
S	Was a chemical/bacteri	ological sample submitted t	o Department?	YES	NO		what mo/day/yr wa	
SI	ubmitted	·····		Was W	ater Well Disinfe	ected?	YES NO	)
5 TYPE OF CASING USED:	5. Wrought I	ron 7. Fiberglas	ss 9. Ott	her (Specify	below) CASI	NG JOINTS: (	Glued	Threaded
1. Steel 3. RPM (S	SR) -	•	CDE	826			Welded	Clamped
2. PVC 4. ABS	6. Asbestos		e tile SDT					
Blank casing diameter 5	in. to 3	30 ft., Dia.	in.	to	ft., C	Dia.	in. to	ft.
Casing height above land surface:	12 in.,	Weight:	<b>2.35</b> Ib	s. / ft.	Wall this	ckness or gaug	ge No214	
TYPE OF SCREEN OR PERFORATION								
1. Steel 3. Stainless Steel	5. Fiberglass	7. PVC	9. A	38	11. Oth	er (specify)		
2. Brass 4. Galvanized	6. Concrete Ti	le 8. RMP (SR	R) 10. As	sbestos-Cem	ent 12. Nor	ne used (open	hole)	
	ICC ARE.							
SCREEN OR PERFORATION OPENIN  1. Continuous slot  3. Mill s		auzed wrapped	7 To	ch cut	0 Drille	ed holes	11. None ( op	en hole)
			-				i i. Holle ( op	in inote;
2. Louvered shutter 4. Key i	punched 6. V	Vire wrapped	(8, Sa)	v cut	10. Othe	r (specify)		•
SCREEN - PERFORATION INTERVAL	From	<b>30</b> ft.	to 40	ft.,	From	ft.	to	ft.
	From	ft.	to	ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS:		<b>24</b> ft.	to <b>40</b>		From	ft.		
GRAVEL FACK INTERVALS.	From			ft.,			to	ft.
	From	ft.	to	ft.,	From	ft.	to	ft,
6 GROUT MATERIALS: 1. Nea	t cement	2. Cement Grout	3	Bentonite		Other ben	tonite hole plu	ig
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.								
What is the nearest source of possible contamination:						الفندء		
1. Septic tank 4. Lateral lines								
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)								
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage								
Direction from well? East		<u> </u>			How ma	ny feet? 10		<u></u> .
From To	LITHOLOGIC	CLOG	From	То		LITHOLO	OGIC LOG	
0 3 topsoil								
3 8 clây								
8 20 fine sand								
20 40 medium san	id							
						<del></del>		
				<u> </u>				
7 Contractor's or Landowner's Cert				constructed		plugged	under my jurisdicti	on and
7 Contractor's or Landowner's Cert was completed on (mo/day/year)	tification: This water 6/1/2013				or 3, knowledge and b		under my jurisdicti	on and
was completed on (mo/day/year)	6/1/2013	and this reco	ord is true to the	e best of my l	knowledge and b	oelief.		on and
	6/1/2013 ense No. 236	and this reco	ord is true to the	e best of my l	knowledge and b	oelief.	under my jurisdicti 5/2013 5. Harb	