Form WWC-5 KSA 82a-1212 WATER WELL RECORD 1 LOCATION OF WATER WELL: SECTION NUMBER RANGE NUMBER FRACTION TOWNSHIP NUMBER NE NE NW7 27 Sedgwick 1/4 Т S 1E 1/4 1/4 E/W Distance and direction from nearest town or city street address of well if located within city? Wichita, Kansas 2021 N. Amidon (New Leaf Plaza) HARRIS, Bruce WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 1223 N. Rock Road #300 Wichita, Kansas CITY, STATE: ZIP CODE: Application Number: 45 ELEVATION: 4 DEPTH OF COMPLETED WELL: ft. LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. ft. ft. Ν WELL'S STATIC WATER LEVEL 14 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 10/31/13 Pump test data: Well water was ft. after hours of pumping @ gpm NW NE Est. Yield: Well water was ft. after hours of pumping @ gpm gpm 12 to 45 Ξ Bore Hole Diameter and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE-3. Feedlot 1. Domestic 12. Other (Specify below) 10. Monitoring well 8. Air conditioning 2. Irrigation 4. Industrial 6. Oil fleld water supply ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) Was Water Well Disinfected? (YES) submitted 5 TYPE OF CASING USED: CASING JOINTS: Glued Threaded 9. Other (Specify below) 5. Wrought Iron 7. Fiberglass 3. RPM (SR) 1. Steel Welded Clamped SDR-26 6 Ashestos-Cement 8. Concrete tile 2. PVC 4. ABS 5 Blank casing diameter 35 ft.. Dia. ft., Dia. ft. to 12 Weight: 2.35 Casing height above land surface: in.. lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 9. ABS 11. Other (specify) 1. Steel 3. Stainless Steel 5. Fiberglass 8. RMP (SR) 12. None used (open hole) 2. Brass 4. Galvanized 6. Concrete Tile 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 7. Torch cut 9. Drilled holes 11. None ( open hole) 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 8. Saw cut 2. Louvered shutter 4. Key punched 6. Wire wrapped 10. Other (specify) SCREEN - PERFORATION INTERVAL 45 35 ft From to ft., From ft. to ft From to ft., From to ft. 24 ft. **GRAVEL PACK INTERVALS:** to 45 From ft., From ft. From ft to From ft. to ft. **GROUT MATERIALS:** Other bentonite hole plug 2. Cement Grout 1. Neat cement 3. Bentonite Grout Intervals: From 24 ft., ft. to ft. From ft. What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 5. Cess Pool 2. Sewer lines 3. Watertight sewer line 6. West 9. Feed yard 12. Fertilizer storage 6. Seepage pit Direction from well? How many feet? 500 ft. plus From From LITHOLOGIC LOG <u>To</u> LITHOLOGIC LOG To O topsoil clay 3 10 10 20 fine sand 30 20 clay sand mix medium sand 30 45 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and 10-31-2013 and this record is true to the best of my knowledge and belief. was completed on (mo/day/year) This water well record was completed on (mo/day/year) Kansas Water Well Contractor's License No. 236 by (signature) Todd S. Harp under the business name of Harp Well and Pump Service