Corrected

WATER WELL RECORD Form WWC-5 KSA 82a-1212 ID No 1 LOCATION OF WATER WELL: Fraction Township Number Section Number Range Number NW ½ NW ½ Sedgwick SW 1/4 27 1 County: 15 Distance and direction from nearest town or city street address of well if located within city? East of I-135, south of 9th St. - Wichita 2 WATER WELL OWNER: UPRR RR#, St. Address, Box # : 1400 Douglas St., Stop 1030 Board of Agriculture, Division of Water Resources RR#, St. Address, BOX#

City, State, ZIP Code : Omaha, NE 68179-1030

3 LOCATE WELL'S LOCATON WITH 4 DEPTH OF COMPLETED WELL Application Number: 25.5 ft. ELEVATION: 1300 (estimated) Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr NE -NW-Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm
Bore Hole Diameter 4 in. to 25.5 ft. and in. to ft.
WELL WATER TO BE USED AS: 5 Public water supply
1 Domestic 3 Feed lot 6 Oil field water supply
9 Dewatering 12 Other (Specify below) W 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was Water Well Disinfected? Yes No X CASING JOINTS: Glued Clamped 5 TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Threaded 2 PVC 4 ABS 7 Fiberglass ...... Blank casing diameter 1 in. to 15.5 ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface 0 in., weight 0.703 lbs./ft. Wall thickness or gauge No. SCH. 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 5 Fiberglass 8 RMP (SR) 11 Other (specify)
6 Concrete tile 9 ABS 12 None used (open hole)
7 Concrete tile 8 Saw cut 11 None (open hole) 7 PVC 10 Asbestos-cement 11 Other (specify) 1 Steel 3 Stainless steel 4 Galvanized steel 2 Brass 6 Concrete tile
5 Gauzed wrapped
6 Wire wrapped SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 9 Drilled holes 7 Torch cut 10 Other (specify) 2 Louvered shutter 4 Key punched SCREEN-PERFORATED INTERVALS: From 15.5 ft. to 25.5 ft. From ft. to ft. GRAVEL PACK INTERVALS: ft. to From fL to ft. From 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals From 2 ft. to 13.5 ft. From ft. to ft. From ft. to ft. 10 Livestock pens What is the nearest source of possible contamination: 14 Abandoned water well 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/ Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedvard 13 Insecticide storage ...... Direction from well? How many feet? LITHOLOGIC LOG CODE FROM ОТ PLUGGING INTERVALS Lithology not logged 0 5 贸 Lean Clay, very dark brown to dark 5 15 gray brown, with fine sand below 8' Lean Clay with sand, dark gray 16.9 15 Clayey Sand, interbedded fine sand 16.9 18 and lean clay Sand, well graded, fine to coarse 18 25.5 grained, brown Latitude: N 37.69946944 Longitude: W 97.31665833 7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/yr) 10/24/13 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/daylyr) 11/13/13, rev. 12/18/13 under the business name of GSI Engineering, LLC by (signature) INSTRUCTIONS: Please fill in blanks and circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, 1000 S W Jackson St., Ste. 420, Topeka, Kansas 66612-1367. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.