WATER WELL RECORD	Form WV	VC-5	7.	er Resources App. No	, l <u></u>
1 LOCATION OF WATER WELL:	Fraction		Section Number	Township No.	Range Number
County: Sedgewick	NW 1/4 NW 1/4 NW		24		R 1
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here					
1					
Elevation: 1350					
2 WATER WELL OWNER: Connoc	DI-98			4, ▼ NAD 83, □	NAD 27
2 WATER WELL OWNER: ConnocoPhillips RR#, Street Address, Box #: 1614-02 Phillips Building Collection Method: ☐ GPS unit (Make/Model: etrek 10					
City, State, ZIP Code : Bartlesville OK 74004 Digital Map/Photo, Topographic Map, Land Surv					Map, Land Survey
Est. Accuracy:					
3 LOCATE WELL JO ft.					
SECTION BOX: Depth(s) Groundwater Encountered (1)					
N WELL'S STATIC WATER LEVEL ft below land surface measured on mo/day/yr					
Pump test data: Well water was ft. after hours pumping gpm EST. YIELD gpm. Well water was ft. after hours pumping gpm					
W NW NE EST. YIELD					
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well					
Domestic Feedlot Oil field water supply Dewatering Other (Specify below)					
Industrial Domestic-lawn & garden M Monitoring well					
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No S If yes, mo/day/yr sample was submitted					
water well disinfected? Yes No					
5 TYPE OF CASING USED: Steel PVC Other					
CASING JOINTS: ☐ Glued ☐ Clamped ☐ Welded 🗸 Threaded					
Casing diameter 2 in. to					
Casing height above land surface6 in., Weight					
TYPE OF SCREEN OR PERFORATION MATERIAL: ☐ Steel ☐ Stainless Steel					
Brass Galvanized Steel None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
☐ Continuous slot ☑ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole) ☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☐ Saw cut ☐ Other (specify)					
L SCREEN-PERFORATED INTERVALS: From the following the foll					
From. ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From ft. to ft. From ft. to ft., From ft. to ft. ft. ft. ft. ft. ft. ft. ft. ft. ft. ft.					
GRAVEL PACK INTERVALS:	From	t. to	ft., From .	tt.	to ft
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other					
Grout Intervals: From					
What is the nearest source of possible contamination:					
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below) ☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☑ Fuel storage ☐ Abandoned water well					
Watertight sewer lines Seepage r		Fertilizer st			gia a ringe de la rinigate de la rinita e el sidio di divida e
Direction from well	Carino de la 1830 de 1830 de 1840 de 1		from well		
FROM TO LITHOLOG	IC LOG	FROM	TO LITHO, L	OG (cont.) or PLU	IGGING INTERVALS
0 3 Sitty clay					
14 17.5 Sand Sandy	0 0 0				<u> Andreas and a state of the st</u>
17.5 20 Clay	eng				
	·				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged					
under my jurisdiction and was completed on (mo/day/year) .12/19/2014 and this record is true to the best of my knowledge and belief.					
Kansas Water Well Contractor's License No. 710 This Water Well Record was completed on (modday/year) 01/14/2014 by (signature)					
INSTRUCTIONS: Use typewriter or ball point per	1. PLEASE PRESS FIRMLY	and PRINT clo	early. Please fill in blank	s and check the correct	answers. Send one copy to
Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.					
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html .					

The state of the s