May. 28. 2014 12:58 PM HARP WELL & PUMP SRVS 3167220024 No. 0584 WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick NE swSW 1/4 1/4 8 Υ 27 1EĘ/W R Distance and direction from nearest town or city street address of well if located within city? 1548 N. Burns Ave. Wichita, Kansas ROLAND, Donald WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#.ST. ADDRESS.BOX #: 1548 N. Burns Ave. Wichita, Kansas CITY, STATE: ZIP CODE: Application Number: 15 4 DEPTH OF CHAPTER CONTROLL: LOCATE WELL'S LOCATION ELEVATION: Basement Floor WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. ft. WELL'S STATIC WATER LEVEL 13 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr. 4/11/14 Pump test data: Well water was ft. after hours of pumping @ -NW - N= gpm Est. Yield: Well water was ft. after hours of pumping @ apm gpm Σ Bore Hole Diameter WELL WATER **WORE** USED AS: Injection well 5. Public water supply 1. Lawn and garden only SE-1. Domestic 12. Other (Specify below) 10. Monitoring weil 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning ; if yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? NO submitted Was Water Well Disinfected? (YES) TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: Glued Threaded 5. Wrought Iron 7. Fiberglass 1. Steel 3. RPM (\$R) Welded Ciamped 8. Concrete tile 6. Asbestos-Cement 2. PVČ 4, ABS 11/4 in. Blank casing diameter to Dia. ft. Di∌ ft. to Casing heighted and transfer food Weight: Wall thickness or gauge No. lbs. / ft. TYPE OF SCREEN OR PERFORATION MATERIAL: 11. Other (specify) N/A 7. PVC 9. ABS 1. Steel 3. Stainless Steel 5. Fiberglass 8. RMP (SR) 12. None used (open hole) 6. Concrete Tile 10. Asbestos-Cement 2. Brass 4. Galvanized SCREEN OR PERFORATION OPENINGS ARE: 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None ( open hole) 1. Continuous slot 2. Louvered shutter 8. Saw cut 10. Other (specify) N/A4. Key punched Wire wrapped SCREEN - PERFORATION INTERVAL ft. From to ft., From ft. From to ft., From ft. ft. ft. GRAVEL PACK INTERVALS: From to From to ft. to From ft.. From to **GROUT MATERIALS:** 6 2. Cement Grout bentonite hole plug 1. Neat cement 3. Bentonite Grout Intervals: to 15 From From What is the nearest source of possible contamination: 10. Livestock pens 15. Oîl well/Gas well 7. Pit privy 13. Insecticide storage 4. Lateral lines 1. Septic tank 16. Other (specify below) Fuel storage 8. Sewage lagoon 14. Abandon water well 5. Cess Pool 2. Sewer lines 9. Feed yard 12. Fertilizer storage 6. Seepage pit 3. Watertight sewer line How many feet? Direction from well? LITHOLOGIC LOG LITHOLOGIC LÖG From Тο From Тο Ò cement hentonite hale plug Contractor's or Landowner's Certification: This water well was 1. constructed reconstructed or 3. plugged under my jurisdiction and 4/11/2014 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. This water well record was completed on (mo/day/year) 4/14/2014 Kansas Water Well Contractor's License No. 236 Todd S. Harb by (signature) under the business name of Harp Well and Pump Service