WATER WELL RECORD	Form WWC-5	Division of Wate	r Resources App. N	0	
1 LOCATION OF WATER WELL: County: Sedgwick	Fraction  1/4 SW 1/4 `SE 1/4 NE 1/4	Section Number 22	Township No. T 27 S		
Street/Rural Address of Well Location;	Global Positioning				
from nearest town or intersection: If at	Latitude: .37.41'.12.58301" (in decimal degrees) Longitude: 97.18'.7.09957" (in decimal degrees)				
Former Mikes Cleaners 2910 East Douglas, Wichita, KS 67203		Elevation: 1307.46			
2 WATER WELL OWNER: KDHE-BER		Datum: ☐ WGS 84, ☑ NAD 83, ☐ NAD 27 Collection Method:			
RR#, Street Address, Box #: 1000 SW Jackson St Ste 410		GPS unit (Make/Model:)			
City, State, ZIP Code : Topeka, KS 66612		☐ Digital Map/Photo, ☐ Topographic Map, ☑ Land Survey  Est. Accuracy: ☑ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m			
3 LOCATE WELL	COMPLETED WELL 40	A			
WITH AN "X" IN SECTION BOX:  N  Depth(s) Groundwater Encountered (1).27					
N WELL'S STATIC WATER LEVEL. 27ft. below land surface measured on mo/day/yr. 3-3-2014					
DOT VIELD M	Pump test data: Well water was N/A ft. after N/A hours pumping. N/A gpm EST. YIELD N/Agpm. Well water was N/A ft. after N/A hours pumping. N/A gpm				
W Bore Hole Diameter 8.25 in. to .40 ft., and .N/A in. to .N/A ft.					
SWSE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)  Irrigation Industrial Domestic-lawn & garden Monitoring well MW-1					
Was a chemical/bacteriological sample submitted to Department? Yes V No					
s If yes, mo/day/yr sample was submitted.N/A					
	fected? Yes No				
5 TYPE OF CASING USED: Stee			····		
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter .2					
Casing height above land surface. 0					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
☐ Steel ☐ Stainless Steel					
SCREEN OR PERFORATION OPENINGS ARE:					
☐ Continuous slot					
SCREEN-PERFORATED INTERVALS:	From	ft., From!	WA ft. :	to <b>N/A</b> ft.	
	From	ft., From!	N/A ft.	to ft.	
GRAVEL PACK INTERVALS:	From N/A ft. to N/A	ft., From .!	.₩.^\ ft. WA n	to!!/^ tt.	
6 GROUT MATERIAL: Neat ceme Grout Intervals: From .2	ent Cement grout Dentor	ite Other Cor	crete 0-2 feet		
Grout Intervals: From .2 ft. to		ft. to ft.,	From .N/A	. ft. to . N/Aft.	
What is the nearest source of possible conta	amination: nes	ens 🗌 Insecticide	storage Oth	er (specify below)	
☐ Sewer lines ☐ Cesspool	Sewage lagoon Fuel storage	e	water well		
☐ Watertight sewer lines ☐ Seepage p Direction from well	oit Feedyard Fertilizer st	orage 🔲 Oil well/ga from well	s well	rinated Solvents	
FROM TO LITHOLOG			OG (cont.) or PLU	GGING INTERVALS	
		24.5 clax di	< brown sl:	ghtly moist	
0.5 2.0 Sity clay ok be			iff Kighly	plastic trace	
2.0 3,5 becomes to ha	plastic. ' 24.5	25.5 SOND F	ive moist		
		- 1	aray to reddic	h brown maist	
5.0 7.5 Clarry silt Lt	brown slightly	Soft his	Aly plastic		
		29.0 Sand me		couse very moist	
7,5 15.0 s. lty clay brow		38.0 Same w		stiff Plastic	
5nit ) Qustic				acar very of if strly moist	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Z constructed, _ reconstructed, or _ plugged					
under my jurisdiction and was completed on (mo/day/year) .3-3-2014 and this record is true to the best of my knowledge and belief.  Kansas Water Well Contractor's License No759 This Water Well Record was completed on mo/day year 4-20-2014					
under the business name of RAZEK Environmental, LLC by (signature)					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send one copy to					
Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.  Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at					
http://www.kdheks.gov/waterwell/index.html					