	WATER WELL RECORD Form		1212 ID No. 0050041	
LOCATION OF WATER WELL		Section Number	i '	Range Number
inty: Sedgwick	SW 1/4 SW 1/4 SE		T 27 S	R 1 E
ance and direction from neare 26 W. 13 th St. – Wichita	est town or city street address of well if located wit	hin city?		
	ansas Department of Health and Er	vironment		
	000 SW Jackson St., Ste. 410	ivii oiiiioiit	Roard of Agriculture Dis	rision of Water Resources
State ZIR Code : To	neka KS 66612		Application Number:	ision of traior resources
OCATE WELL'S LOCATON	WITH			
N "X" IN SECTION BOX:	DEPTH OF COMPLETED WELL Depth(s) Groundwater Encountered 1	27.92 ft. ELE	VATION: 131'	1.70 (TOC)
	Depth(s) Groundwater Encountered 1	22.5 f	t. 2 ft.	3ft.
NW NE	WELL'S STATIC WATER LEVEL 21	.72 ft. below TOC	measured on mo/day/yr	04/04/14
	Pump test data: Well water v			
w 	Est. Yield gpm: Well water v	vas	ft. after hours	pumping gpm
	Bore Hole Diameter 8.25 in to	28	ft and i	n to ft.
SW SE	WELL WATER TO BE USED AS: 5 Put 1 Domestic 3 Feed lot 6 Oil	olic water supply	8 Air conditioning	1 Injection well
i x	1 Domestic 3 Feed lot 6 Oil	field water supply	9 Dewatering 1	2 Other (Specify below)
S	2 Irrigation 4 Industrial 7 Lav			
3	Was a chemical/bacteriological sample su			
	submitted	W	ater Well Disinfected? Yes	No X
YPE OF BLANK CASING US	SED: 5 Wrought Iron	8 Concrete tile	CASING JOINTS: Glue	ed Clamped
1 Steel 3	RMP (SR) 6 Asbestos-Cement	9 Other (specify belo		
2 PVC 4	ABS 7 Fiberglass		Threa	_{ided} Flush
	l in. to 17.92 ft., Dia	in. to	ft., Dia	in. to ft.
ng height above land surface	in. to 17.92 ft., Dia 0 in., weight 0.	.703 lbs./ft.	Wall thickness or gauge No	SCH. 40
OF SCREEN OR PERFOR	RATION MATERIAL:	7 PVC	10 Asbestos-cem	ent
1 Steel 3	Stainless steel 5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass 4	Galvanized steel 6 Concrete tile	9 ABS	12 None used (or 8 Saw cut	en hole)
EEN OR PERFORATION O		d wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot 6 Wire w	rapped	a Dillied Holes	
2 Louvered shutter	4 Key punched 7 Torch of		10 Other (specify)	
EEN-PERFORATED INTER	VALS: From 17.92 ft. to	27.92 ft.	From ft.	toft.
	Fromft. to	ft.	From ft.	toft.
GRAVEL PACK INTERV				
	From ft. to	ft.	From ft.	to ft.
ROUT MATERIAL: 1	Neat cement 2 Cement grout	3 Bentonite	From ft. 4 Other	
t Intervals From 1	ft. to 16 ft. From	ft. to	ft. From	ft. to ft.
t is the nearest source of pos	ssible contamination:	10 Lives	took some 14 Al	andoned uniter well
1 Septic tank	4 Lateral lines 7 Pit privy	11 Fuel	storage 15 O	il well/ Gas well
2 Sewer lines	5 Cess pool 8 Sewage la		lizer storage 16 O	ther (specify below)
3 Watertight sewer lines	6 Seepage pit 9 Feedyard		cticide storage	
tion from well?		How many		
OM TO CODE		FROM TO	PLUGGING I	NTERVALS
0 0.33 33 5	Concrete Sand, tan, fine to medium grained			
.33 5 5 8	Clayey Sand, brown			
	Sand, tan to olive brown, fine to	 		
	medium grained, with coarse grains			
8 28	below 22.5'			
		ļ		
		ļ	Cumou Date: 0414F	14
		Survey Date: 04/15/ Northing: 1693414.9		
		 	Easting: 1641685.0	
			Lasuny. 1041003.00	
1	WINED'S CERTIFICATION: This water well was	(1) constructed (2) mod	nnstructed or (3) philoged use	ler my juriediction and was
ONTRACTOR'S OR LANDO		R : / OOI 100 GOGGE, (C/ 150	or readered, or to biogram mile	y jui wakulon ana was
	,		have to the best of !	des and halled 1/
eleted on (mo/day/yr)	04/03/14	and this record is	true to the best of my knowle	
CONTRACTOR'S OR LANDO pleted on (mo/day/yr) er Well Contractor's License or the business name of	04/03/14	and this record is	true to the best of my knowle ecord was completed on (mo	