WATER WELL RECORD	Form WWC-5	Division of Water Resources App. No.
1 LOCATION OF WATER WELL:	Fraction	Section Number Township No. Range Number
County: Sedgwick	1/4 NW 1/4 SW 1/4 NW 1/4	28 T 27 S R 1 ZE W
Street/Rural Address of Well Location; i		Global Positioning System (GPS) information:
from nearest town or intersection: If at o	owner's address, check here .	Latitude: .37.67496 (in decimal degrees)
Automax		Longitude: 97.33584 (in decimal degrees)
940 South Broadway St., Wichita, KS 67211		Elevation: 1296.41
		Datum: ☐ WGS 84, ☑ NAD 83, ☐ NAD 27
1,0112	N Jackson Street Suite 410	Collection Method: GPS unit (Make/Model:)
		☐ Digital Map/Photo, ☐ Topographic Map, ☑ Land Survey
l one, state, zm code . Topeka,	KS 66612-1367	Est. Accuracy:
3 LOCATE WELL		
WITH AN "X" IN 4 DEPTH OF C	COMPLETED WELL .22	ft.
SECTION BOX: Depth(s) Groundwater Encountered (1).17		
N WELL'S STATIC WATER LEVEL. 16.82ft. below land surface measured on mo/day/yr. 5/6/2014		
Pump test data: Well water was. N/A		
EST. YIELD. N/Agpm. Well water was. N/Aft. after. N/Ahours pumping. N/Agpm Bore Hole Diameter 8.25in. to .22ft., and .N/Ain. to .N/Aft.		
W E Bore Hole Diam		
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well		
SWSE Domestic		
Irrigation	☐ Industrial ☐ Domestic-law	m & garden M Monitoring well MMY-19
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No If yes, mo/day/yr sample was submitted.N/A		
S If yes, mo/day/yr sample was submitted.!!//A		
Water wen disinfected: 165 kg 140		
5 TYPE OF CASING USED: Steel PVC Other		
CASING JOINTS: Glued Clamped Welded Threaded		
Casing diameter .2 in. to .12 ft., Diameter .N/A in. to .N/A ft., Diameter .N/A in. to .N/A ft.		
Casing height above land surface. 0		
TYPE OF SCREEN OR PERFORATION MATERIAL:		
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)		
SCREEN OR PERFORATION OPENINGS ARE:		
☐ Continuous slot		
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)		
SCREEN-PERFORATED INTERVALS: From 12 ft. to 22 ft. From N/A ft. to .N/A ft.		
From. N/A ft. to . N/A ft., From . N/A ft. to . N/A ft.		
GRAVEL PACK INTERVALS:	From10 ft. to22	ft., From .N/A ft. to .N/A ft.
FromN/Aft. toN/A		
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Concrete 0 to 2 feet Grout Intervals: From .2		
What is the nearest source of possible contamination:		
☐ Septic tank ☐ Lateral lin☐ Sewer lines ☐ Cesspool	es Pit privy Livestock p Sewage lagoon Fuel storage	
	it Feedyard Fertilizer sto	
Direction from well		rom well
FROM TO LITHOLOG	. , ,	TO LITHO. LOG (cont.) or PLUGGING INTERVALS
0 0.5 Asphalt		\ <u></u>
0.5 5.0 5:11		
5 7 8'12 clas		
7 12 Sand - F. We	Len St.	
12 17 Sad med to	(30156	
17 22 Soud very	moist	
7		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged		
under my jurisdiction and was completed on (mo/day/year) .5/5/20.14 and this record is true to the best of my knowledge and belief.		
Kansas Water Well Contractor's License No. 759 This Water Well Record was completed on (mo/day/year) 5/26/2014		
under the business name of RAZEK Environmental LLC by (signature)		
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the consect answers. Send one copy to		
Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at		

http://www.kdheks.gov/waterwell/index.html