	***			ER WELL RECO	ORD For		KSA 82a-12			
	ION OF WATE			<u></u>	<u></u>		tion Number	Township Numbe		ange Number
	Sec.		SE 1/4			1/4	31	т 27	S   R	<u> </u>
				djacent to 2			/ichita, KS			
			Manufacturing							
RR#, St. A	ddress, Box #	: 251	5 McKinney Av	e				Board of Agricultur	e, Division of	Water Resources
City, State	, ZIP Code	Dal	as, TX 75201					Application Numbe	<u>r:</u>	
3 LOCAT	E WELL'S LO	CATON W	DEPTH OF		WELL	47	ft. ELEV	ATION		
	N		Denth(s) Groun	dwater Encoun	tered 1.5		ft.	2	ft. 3	Ft.
<b>∔ Г</b>	i	i	WELL'S STATIO	WATER I EV	FI 10	<b>).01</b> ft.	below land su	urface measured on m	o/dav/vr	
	NW	NF						after h		-
			Est Yield	Gpm <sup>·</sup> \	Well water v	was	Ft	after H	lours pumpine	a Gom
≝ W			E Bore Hole Diam	eter 8.625	In. to	47	7	ft. and 8 Air conditioning 9 Dewatering	in. to	Ft.
ī			WELL WATER	TO BE USED A	AS: 5 Pul	blic water su	upply	8 Air conditioning	11 Injec	tion well
	SW	SE	1 Domesti	c 3 Feed lot	6 Oil	field water	supply	9 Dewatering	12 Othe	r (Specify below)
	x		2 Irrigation	4 Industria	al 7 Lav	wn and gard	den (domestic	) 10 Monitoring well	A	C-19 (D)
' L	<u> </u>		Was a chemical	/bacteriologica	I sample su	bmitted to [	Department?	Yes No X	lf yes, mo/da	y/yr sample was
			Submitted					er Well Disinfected?		
5 TYPE C	OF BLANK CA	SING USE	D:	5 Wrough	t Iron	8 Concre	ete tile	CASING JOINTS:	Glued	Clamped
1 <u>St</u>	teel		MP (SR)	6 Asbesto	s-Cement	9 Other	(specify below	v)	Welded	
2 P	VC	4 AE	BS	7 Fibergla	SS				Threaded	X
Dier:	na dicession	2	in tr. 2.	Ft.,		1- 1	ha	ft., Dia		
Blank casil	ng diameter	<b>4</b>		Dia	50	י יווי <b>טע די</b>	[0 			<sup>IL.</sup>
1				In., weight				Wall thickness or gau 10 Asbestos		
1 St			TION MATERIAL: ainless steel	5 Fibergla						
2 Br			alvanized steel	6 Concret		9	ABS	11 Other (sp 12 None use		
			NINGS ARE:			d wrapped		8 Saw cut		·
1 Co	ontinuous slot		3 Mill slot		6 Wire w	rapped		9 Drilled holes		
2 Lo	ouvered shutte	۲	4 Key punched		7 Torch o	sut		10 Other (specify)		
SCREEN-F	PERFORATED		LS: From	<b>37</b> ft	. to	47	ft. Fi	rom	ft. to	ft.
								rom		
SA	ND PACK INT	TERVALS:		<b>35</b> ft				om		
			From		. to			rom	ft. to	Ft.
6 GROUT	MATERIAL:	1 N	eat cement 2	Cement grou	it	3 Ben	tonite	4 Other		
		0.5		Ft.		Ft.				
			ft. to <b>33</b>	From3	33	to		ft. From		
		ce or possi	ble contamination:	7	Pit privy			•	4 Abandone 5 Oil well/ G	1
	eptic tank		4 Lateral lines				11 Fuels			
	ewer lines	. Un co	5 Cess pool		Sewage la	agoon	12 Fertiliz	•	6 Other (spe	<u> </u>
3 W Direction fr	atertight sewe	ranes	6 Seepage pit	9	Feedyard		13 Insecti How many f	cide storage	Contam	inated Site
FROM		CODE				FROM	TO TO			
- FROM	0.5		Topsoil				+' <u>`</u> +-	FLUGGI	ING INTERVA	1L3
0.5	14	+	Silty Clay							
		1	Alternating lay	ers of fine	sands.					
14	47		medium sands	, coarse s	ands					
			and some grav							
47	TD	ļ	End of boreho	e						
							++			
	+						++-			
			×							
						ļ <u></u>				
								nstructed, or (3) plugge		
			01/2					ue to the best of my kn		
							/ater Well Red	cord was completed or	(mo/day)	500/1/14
under the t		e of		ted Enviro			By as Department	(signature) Brach of Health and Environm	242 ARD	1501
			913-296-5545. Send							Trater, ropeka,-