3SI Job I	No. 14725	4	,	WATER WE	ELL RECORD For	m WWC-5	KSA 82	a-1212 ID No.		MW-16	30D
	N OF WATER		Fraction				on Numb		ip Number	Range Number	r
County:	Sedç	jwick	NW	1/4 S	E 1/4 NW	1/4	21	<u> </u>	27 s	R 1	Е
Distance and	direction from	n nearest tov	vn or city stre	et address	of well if located will be of 1st St. – W	thin city?					
	WELL OWNE					icnita					
	ress, Box#				У			Roard of	Aaricultura Divi	ision of Water Resou	rces
Tity State 7	ID Code	· Wichit	a KS 67	219				A maliantia	.m. Nijimahanii		
3 LOCATE	WELL'S LOC	ATON WITH	4			40.7			4000	3.15 (TOC)	
AN "X" IN	I SECTION B	OX:	DEPTH	OF COMP	LETED WELL	40.0	tt. EL	EVATION:	1290	.15 (100)	
1 1	!	!	Dopunto, C	ou lawate	Liloddinered			_ 11. 4	11.		''
	- N/\/ : X	NE								/yr	
w w		i l	Fet Viold	rump test	anm: Well water	was		t after	houre r	oumpingg	apm
7			Bore Hole I	Diameter	8.25 in to	was 40 .	5	ft and	ir	n to	tt l
ļ	sˈw	- s'E	WELL WAT	ER TO BE	USED AS: 5 Pu	blic water su	pply	8 Air cor	nditioning 1	n. to 1 Injection well 2 Other (Specify bel	"
	į l	į	1 Dor	nestic 3	Feed lot 6 Oil	field water s	upply	9 Dewat	ering 1	2 Other (Specify bel-	low)
Y Insumeses	S							222-222-222-22-22-22-22-22-22-22-22-22-	SERVICE CONTRACTOR SERVICE CONTRACTOR -		
	•		1	nical/bacte	eriological sample si	ubmitted to D				, mo/day/yr sample w	vas
		***************************************	submitted				~	***************************************	~ .	No X	
-	BLANK CAS				Wrought Iron					dClamped	
2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	el	attack-by	(SR)		Asbestos-Cement	9 Other (specify be	-	Weld	CANDON PROGRAMMA MARKON MARKON POPULAR PROGRAMMA POPULAR PROGRAMA POPULAR PROGRAMA POPULAR PROGRAMMA P	
2 PV		4 ABS			Fiberglass			L	Threa	_{ded} Flush	
Blank casing	g diameter	2	in. to	30.5	ft., Dia	in. to		ft., Dia		in. to	ft.
Casing heigh	ht above land	surface	0	in., v	veight0	.703	lbs./	ft. Wall thicknes	ss or gauge No.	SCH. 40 ent	
TYPE OF SO	CREEN OR P	ERFORATIO	N MATERIA	L:		7	PVC	10	Asbestos-ceme	ent	
1 Stee 2 Bra		3 Staini	ess steel	. 5	Fiberglass Concrete tile	8	RMP (SR) 11	Other (specify)	.,	
		ION OPENII	NGS ARE:	0	5 Gauze	d wrapped	ABS	8 Saw cut	ivone usea (op	en noie) 11 None (open hoi	ile)
	ntinuous slot		Mill slot			rapped				The trains (apparent	,
2 Lou	vered shutter	4	Key punche	d	THE CONTROL OF THE CO						
SCREEN-PE	ERFORATED	INTERVALS	: From	30.5	ft. to	40.5	ft	. From	ft.	to	ft.
			From		ft. to		ft	. From	ft.	to	ft.
GRA	AVEL PACK I	NTERVALS:	From	28.5	ft. to	40.5	ft	. From	ft.	to	ft.
			From	~	ft. to		ft	. From	ft.	to	ft.
6 GROUT	MATERIAL:	1 Neat	cement	2 Cer	nent grout	3 Ben	onite	4 Other			
Grout Interv	als From	1	ft. to	28.5	ft. From	ft. t	0	ft, Fr	om	ft. to	ft.
What is the	nearest sourc	e of possible	contamination	on:			10 Liv	estock pens	14 Ab	andoned water well	
	ptic tank		4 Lateral		7 Pit privy			el storage		l well/ Gas well	
	wer lines itertight sewer	linge	5 Cess p 6 Seepag		8 Sewage 9 Feedyard			rtilizer storage secticide storage		her (specify below)	
Direction fro	•	111100	o Geepa	Je hir	9 reedyan	1		ny feet?	;		
FROM	ТО	CODE	LI	THOLOGI	C LOG	FROM	TO	iny leet.	PLUGGING I	NTERVALS	
0	5				ology not logged						
5	6		layey Silt								
6	9.5		ilty Clay,		graded, very fine		 				
9.5	20		fine, some								
					aded, fine to						
20	20 =	l i		ple interv	als with no						
20 32.5	32.5		covery and, brow	a na!-	ar was also al	-					
34	37		lay, brown		graded	-	_	Survey d	ate: 06/11/	14	
·			and, gray,		led, fine to		-	- Caracy a	aroi voi i li	B - B	
37	40.5	m	edium						: 1686353.2		
40.5			oring termir						1650966.03		
						(1) construc	ted, (2) re	econstructed, or	(3) plugged und	ler my jurisdiction and	asw t
	on (mo/day/yr			05/22/1						dge and belief. Kans	
	Contractor's I				31			Record was co	mpleted on (mo	o/day/yr) 07/21 /	/14
	usiness name		iks and circle :	Engine	ering, LLC	by	(signatur	rey lu lucius	d Environment F	Bureau of Water, 1000	S M
Jackso	on St., Ste. 420,	Topeka, Kan	sas 66612-136	7. Telepho	ne: 913-296-5545. S	end one to W	ATER WEI	L OWNER and r	etain one for you	r records.	