			WA	TER WELL RECOR	RD Form	WWC-5	KSA 82a	a-1212	ID No				
	N OF WATE		Fraction			i	on Numbe	er	Township N	umber	Rang	e Numbe	-
County:	Sedç	gwick	NW 1/2	NW 1/4		1/4	31		27	S	R	1	Ε
				address of well if lo	ocated with	in city?							
			. Meridian – ' rip Corpora					· · · · · · · · · · · · · · · · · · ·					
			5. 129 th E. A						and of And	udtura Dis	inion of \A/o	tor Boso	
City State 7	ZID Codo	. Tules	OK 74134						loard of Agric		ision of vva	ilei Keso	urces
LOCATE	WELL'S LOC	ATON WITH							pplication N				
3 AN "X" IN	SECTION B	UX:	MDEE IN OF	COMPLETED WI	ELL	19	ft. EL	EVATIO	ON:	1294	1.14 (TO	<u>C)</u>	
† ×	i	i	Depth(s) Grou	ndwater Encounte	red 1	13.	B	_ft. 2		ft.	3		ft.
	NW -	- NE	WELL'S STAT	IC WATER LEVEL		ft. I	oelow land	d surfac	e measured	on mo/day	/уг		
	i l	į	Pu	mp test data: We	ell water wa	as		ft. afte	er	hours	pumping		gpm
₩ W		·	Est. Yield	gpm: We	ell water wa	as		ft. afte	er	hours	pumping		gpm
ī l	i	1 1	Bore Hole Dia	meter 8.5 R TO BE USED AS stic 3 Feed lot	in. to	19		ft. a	nd	i	n. to		ft.
	-sw	- SE	WELL WATER	R TO BE USED AS	5 Publ	ic water su	pply	8	Air condition	ning 1	1 Injection	well	olow)
↓	i I		Domes	auc 3 reed ioi	6 OH 11	eio water s	uppiy	\ Č	Dewatenng	' 	2 Otner (a	pecity be	elow)
'	S			on 4 Industrial									
			I .	al/bacteriological s	ample sub	mitted to D							was
			submitted						ell Disinfecte			No X	
	BLANK CAS			5 Wrought In					CASING JOI	NTS: Glue	ed	Clamped	j
	el	3 RMP((SR)	6 Asbestos-	Cement	9 Other (specify be	elow)		Wel			
2 PVC		4 ABS		7 Fiberglass						Threa	ded	Flust	h
Blank casing	diameter	2	in. to	9 ft., Dia									ft.
Casing heigh	ht above land	surface	0	ft., Diain., weight	0.7	703	lbs./	ft. Wall	thickness or	gauge No	Š	CH. 40)
			N MATERIAL:	'		7	PVC		10 Asb	estos-cem	ent		
1 Stee	el	3 Stainle	ess steel	5 Fiberglass	3	8	RMP (SR	()	11 Oth	er (specify))		
2 Bras		4 Galvaı	nized steel	6 Concrete t	tile	9 .	ABS		12 Non	e used (op	en hole)		
SCREEN OF	R PERFORAT			5	Gauzed	wrapped		8	Saw cut		11 None	(open h	ole)
1 Con	ntinuous slot	3	Mill slot	6	Wire wra	pped			Drilled holes				
2 Lou	vered shutter	4	Key punched		Torch cu			10	Other (spec	:ify)			
SCREEN-PE	ERFORATED	INTERVALS:	From	9 ft. t	ю	19	ft	. From		ft.	to		ft.
			From	ft. t	ю		ft	. From		ft.	to		ft.
GR/	AVEL PACK II	NTERVALS:	From	6 ft. t	ю	19	ft	. From		ft.	to		ft.
			From	ft. t	0		ft	. From		ft.	to		ft.
6 GROUT I	MATERIAL:	1 Neat	cement	2 Cement grout		3 Bent	onite	4 0	ther				
 Grout Interva	als From	1	ft to 6	ft. From		ft t			ft From		ft to		errererererer
What is the r	nearest source	e of possible	contamination:						pens		andoned v		
	otic tank	.	4 Lateral line	es 7 F	Pit privy				ge		l well/ Gas		•
•	ver lines		5 Cess pool		Sewage lag	oon	12 Fe				ther (specif		
3 Wat	tertight sewer	lines	6 Seepage p		Feedyard	-			storage		. ,	. ,	
Direction from	m well?						How ma	ny feet	?				
FROM	TO	CODE		OLOGIC LOG]	FROM	то			UGGING I	NTERVAL	S	
0	0.5		phalt										
0.5 10	10			wn, with small p	pebbles		ļ			· · · · · · · · · · · · · · · · · · ·			
15	15 19		t with mind			· · · · · · · · · · · · · · · · · · ·	<u> </u>						
10	13	Ja	iriu, iine graii	ned, gray, well s	orted		-	+					
							 	+					
							 	_				,	
							†						
							1	1					
									vey date			83)	
								Lat	itude: N 3	37.6647	7		
								Lor	ngitude: \	N 97.37	077		
		L											
7 CONTRA	ACTOR'S OR	LANDOWNE	R'S CERTIFICA	TION: This water	well was (1) construc	ted, (2) re	econstru	cted, or (3) p	lugged und	ler my juris	diction ar	nd was
completed o	on (mo/day/yr)		11.	/24/14		and thi	s record i	is true to	the best of	my knowle	dge and be	elief. Kar	nsas
	Contractor's L			531		. -			was/comple	-	-		
under the bu	usiness name	of	GSI En	aineerina. LL	_C	by	(signatur	e) /\	$I \smile$	\			
INSTRU	UCTIONS: Ple	ase fill in blank	s and circle the c	orrect answers. Ser	nd three con	ies to Kans	as Departn	nenf of P	lealth and Env	rironment, E	Sureau of W	ater, 1000	sw
Jacksor	n St., Ste. 420,	Topeka, Kansa	as 66612-1367. T	Telephone: 913-296	-5545. Sen	d one to WA	TER WEL	L OWN	ER and retain	one for you	r records.		