	WATER WE	ELL REC	ORD	Form WV	VC-5 K	(SA 82a-	1212			
1 LOCATION OF WATER WELL:	FRACTION SW SE SE NW			SEC	SECTION NUMBER		l .		RANGE NUMBER	
Sedgwick,	PANK 1/4		/4 8%	1/4	17	Т	27 S	R 1	E/W	
Distance and direction from nearest town or city			in city?							
	Wichita, Kansa	ıs								
in the second se	IES, Mark W. 9th N.						Board of A	griculture, Division o	f Water Resource	
	hita, Kansas			7	IP CODE: 6	7203	Application N	umber:		
	DEPTH OF CHAR	WEI	1: 2	28 ft.	ii OODL.	ELEVATIO				
WITH AN "X" IN SECTION BOX:	epth of groundwater	, ,		fi	1.		ft.		ft.	
	ELL'S STATIC WAT			FT. BELO	W LAND S	URFACE ME	ASURED ON mo	o/day/yr: 12/	16/14	
NWNE	Pum	p test data:	Well w	ater was		ft. after	hou	irs of pumping @	gpm	
	Est. Yield:	gpm	Wellw	ater was		ft. after	hou	irs of pumping @	gpm	
1— 1 × 1	Bore Hole Diameter		in.	to	f	t. and	in.	to	ft.	
1 1 de 1 de 1 1	/ELL WATER W.S e 1. Domestic 3. F	E USED AS: Feedlot	5 Public w	ater sunniv	<7. Lawn	and garden	9. Dewate	9	jection well	
				water supply		nditioning	10. Monito		(Specify below)	
	Was a chemical/bacterio				YES	NO		s, what mo/day/yr		
	ubmitted				Was	Water Well D	isinfected?	(YES)	NO	
TYPE OF CASING USED: 1. Steel 3. RPM (S	5. Wrought I	ron	7. Fiberglas	s 9. C	ther (Specif	y below)	CASING JOINTS		Threaded	
2. PVC 4. ABS	6. Asbestos-	-Cement	8. Concrete	tile				Welded	Clamped	
Blank casing diameter 6	in. to	ft.,	Dia.	in.	to	ft.,	Dia.	in. to	ft.	
Casing height Ca	60 in.,		Weight:	1	ibs. / ft.	Wa	all thickness or ga	uge No.		
TYPE OF SCREEN OR PERFORATION MATERIAL:										
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) N/A										
2. Brass 4. Galvanized	Concrete Til	le 8	B. RMP (SR)	10. A	Asbestos-Ce	ment 12	. None used (ope	en hole)		
SCREEN OR PERFORATION OPENIN	IGS ARE:									
1. Continuous slot 3. Mill s	lot 5. G	auzed wrap	oped	7. T c	orch cut	9. i	Drilled holes	11. None	(open hole)	
2. Louvered shutter 4. Key p	ounched 6. W	ire wrappe/	d	8. S a	aw cut	10.	Other (specify)	N/A		
SCREEN - PERFORATION INTERVAL	From	ft.	. 1	to	ft.,	From	ft.	to	ft.	
	From	ft.	. t	to	ft.,	From	ft.	to	ft.	
GRAVEL PACK INTERVALS:	From	ft.		to	ft.,	From	ft.	to	ft.	
	From	ft.		to	ft.,	From	ft.	to	ft.	
6 GROUT MATERIALS: 1. Neat	cement	2. Cemen	nt Grout		3. Bentonito	9	Other bei	ntonite hole p	olug	
Grout Intervals: From	ft. to	ft.,	From	ft.	to	ft.	, From	1 ft.	to 12 ft.	
What is the nearest source of possible of	7	Pit privy		10. Livesto	ck pens	13. Ins	ecticide storage	15. Oil wel	I/Gas well	
1. Septic tank 4. Lateral lines 7. Fit pivy 10. Electrode storage 13. Insecticide storage 14. Abandon water well 16. Other (specify be							specify below)			
3. Watertight sewer line 6. Seepa	_	Feed yard		12. Fertilize	r storage					
Direction from well? East	-go p.:	•				Hov	v many feet? 12	ft. plus		
From To	LITHOLOGIC	LOG		From	То		LITHOL	OGIC LOG		
				0	1		basement flo	oor)		
				12	12 28	well grav	e hole plug			
				1-14	1 20	wen grav	/ei			
					-				******	
								W.,		
				-	-					
7 Contractor's or Landowner's Certif	fication: This water v	well was 1.	constructe	ed 2. re	econstructe	d or 3.	plugged	under my jurisd	liction and	
was completed on (mo/day/year)	12/16/2014					knowledge a				
Kansas Water Well Contractor's Licer		۵.				d on (mo/day		18/2014		
		C '			•				Th.	
under the business name of Harp	well and Pum	ip Servic	е	by (s	ignature)		i oaav.	S. Har	p	