			WATE	R WELL RE	CORD	Form W	VC-5	KSA 82a	1212		
_	N OF WAT	ER WELL:		SW SE	SW NE			Number	Township	_	Range Number
County: Sec			NHE 1/4		1/4	\$12 1/4		20	T 2	⁷ S	R 1 €W
			vn or city street a		ell if locate	ed within o	eity?		50875046	:	MW-5
			Waco, Wichita		• • • •				30673046		MM-2
-			ive Manor Wich	nita Assoc	iates						
RR#, St. Ad	-		ox 1598								Division of Water Resources
City, State,		: Topeka				25				tion Number:	Hove 1302
LOCATE	WELL'S LC N SECTION	CATION WITH	4 DEPTH OF C								
AN A II	N SECTION N	BOA.	Depth(s) Ground	water Encou	ntered	1 ! 8		ft. 2	L	ft. :	3
ī	!	!	WELL'S STATIC								
	- NW	- NE									umping gpm
	1		Est. Yield N.	^A gpm:	Well wat	ter was .	<u></u>	ft. a	ter	hours p	umping gpm
<u>•</u> L	<u>i</u> 1		Bore Hole Diame	eter ⁸	in. to) ³	25 , .	ft., a	and	ir	n. to
* w	! 1	X 1 '	WELL WATER T	O BE USED	AS:	5 Public	water su	pply	8 Air condition	ing 11	Injection well
ī	- sw	SE	1 Domestic	3 Fee	dlot	6 Oil field	d water s	supply	9 Dewatering	12	Other (Specify below)
-	- 🥎	%	2 Irrigation	4 Indu	ustrial	7 Lawn a	and gard	en only 🤇	Monitoring v	well	
	i 1	1	Was a chemical/t	oacteriologica	al sample	submitted	to Depar	tment? Ye	sNo	X; If yes	s, mo/day/yr sample was sub-
<u> </u>	5		mitted					Wa	er Well Disinfe	cted? Yes	No X
5 TYPE OF	F BLANK C	ASING USED:		5 Wrought	iron	8 C	oncrete t	ile	CASING	JOINTS: Glue	ed Clamped
1 Stee	∍l	3 RMP (SI	R)	6 Asbestos	s-Cement	9 0	ther (spe	cify belov	()	Weld	ded
2)PVC		4 ABS		7 Fiberglas							adedX
											in. to ft.
Casing heigh	ht above la	nd surface	36	in., weight.				Ibs./	t. Wall thickne	ss or gauge N	No. Schedule 40
TYPE OF S	CREEN OF	PERFORATION	N MATERIAL:				PVC		10 /	Asbestos-cem	ent
1 Stee	el	3 Stainless	s steel	5 Fiberglas	SS	8	RMP (SR)	11 (Other (specify)
2 Bras	SS	4 Galvaniz	ed steel	6 Concrete	tile	9	ABS		12	None used (o	pen hole)
SCREEN O	R PERFOR	ATION OPENIN	IGS ARE:		5 Gau	zed wrapp	ed		8 Saw cut		11 None (open hole)
1 Con	itinuous slot	3 M	lill slot		6 Wire	wrapped			9 Drilled hole	es	
2 Louv	vered shutte	er 4 Ko	ey punched		7 Torc				, ,	• /	
SCREEN-PE	ERFORATE	D INTERVALS:	From	. 15	ft. to .		25	ft., From	n	ft.	toft.
			From								toft.
GF	RAVEL PAC	K INTERVALS:	From	13.5	ft. to .		25	ft., From	n <i></i>	$\dots \dots ft.$	toft.
			From		ft. to			ft., Fron	n	ft.	to ft.
6 GROUT	MATERIAL:		cement (2)Cement g	rout	<u> </u>	Bentonite	4			
Grout Interv	als: From	1	. ft. to 9.•	⁵ ft., Fr	om	9•5	ft. to	13•5.	ft., From		ft. to ft.
What is the	nearest sou	urce of possible	contamination:					10 Lives	ock pens	14 /	Abandoned water well
1 Sept	tic tank	4 Later	al lines	7 Pi	t privy			11 Fuel:	storage		Oil well/Gas well
2 Sew	ver lines	5 Cess	pool	8 S	ewage la	goon		12 Fertili	zer storage		Other (specify below)
3 Wat		er lines 6 Seep	page pit	9 Fe	eedyard			13 Insec	ticide storage		Çoal Gasometer
Direction fro	om well?	Southeast						How mai	ny feet⊅0		
FROM	то		LITHOLOGIC			FRO	M	то		PLUGGING	INTERVALS
0	3	Black and Li	ight Brown Lea	n Clay Fi	il With						
		Sand and Deb									
3	8	Gray Fat Cla									
. 8	11	Gray-Brown C	Clayey Silty F	ine Sand							
	25	Dark Gray St	ilty Fine Sand								
											
			RING WELL WAS			-	LLING (CASING	ITH SAND BE	LOW	
		15' AND BENT	TON I TE-CEMENT	GROUT FRO	M 0' TO	15'.					
										According	
7 CONTRA	ACTOR'S C	R LANDOWNE	R'S CERTIFICATI	ON: This wa	ater well	was 🗚 co	nstructed	l. (2) reco	nstructed. or 6	Polugged un	nder my jurisdiction and was
completed of		/4\	3/13/88 (3)	9/19/88							nowledge and belief. Kansas
		,,									78911
TTULO TYON	Contractor's	License No	416	Thi	s Water \	Well Recor	d was ∼	ompleted a	on (mo/dav#@r¥		. / 4 / / / / / / / / / / / / / / / / /
		License No			s Water	Well Recor			on (mo/day/yr)	1	1 111/1/1
under the b	usiness nan	ne of Terra	acon Consultan	ts. Inc.				by (signa	ture)	Men 1	copies to Kansas Department