


USE TYPEWRITER OR BALL  
POINT PEN-PRESS FIRMLY,  
PRINT CLEARLY.

WATER WELL RECORD  
KSA 82a-1201-1215

Kansas Department of Health and  
Environment-Division of Environment  
(Water well Contractors)  
Topeka, Kansas 66620

1. Location of well:		County	Fraction	Section number	Township number	Range number
		SEDGWICK	SW SE NW 1/4 1/4 1/4	21	T 27 S R 1	0 EW
2. Distance and direction from nearest town or city:		3. Owner of well:		67052		
Street address of well location if in city: 432 EAST DOUGLAS, WICHITA, KS		R.R. or street: 14250, 199 WEST		City, state, zip code: WICHITA, KS 67214		
4. Locate with "X" in section below:		Sketch map:		6. Bore hole dia. 7 in. Completion date 7/19/79		
		BORED 9 INCH HOLE TO 19 FT H2O INSTALLED 5" CASING AND COMPLETED WITH JAND BUCKET AT 3.5 FT.		Well depth 35 ft.		
5. Type and color of material		From		To		7. Cable tool Rotary Driven Dug Hollow rod Jetted Bored Reverse rotary
TOP SOIL BLACK		0		3		8. Use: Domestic Public supply Industry Irrigation Air conditioning Stock Lawn Oil field water Other
CLAY SANDY TAN		3		8		9. Casing: Material PVC Height: Above or below Threading Welded Surface 17 in. RMP PVC Weight 2.0 lbs./ft. Dia. 5 in. to 36 ft. depth Wall thickness: inches or Dia. in. to ft. depth Gauge No. 0250
CLAY BROWNISH SANDY		5		11		10. Screens: Manufacturer's name JET STREAM Type PVC Dia. 5 INCH Slot/gauze .031 Length 12 FT. Set between 23 ft. and 3.5 ft. Gravel pack? NO
SAND FINE TAN		11		13		11. Static water level: 19 ft. below land surface Date 7/19/79
SAND RED MEDIUM		13		15		12. Pumping level below land surfaces: ft. after hrs. pumping NA g.p.m. Estimated maximum yield 125 g.p.m.
SAND MEDIUM TAN		15		17		13. Water sample submitted: Yes X No Date
SAND GRAY COARSE		17		19		14. Well head completion: Pitless adapter 12 Inches above grade
SAND COARSE TAN		19		22		15. Well grouted? YES With: Neat cement Bentonite X Concrete Depth: From 0 ft. to 19 ft.
GRAVEL LARGE BROWN		22		24		16. Nearest source of possible contamination: ft. Direction EAST Type CAST IRON SINKER Well disinfected upon completion? Yes X No
SAND COARSE TAN		24		35		17. Pump: Not installed Manufacturer's name FTW Model number 25 HP 5 Volts 230 Length of drop pipe 25 ft. capacity 100 g.p.m. Type: Submersible Turbine Jet Reciprocating Centrifugal Other
SHALE BLUE		35				20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. BEARDEN Pump & Well Business name 3127 MENTOR License No. Address 432 EAST DOUGLAS, WICHITA, KS Signed Date 8/29/79 Authorized representative
18. Elevation: 1300 FT. Topography: Hill Slope Upland Valley		19. Remarks: PERMISSION WAS GRANTED BY DWIGHT BRINKLEY TO DRILL THIS CLOSER TO SEWER IF GROUTED TO STATIC LEVEL - OWNER HAS PERMISSION TO DRILL FOR HEAT PUMP USE APPLICATION # 33000				

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5