		Water Well Record	Form WWC-5	KSA 82a-1212		
1 LOCATION OF WATER WELL:	FRACTION			Section Number	Township Number	Range Number
Sedgwick	SW 1/4	NE 1/4 N	E 1/4	27	T 27 s	R 1E EW
Distance and direction frem nearest town or city str					1 1 3	I K EW
833 S. Chatauqua Wichita, Kansas						
WATER WELL OWNER: CALLE	, Irene					
RR#, ST. ADRESS, BOX#: 833 S	. Chatauq	ua			Board of Agriculture, Di	vivsion of Water Resource
	ta, Kansa				Application Number	r:
		POETED WELL	24	A FIL	EVATION:	
N		ater Encountered	1	ft.	2 ft.	3 ft.
	ELL'S STATIC W	ATER LEVEL 13	FT.	BELOW LAND SU	RFACE MEASURED ON mo/day/yr	04/06/1998
×	Pump tes	t data: Well wa	ater was	ft.	after hours pum	ping gpm
Est	. Yield	gpm: Well w	ater was	ft.	after hours pum	ping gpm
E Bon	e Hole Diameter		0	ft.	and in.	to ft.
E Bor	LL WATER TO	S HOED AC. 5	o Public water			njection well
						·
	1 Domestic		Oil field wat		· ·	Other (Specify below)
	2 Irrigation	4 Industrial 7	Lawn and g	arden only	10 Monitoring well	
	s a chemical/bacte	eriological sample sub	mitted to De	partment? Yes	No 🗶 ; If yes, m	o/day/yr sample was
S submitted Water Well Disinfected? Yes X No						
5 TYPE OF CASING USED:						<u> </u>
		5 Wrought iron		Concrete tile		lued Clamped
1 Steel 3 RMP (SR)		6 Asbestos-Cement	9	Other (Specify b	/	/elded
2 PVC 4 ABS		7 Fiberglass			T	hreaded X
Blank casing Diameter 1 1/4 in.	to	ft., Dia	in.	to	ft., Dia in.	to ft.
Casing height asset land surface 100		weight		••	Wall thickness or gauge No.	
TYPE OF SCREEN OR PERFORATIO	,	Actair	7	PVC	10 Asbestos-ceme	ent
1 Steel 3 Stainless Steel	· · · · · · · · · · · · · · · · · · ·	5 Fiberglass		RMP (SR)	11 other (specify	
		-				M/A
2 Brass 4 Galvantzed steel		6 Concrete tile	9	ABS	12 None used (op	en hole)
SCREEN OR PERFORATION OPENIN	NG ARE:	5 Gauze	d wrapped		8 Saw cut	11 None (open hole)
1 Continous slot 3 Mill slot		6 Wire v	vrapped		9 Drilled holes	
2 Louvered shutter 4 Key punch	ed	7 T b	4		10 Other (specify)	/ n
1						
SCREEN-PERFORATION INTERVAL	S: from	ft. (to	ft., From	ft. to	ft.
i	from	ft. 1	to	ft., Fron	t ft. to	ft.
GRAVEL PACK INTERVAL	S: from	ft.	to	ft., Fron	n ft. to	ft.
	from	ft.	to	ft., Fron	n ft. to	ft.
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug						
	. to 6	ft. From	ft.		ft. From 6	ft. to 20 ft.
What is the nearest source of possible contamination:			10 Livestock pens			bandon water well
1 Septic tank 4 Lateral lines		7 Pit privy		11 Fuel storage		Dil well/Gas well
2 Sewer lines 5 Cess pool		8 Sewage lagoon		12 Fertili	12 Fertilizer storage 16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage						
	HOLOGIC LOG		EDOM	TO 1	How many feet? 10 PLUGGING INTE	DYATC
FROM 10 LII	HOLOGIC LOG		FROM	ТО		RVALS
			0		cement grout	
			6	20	bentonite hole	plug
			20	24	chlorinated san	d and gravel
				-		
			1			
			1	1		
				+		
			<u> </u>	1 1		
		4-4-4-7-11-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1				1.00
				 		
7 CONTRACTOR'S OR LANDOWNER'S	ERTIFICATION: Th	is water well was (1) construct	ed, (2) reconstr	ucted, or (3) plugged under n	ny jurisdiction and
was completed on (mo/day/year)						
Well Contractor's License No236						
Under the business name of Harp Well & Pump Service Inc. by (signature)						
Todd S. Harp						
					o outur L	. JUULUU