

1) LOCATION OF WATER WELL:		Fraction	Township Number	Range Number
County: Sedgwick	SE ¼ NE ¼ SE ¼	Section Number 32	T 27 S	R 1 E
Distance and direction from nearest town or city street address of well if located within city? 2160 S. Broadway, Wichita, Kansas				
2) WATER WELL OWNER: Conoco Inc. RR#, St. Address, Box # : P.O. Box 2197 City, State, ZIP Code : Houston, TX 77252-2192				
Board of Agriculture, Division of Water Resources Application Number:				
3) LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4) DEPTH OF COMPLETED WELL 20 . . . ft. ELEVATION: 1286.29		
N W NW NE SW SE X S		Depth(s) Groundwater Encountered 1. ft 2. ft 3. ft WELL'S STATIC WATER LEVEL . . . 14.71 . . . ft below land surface measured on mo/day/yr . . . 6/11/98 Pump test data: Well water was . . NA . . . ft after . . . hours pumping . . . gpm Est Yield . . NA . . . gpm; Well water was . . . ft after . . . hours pumping . . . gpm Bore Hole Diameter . . . 8 . . . in. to . . . 20 . . . ft, and . . . in. to . . . ft WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.....No✓..... If yes, mo/day/yr sample was submitted _____ Water Well Disinfected? Yes No ✓		
5) TYPE OF BLANK CASING USED:				
1 Steel 3 RMP (SR)				
(2) PVC 4 ABS				
Blank casing diameter 2 in. to 10 ft, Dia in. to ft, Dia in. to ft				
Casing height above land surface . . . -2.52 . . . in., weight . . . Sch 40 . . . lbs./ft. Wall thickness or gauge No.				
TYPE OF SCREEN OR PERFORATION MATERIAL				
1 Steel 3 Stainless steel 5 Fiberglass (7) PVC 10 Asbestos-cement				
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)				
SCREEN OR PERFORATION OPENINGS ARE:				
1 Continuous slot (3) Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)				
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes				
7 Torch cut 10 Other (specify)				
SCREEN-PERFORATED INTERVALS: From 10 ft to 20 ft, From ft to ft				
From ft to ft, From ft to ft				
GRAVEL PACK INTERVALS: From 9 ft to 20 ft, From ft to ft				
From ft to ft, From ft to ft				
6) GROUT MATERIAL: 1 Neat cement (2) Cement grout (3) Bentonite 4 Other				
Grout intervals: From 0 ft to 7 ft, From 7 ft to 9 ft, From ft to ft				
What is the nearest source of possible contamination:				
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well				
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well				
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage (16) Other (specify below)				
Direction from well? East How many feet? 170 UST Basin				
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS				
0 3 Clay, Brown				
3 6.5 Sand, Orange-Brown				
6.5 8 Sand, Buff				
8 14 Sand, Tan				
14 20 Sand, Gray/Tan				
MW4 , Tag # 00271970 , Flushmount				
Project Name: Secor - Conoco #16016 - Broadway				
GeoCore # 676 , #				
7) CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6/5/98 and this record is true to the best of my knowledge and belief.				
Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 6/24/98 under the business name of GeoCore Services, Inc. by (signature) [Signature]				
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY AND PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-298-5545. Send one to WATER WELL OWNER and retain one for your records.				