


1 LOCATION OF WATER WELL:		Fraction	Section Number		Township Number		Range Number	
County: SEDGWICK		8E 1/4 8E 1/4 8E 1/4	32		T 27 S		R 1 E	
Distance and direction from nearest town or city street address of well if located within city? 2207 S. MARKET WICHITA KANSAS 67211								
2 WATER WELL OWNER:			Board of Agriculture, Division of Water Resources					
RR#, St. Address, Box #:			Application Number:					
City, State, ZIP Code:								
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL: 34 ft. ELEVATION: 1420 ft.					
			Depth(s) Groundwater Encountered 1420 ft. 2. 14 ft. 3. 15 ft.					
			WELL'S STATIC WATER LEVEL 1420 ft. below land surface measured on mo/day/yr 3-28-82					
			Pump test data: Well water was 14 ft. after 1 hours pumping 15 gpm					
			Est. Yield 25 gpm Well water was 14 ft. after 1 hours pumping 15 gpm					
			Bore Hole Diameter 5 in. to 34 ft., and 1 in. to 1 ft.					
			WELL WATER TO BE USED AS:					
			5 Public water supply 8 Air conditioning 11 Injection well					
			1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)					
			2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well					
			Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted					
			Water Well Disinfected? Yes No					
5 TYPE OF BLANK CASING USED:			CASING JOINTS Glued Clamped					
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded								
2 PVC 4 ABS 7 Fiberglass Threaded								
Blank casing diameter 2 in. to 29 ft., Dia 1 in. to 1 ft., Dia 1 in. to 1 ft.								
Casing height above land surface 12 in., weight 167 lbs./ft. Wall thickness or gauge No. 167								
TYPE OF SCREEN OR PERFORATION MATERIAL:			10 Asbestos-cement					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)								
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:			5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes								
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)								
SCREEN-PERFORATED INTERVALS:			From 29 ft. to 34 ft. From 16 ft. to 34 ft.					
GRAVEL PACK INTERVALS:			From 16 ft. to 34 ft. From 16 ft. to 34 ft.					
6 GROUT MATERIAL:			4 Other SURFACE SILT+DIRT					
1 Neat cement 2 Cement grout 3 Bentonite								
Grout Intervals: From 0 ft. to 16 ft. From 16 ft. to 34 ft.								
What is the nearest source of possible contamination:			10 Livestock pens 14 Abandoned water well					
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well								
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)								
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage								
Direction from well? South			How many feet? 25					
FROM TO LITHOLOGIC LOG			FROM TO LITHOLOGIC LOG					
0 5 SURFACE SOIL								
5 9 FINE SAND								
9 13 CLAY - GRAY								
13 34 SAND + SMALL GRAVEL								
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-28-82 437 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. Before License This Water Well Record was completed on (mo/day/yr) AUG 7, 1982 under the business name of RALPH METZGER WELL DIGGER DALLAS (signature) Ralph Metzger								
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.								

OFFICE USE ONLY

T

R

DEN

SEC

32

SE 1/4

SE 1/4

SE 1/4

SE 1/4