			\A/A TT-1	DWELL BECC	200 1	\656/	DE KOA	92- 424					
11 LOCATION	OF WA	ATER WELL:	Fraction	R WELL RECO	JRD F		ection Num		Z Township N	umber	Rar	nge Nu	mber
County: Sedgwick			SW 1/4	NW ¼	SW	1 1/4	33		T 27	S	R	1	EW
Distance and	direction	n from nearest town		ddress of well	if locate	d within cit	y?						-
		ay, Wichita, Kans	as										
2 WATER W	VELL O	WNER: Conoco Inc.											
RR#, St. Addr	ess, Bo							В	ard of Agric	ulture, Divi	sion of W	ater Re	esources
City, State, ZII	P Code	Houston, TX	77252-2192					Ar	plication Nu	mber:			
3 LOCATE W	VELL'S	LOCATION 4	DEPTH OF CO	MPLETED WE	ELL	20	ft. El	LEVATIO	V :	1	28.7.95		
— WITH AN ".		ECTION BOX: De	pth(s) Ground	water Encount	ered 1.			. ft. 2		ft	3		ft
T		i w	ELL'S STATIC	WATER LEVE	EL 15	5.9 9 f	t. below lan	nd surface	measured o	on mo/day/	yr	6/11/9	98
,		,	Pump	test data: We	ell water	was	N.A f	ft. after		hours pu	mping		gpm
"	WV	NE Es	Yield NA	gpm: W	ell water	was	1	ft. after .		. hours pu	mping		gpm
e w		_ Bo	re Hole Diame	ter 8	. in. to .	20	0 1	ft., and.		ir	n. to		ft
≅ W		 	ELL WATER T	O BE USED A	S: 5	Public wate	er supply	8 A	r conditionin	ng 11	Injection v	well	
, x			1 Domestic	3 Feedlot					ewatering		Other (Sp	ecify t	elow)
	SW	SE	2 Irrigation	4 Industri	al 7	Lawn and	garden only	y (10) M	onitoring we	ı			
1			as a chemical/	bacteriologica	l sample	submitted					, mo/day/y	yr sam	ple was
<u>. </u>		su	omitted						ell Disinfect			No √	
TYPE OF E	BLANK	CASING USED:		5 Wrought iro	n	8 Con	crete tile		CASING JO	INTS: Glue	d	Clamp	ed
1 Steel		3 RMP (SR)		6 Asbestos-C	ement	9 Othe	r (specify I	below)			ded		
2 PVC		4 ABS		7 Fiberglass							aded. 🏑		
Blank casing d	diamete	r ir	. to 10	ft, Dia	1	in.	to		ft, Dia		. in. to	<i>.</i>	ft
Casing height	above !	and surface	5.04 i	n., weight		Sch 40	1	bs./ft. W	all thickness	or gauge I	Vo		
TYPE OF SCF	REENC	R PERFORATION M	ATERIAL			(7) P	_		10 Ast	estos-cem	ent		
1 Steel		3 Stainless ste	el	5 Fiberglass		8 R	MP (SR)		11 Oth	er (specify)		
2 Brass	,	4 Galvanized s	teel	6 Concrete til	е	9 A	BS		12 Nor	ne used (op	en hole)		
SCREEN OR F	PERFO	RATION OPENINGS		5	Gauzeo	wrapped		8 S	aw cut		11 None	e (oper	n hole)
1 Contir	nuous s			6	Wire w	rapped		9 D	rilled holes				
2 Louve		,			Torch o				ther (specify				
SCREEN-PER	RFORAT	ED INTERVALS:											
			From										
GRA	VEL PA	CK INTERVALS:											
			From										
GROUT MA				Cement grou			tonite		r				
		m ft.		ft, From		7 ft	to	9	ft, From		ft. to.		ft
What is the ne	earest s	ource of possible co	ntamination:					ivestock			bandoned		well
1 Septic ta		4 Lateral li		7 Pit pr	•			uel stora			il well/Gas		
2 Sewer lin		5 Cess po		8 Sewa		on		ertilizer s	_		Other (spec		low)
•		er lines 6 Seepage	pit	9 Feed	yard			nsecticide		<u>r</u>	ST Basi	n	
Direction from		South						many fee			NITTE IN CALL		
FROM	10		THOLOGIC L	<u> </u>		FROM	10		PL	UGGING I	NIEKVAL	···-	
0	4	Clay, Brown				ļ							
4	8	Clay, Yellow Bro				-							
	12	Sand, Orange Bi				ļ							
	18	Sand, Orange Br	own	· - · · · · · · · · · · · · · · · · · ·		 							_
18	20	Sand, Brown				ļ							
						 							
						1	-						
						<u> </u>							
		*											
		4						MW8	Tag # 00272	2034 , Flus	mount		

Project Name: Secor - Conoco #16016 - Broadway

×