		WATERWI	ELL REC	ORD F	orm vv v		SA 82a-12	12		
1 LOCATION OF WATE	ER WELL:	FRACTION	CF.		- 1	TION NUMBER	1	P NUMBER	ſ	NUMBER
Sedgwick		SE 1/4		/4 SW	1/4	9	T 2	7 s	R 1	E E/W
Distance and direction fro	-			in city?		(2 los	1	.:4\		
1401 N. Mosl		Wichita, Kans GILL	sas			(2 10)	s on 1 pern	ut)		
2 WATER WELL (		N. Mosley						Board of Agric	culture, Division of	Water Resource
		ita, Kansas			-	ID CODE:		Analiantina Norm	201	60243
			ETER WE	1: 3		IP CODE:	EL ELVATION!	Application Num	iber: 201	002.15
3 LOCATE WELL'S LOCATE WITH AN "X" IN SE	CTION BOX:	DEPTH OF COMP					ELEVATION:	_		
N N		oth of groundwater			f			ft.		ft.
	WE	ELL'S STATIC WA	TER LEVEL			OW LAND SU	JRFACE MEAS	JRED ON mo/d	lay/yr: 12/2	23/16
NW	NE -		np test data:	Well wat	er was		ft. after	hours	of pumping @	gpm
w Zie		Est. Yield:	gpm	Well wa			ft. after	hours	of pumping @	gpm
1 1 1	' I I	ore Hole Diameter	12	in.	to .	35 ft	. and	in.	to	ft.
√ sw	1 1	ELL WATER TO BI  Domestic 3.	E USED AS: <b>Feedlot</b>	: -5. Public wa	tar sunnly	7 Lawn	and garden onl	9. Dewaterir		ection well
			Industrial	6. Oil field w			nditioning	7 10. <b>Monitori</b> n		Specify below
		as a chemical/bacter				YES	NO		vhat mo/day/yr	was sample
3		omitted					Water Well Disin	fected?	YES	NO
5 TYPE OF CAS	SING USED:	5. Wrought	Iron	7. Fiberglass	9. C	ther (Specify	/ below) CA	SING JOINTS:	Glued	Threaded
1. Steel	3. RPM (SR	()		-	SD	R-26	, ,		Welded	Clamped
2. PVC	4. ABS	6. Asbestos	-Cement	8. Concrete ti	le SD	K-20				,
Blank casing diamet	er <b>8</b> i	in. to	20 ft.,	Dia.	in.	to	ft.,	Dia. i	in. to	ft.
Casing height above	e land surface:	12 in.,		Weight:	5.52	lbs. / ft.	Wall th	nickness or gaug	je No332	2
TYPE OF SCREEN	OR PERFORATION	MATERIAL:								_
1. Steel	3. Stainless Steel	5. Fiberglass		7. PVC	9. A	ABS	11. O	ther (specify)		
2. Brass	4. Galvanized	6. Concrete Ti	ile i	8. RMP (SR)	10. /	Asbestos-Cei	ment 12. N	one used (open	hole)	
SCREEN OR PERFO	DRATION OPENING	S ARE:								
1. Continuous slo			auzed wra	pped	7. <b>T</b> c	orch cut	9. Dril	led holes	11. None (	open hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped						aw cut	10 Oth	Other (specify)		
		inched 0. v				aw cut	10. 01	er (specify)		
SCREEN - PERFORA	ATION INTERVAL	From	<b>20</b> ft	. to	35	ft.,	From	ft.	to	ft.
		From	ft	. to		ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS: From 20 ft.			. to	28	ft.,	From	ft.	to	ft.	
		From	ft.	. to	ı	ft.,	From	ft.	to	ft.
6 GROUT MATER	IALS: 1. Neat o	coment	2. Cemer	at Grout		3. Bentonite			onite hole p	
Grout Intervals:	From 0	ft. to	20 ft.,		ft.		ft.,	From	ft. to	•
What is the nearest s	, , , , , ,		20 (6.)				п.,	FIOIII	11. 10	η, η,
1. Septic tank	4. Lateral	lines 7.	Pit privy	1	0. Livesto	ck pens	13. Insect	icide storage	15. Oil well/	
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage						14. Aband	ion water well	-	pecify below)	
3. Watertight sew	er line 6. Seepag	ge pit 9.	Feed yard	•	2. Fertilize	r storage			None A	pparent
Direction from well?		-					How m	any feet?		
From To		LITHOLOGIC	LOG		From	То		LITHOLO	GIC LOG	
0 3	topsoil									
3 9	sandy clay									
9 22	fine sand				<b>.</b>					
22 35	medium sand									
						-				
	1									
					<u> </u>					
	<b> </b>									
	1				L					
7 Contractor's or	Landowner's Certific		well was 1.C	constructed	) 2. re	constructed	or 3.	plugged (	under my jurisdic	ction and
was completed on	(mo/day/year)	12/28/16	ar	nd this record	s true to the	e best of my	knowledge and	belief.		
Kansas Water Wei	l Contractor's Licens	se No. 236		This water we	ell record wa	as completed	I on (mo/day/yea	ar) 12/3	30/16	
under the business	name of Harp V	well and Pum	ip Servic	e	by (s	ignature)	T	odd S.	. Hart	)