WATER WELL R			Division of Water					
Original Record		ge in Well Use		ources App. No.		Well ID		
1 LOCATION OF W	Fraction		ction Number	Township Number		ge Number		
County: SEDGWIC	NW 1/4 SE 1/4 NW 1/4							
2 WELL OWNER: Last Name: First: Street or Rural Address where well is located (if unknown, distance								
Business: PREMIER		direction from	irection from nearest town or intersection): If at owner's address, check here:					
Address: 12729 SW BUTLER ROAD Address: - 18				605 W MAY				
Address.				VICHITA, KS 67213				
2 LOCATE WELL								
WITH "X" IN	4 DEPTH OF COM							
Depth(s) Groundwater Encountered: 1)!9.								
N 2) tt. 3) tt., or 4)								
WELL'S STATIC WATER LEVEL:				ft. Source for Latitude/Longitude:				
below land surface, measured on (mo-day-yr								
above land surface, measured on (mo-day-yr				(,				
	Pump test data: Well water was27 ft. after 1.5 hours pumping 35 gpt			☐ Land Survey ☐ Topographic Map				
WE	after	gpm	☐ Onlin	☐ Online Mapper:				
SW SE	1	vater was f						
	after hours pumping gpr Estimated Yield:40gpm			6 Elevation:ft. ☐ Ground Level ☐ TOC				
S	Bore Hole Diameter:10.5 in. to 50			Source: Land Survey GPS Topographic Map				
mile	Bore Hole Diameter	in to	It. allu	Other				
1 mile  in. to ft.   Other								
1. Domestic: 5. Public Water Supply: well ID								
☐ Household				11. Test Hole: well ID				
Lawn & Garden	_ ,				☐ Cased ☐ Uncased ☐ Geotechnical			
Livestock					12. Geothermal: how many bores?			
2. Irrigation					a) Closed Loop   Horizontal   Vertical			
3. ☐ Feedlot					b) Open Loop   Surface Discharge   Inj. of Water			
4.  Industrial	☐ Recovery				(specify):			
Was a chemical/bacteriological sample submitted to KDHE? ☐ Yes ☐ No If yes, date sample was submitted:								
8 TYPE OF CASING USED: ☐ Steel ☐ PVC ☐ Other								
Casing diameter 5 in to 50 ft., Diameter in to ft., Diameter in to ft., Diameter in to ft.  Casing height above land surface in Weight lbs./ft. Wall thickness or gauge No. SDR-26								
TYPE OF SCREEN OR PERFORATION MATERIAL:  ☐ Steel ☐ Stainless Steel ☐ Fiberglass ■ PVC ☐ Other (Specify)								
☐ Steel ☐ Stainless Steel ☐ Fiberglass ☐ PVC ☐ Other (Specify)								
SCREEN OR PERFORATION OPENINGS ARE:								
☐ Continuous Slot								
Louvered Shutter    Key Punched    Wire Wrapped    Saw Cut    None (Open Hole)								
SCREEN-PERFORATED INTERVALS: From .20ft. to .50								
GRAVEL PACK INTERVALS: From 20 ft. to 50 ft., From ft. to ft., From ft. to ft.								
0 CDOUT MATERIAL - Diseasement - Coment group - Bentonite - Other								
9 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☐ Bentonite ☐ Other								
Nearest source of possible contamination:								
Septic Tank								
Sewer Lines Cess Pool Sewage Lagoon Fuel Storage Abandoned Water Well								
■ Watertight Sewer Lines								
Direction from well? SOUTH WEST Distance from well? .44 ft.								
10 FROM TO	LITHOLO		FROM		THO. LOG (cont.) or F	PLUGGIN	G INTERVALS	
0 1 7	TOP SOIL							
	CLAY							
	FINE/MED SAND							
	MED GRAVEL							
	SHALE		1					
	or of the law			<del> </del>				
			Notes:					
11005.								
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged								
under my jurisdiction and was completed on (mo-day-year) .1/29/2017 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No. 884 This Water Well Record was completed on (mo-day-year) 2/14/2017								
under the business name of WENINGER DRILLING LLC Signature								
Mail I white copy along with a fee of \$5.00 for each constructed well to: Kansas Department of Health and Environment, Bureau of Water, GWTS Section,								
1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Mail one to Water Well Owner and retain one for your records. Telephone 785-296-5524.								
Visit us at http://www.kdheks			SA 82a-1212 Revised 7/10/2015					