	WATER W	ELL REC	ORD	Form W	WC-5 k	SA 82a-12	212		
1 LOCATION OF WATER WELL:	FRACTION			SECTION NUMBER			HIP NUMBER	RANGE NUMBER	
Sedgwick Distance and direction from nearest town or city	SE 1/4		/4 SW	1/4	11	T	27 s	R 1E	E/W
13405 E. Crestwood Ct.		chita, Kans	•						
2 WATER WELL OWNER: SCHOPNER, Travis									
	5 E. Crestwo						Board of A	griculture, Division of W	ater Resource
CITY, STATE: Wich	nita, Kansas				ZIP CODE: 6	67230	Application N	umber:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	DEPTH OF COMP	LETED WEL	L: 1	00 ft		ELEVATION			
N Del	pth of groundwate	r Encountered			ft.		ft.		ft.
	ELL'S STATIC WA		45	FT. BEL	OW LAND S	URFACE MEAS	SURED ON mo	o/day/yr: 6/18	/18
NW NE		mp test data:		ater was		ft. after		rs of pumping @	gpm
M Miles	Est. Yield: ore Hole Diameter	дрт г 12	Well wa	ater was	100 ff	ft. after t. and		irs of pumping @	gpm
	ELL WATER TO B		и.	10	100 11	t. and	in.	to	ft. ction well
1 1 000 1 1			5. Public w	ater supply	7. Lawn	and garden or	9. Dewate	12. Other (Sp	
		Industrial			-	nditioning	10. Monitor	ring well	-
	Vas a chemical/bacte bmitted	nological sample	e submitted to	Department?		NO Water Well Disi		, what mo/day/yr w	as sample
5 TYPE OF CASING USED:			.	0				\succeq	Threaded
1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass 9. Other (Specify below) CASING JOINTS: Glued Threaded Clamped									
2. PVC 4. ABS	6. Asbestos	s-Cement 8	8. Concrete	tile S1	JK-20				
Blank casing diameter 5	in. to	24 ft.,	Dia.	in.	to	ft.,	Dia.	in. to	ft.
Casing height above land surface:	12 in.,		Weight:	2.35	lbs. / ft.	Wall	thickness or ga	uge No214	
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)									
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)									
SCREEN OR PERFORATION OPENING 1. Continuous slot 3. Mill slo		Causad wear	nad	7.7		0 D -	عمله ما العمالية	44 Name (a	
		Gauzed wrap	•		orch cut		illed holes	11. None (o	pen noie)
, p.	unched 6. V	Wire wrapped	d		aw cut	10. Ot	her (specify)		
SCREEN - PERFORATION INTERVAL	From	24 ft.	to	100	ft.,	From	ft.	to	ft.
	From	ft.	to)	ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS:	From	45 ft.	t	o 100	ft.,	From	ft.	to	ft.
	From	ft.	t	0	ft.,	From	ft.	to	ft.
6 GROUT MATERIALS: 1. Neat		2. Cement	t Grout		3. Bentonite	e	Other ben	itonite hole plu	ıg
Grout Intervals: From 4 What is the nearest source of possible co	ft. to	24 ft.,	From	f	. to	ft.,	From	ft. to	ft.
1. Septic tank 4. Lateral	7	. Pit privy		10. Livesto	ck pens	13. inse d	cticide storage	15. Oil well/G	as well
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify bel								ecify below)	
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage									
Direction from well? South						How r	many feet? 40	ft plus	
	LITHOLOGIC	CLOG		From	То		LITHOL	OGIC LOG	
0 3 topsoil 3 42 brown shale									
42 100 grey shale				 	 	 			
5-3									
				<u> </u>					
				 	-				
					 				
				-					
	_				1				
7 Contractor's or Landowner's Certific	cation: This water	well was 1.	constructe	d) 2. r	econstructe	d or 3.	plugged	under my jurisdiction	on and
was completed on (mo/day/year) 6/18/18 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's Licens	se No. 236					•		19/18	
Wansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 6/19/18 under the business name of Harp Well and Pump Service by (signature) Todd S. Harb									