			WATER W	ELL REC	ORD F	orm WW	/C-5 K	SA 82a-12	12		
1 LOCATION OF WATER WELL: FRACTION							ION NUMBER	TOWNSH	ISHIP NUMBER RANGE NUMBER		
<sup>□</sup> Sedgwi	ick		NW 1/4	<b>SE</b> 1	/4 NE	1/4	12	Т 2	27 s	R 1	E E/W
Distance and di	rection from	nearest town or city s	treet address of we	l if located with	in city?			<u> </u>		•	
1926 N	. Gordo	n Wi	chita, Kansa	s							
2 WATER	WELL O	WNER: FOR	D, Gary								
RR#,ST. AI	DDRESS,	BOX #: 1926	N. Gordon						Board of Ag	riculture, Division o	f Water Resource
	CITY, S	STATE: Wich	ita, Kansas			ZIF	CODE:		Application Nu	mber:	
3 LOCATE V	WELL'S LO	CATION 4 D	EPTH OF COMF	LETED WEL	L: 40	ft.		ELEVATION:			
WITH AN	"X" IN SEC	TION BOX:	th of groundwate			ft.			ft.		ft.
	N		LL'S STATIC WA				W I AND SI	IDEACE MEAS	URED ON mo	/day/yr: 1	4/19
	i. I	"-		mp test data:			W LAND SC	ft, after		s of pumping @	gpm
)N	W		Est. Yield:	gpm	Well water			ft. after		rs of pumping @	gpm
w Wile		E Bo	ore Hole Diameter	- 10	in.	to 4	<b>0</b> ft.		in.	to	ft.
-		, I I	LL WATER TO E						9. Dewater	44 1-	jection well
3	- w			Feedlot	5. Public wat	er supply '	7. Lawn a	nd garden on	Dewater	9	(Specify below)
		2.	Irrigation 4.	Industrial	6. Oil field wa	ter supply	8. Air con	ditioning	10. Monitor		, , , , , , , , , , , , , , , , , , , ,
'	S	w	as a chemical/bacte	nological samp	le submitted to De	epartment?	YES	NO		what mo/day/yr	•
		sub	mitted				Was V	Vater Well Disi	nfected?	YES	NO
		NG USED:	. 5. Wrought	Iron	7. Fiberglass	9. Ot	her (Specify	below) CA	SING JOINTS:	Glued	Threaded
1.5	Steel	3. RPM (SR	2)		-	SDI	R-26			Welded	Clamped
2.1	PVC	4. ABS	6. Asbesto	s-Cement	8. Concrete tile	9 021					
Blank casing	g diamete	r <b>5</b> i	in. to	30 ft.,	Dia.	in.	to	ft.,	Dia.	in. to	ft.
Casing heig	ght above	land surface:	12 in.,		Weight:	2.35 lb	os. / ft.	Wall	thickness or gau	ige No21	4
TYPE OF S	CREEN C	R PERFORATION	MATERIAL:								
1. Steel	3	Stainless Steel	<ol><li>Fiberglass</li></ol>		7. PVC	9. A	BS	11. C	Other (specify)		
2. Brass	4	Galvanized	6. Concrete	Tile	8. RMP (SR)	10. A	sbestos-Cer	ment 12. N	lone used (oper	n hole)	
SCREEN OF	R PERFO	RATION OPENING	S ARE								
1. Continu		3. Mill slo		Gauzed wra	pped	7. <b>To</b>	rch cut	9. <b>D</b> ri	illed holes	11. None	( open hole)
2. Louvere	od ebutto	r 4. Key pu		Wire wrappe		9 83	w cut	10.04	her (specify)		
		, p.	inched o.		, u		11 001	10. 01	nor (specify)		
SCREEN - P	PERFORA	TION INTERVAL	From	<b>30</b> ft	t. to	40	ft.,	From	ft.	to	ft.
			From	ff	t. to		ft.,	From	ft.	to	ft.
GR/	AVEL PAG	CK INTERVALS:	From	<b>24</b> ft	to to	40	ft.,	From	ft.	to	ft.
			From	ft	. to		ft.,	From	ft.	to	ft.
G GROUT	MATERI	ALS: A Marke								tonite hole	
Grout Inf		From 4		2. Cemer			Bentonite			nomic noic j	orug "
		urce of possible co		<b>24</b> ft.	, From	ft.	to	ft.,	From	π.	to II.
1. Septic 1		4. Lateral		7. Pit privy	10	D. Livestoc	k pens	13. <b>Ins</b> ec	ticide storage	15. Oil we	II/Gas well
2. Sewer i		5. Cess P	ool 8	. Sewage la	goon 1	1. Fuel sto	rage	14. <b>Aba</b> n	don water wel	16. Other	(specify below)
3. Waterti			_	Feed yard	1	2. Fertilize	r storage				
Direction fro	-	East	ge pit	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	-			How r	many feet? 40	ft. plus	
From	То		LITHOLOGI	CLOG		From	То	1.0		OGIC LOG	
0		topsoil	LITTIOLOGI	0 100		110111			LITTIOL	OOIO LOO	
3	11	clav						· · · · · · · · · · · · · · · · · · ·			
11	24	fine sand									
24	40	gray shale									
								<u> </u>			
							<del> </del>				
							<del> </del>	<del></del>			
17							<u> </u>				N - C
7 Contra	actor's or l	andowner's Certific					constructe	d or 3,	plugged	under my juriso	aiction and

was completed on (mo/day/year)

1/4/19

And this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 236

This water well record was completed on (mo/day/year)

1/7/19

under the business name of Harp Well and Pump Service

by (signature)

y/year) 1/7/19 Todd S. Harp