WATER WELL RI		WWC-5		ision of Water		Well ID NAW-PID		
Original Record LOCATION OF W		ge in Well Use		urces App. No. tion Number	Township Numb			
County: Sedgwick	TER WELL:	SW 14 SE 14 SE 14		9	T 27 S	RIBEDW		
2 WELL OWNER: Last Name: First: Street or Rural Address where well is located (if unknown, distance and								
Business: City of Wic		direction from nearest town or intersection): If at owner's address, check here:						
Address: 455 N. Main			Northelike right of may on E partist the west of Mosley Ave.					
Address:	wichite, ks							
City: Wichita	State: KS	ZIP: 67202		· 1				
3 LOCATE WELL WITH "X" IN 4 DEPTH OF COMPLETED WELL: 35 ft. 5 Latitude:						(decimal degrees)		
SECTION BOX:	Depth(s) Groundwater	r Encountered: 1)12-	ft.	ft. Longitude: 97. 32784 (decimal degrees)				
N N	N [2) It. 3) It., or 4) [The state of the s			
	WELL'S STATIC WATER LEVEL:				Source for Latitude/Longitude:			
				GPS (unit make/model: garmen c60				
NWNE	Pump test data: Well		(WAAS enabled? Wes No)					
w x E	after hou		☐ Land Survey ☐ Topographic Map ☐ Online Mapper:					
] "	Well							
SW SE	after≒ hou	gpm	(Florida					
	Estimated Yield:		6 Elevation:					
S				Other				
7 WELL WATER TO BE USED AS:								
1. Domestic:		/ater Supply: well ID		10 🗆 0917	ield Water Supply- 1	case		
Household		ing: how many wells?			le: well ID			
☐ Lawn & Garden	☐ Lawn & Garden 7. ☐ Aquifer Recharge: well ID							
Livestock	— - •							
2. Irrigation								
3. ☐ Feedlot ☐ Air Sparge ☐ Soil Vapor 4. ☐ Industrial ☐ Recovery ☐ Injection			extraction	, , <u> </u>				
Was a chemical/bacteriological sample submitted to KDHE? Yes No If yes, date sample was submitted:								
Water well disinfected? ☐ Yes ■ No								
8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded								
Casing diameter 1.25 in. to 20 ft. Diameter in. to ft. Diameter in. to ft. Diameter in. to ft. Casing height above land surface 0.3 in. Weight lbs/ft. Wall thickness or gauge No. Sch. 40								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
☐ Steel ☐ Stainless Steel ☐ Fiberglass ■ PVC ☐ Other (Specify)								
	anized Steel 🔲 Con	nerete tile 🔲 None u	sed (open hole					
SCREEN OR PERFORATION OPENINGS ARE:								
☐ Continuous Slot								
□ Louvered Shutter □ Key Punched □ Wire Wrapped □ Saw Cut □ None (Open Hole)								
SCREEN-PERFORATED INTERVALS: From 20 ft. to 35 ft. From 1 ft. to 1 ft.								
OCRAVEL FACE INTERVALS. FIOR								
GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From								
Nearest source of possible contamination:								
☐ Septic Tank ☐ Lateral Lines ☐ Pit Privy ☐ Livestock Pens ☐ Insecticide Storage								
☐ Sewer Lines	Cess Pool			Fuel Storage		loned Water Well		
☐ Watertight Sewer Lines ☐ Seepage Pit ☐ Feedyard ☐ Fertilizer Storage ☐ Oil Well/Gas Well								
☐ Other (Specify) Direction from well?								
10 FROM TO	LITHOLO	OGIC LOG	FROM			I. FPLUGGING INTERVALS		
0 6	Sant-		1	- · · · · · · ·		THE PROPERTY OF PERSONS ASSESSED.		
6 12	Silty clays		 					
12 35	Sand	·····	1					
35 -	Shale							
			Notes: L	ithologic log bas	ed on Electrical Cond	luctivity logging data.		
11 CONTRACTORS OF LANDOWNERS CERTIFICATION. TO								
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed. reconstructed, or plugged under my jurisdiction and was completed on (mo-day-year)? 119.1.20 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No. 710								
under the business name	of Below Ground Surfa	ce, inc.	Si	gnature				
under the business name of Below Ground Surface, Inc. Signature								
1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Mail one to Water Well Owner and retain one for your records. Telephone 785-296-5524.								
With most filling fraction believes and an administration from the WSA 972-1717 Provided 7/10/7015								