

WATER WELL RECORD Form WWC-5

Division of Water Resources App. No.

Well ID

NMW-638

Original Record Correction Change in Well Use

1 LOCATION OF WATER WELL: County: Sedgwick Fraction SE 1/4 NW 1/4 SW 1/4 Section Number 9 Township Number T 27 S Range Number R 1 E W

2 WELL OWNER: Last Name: City of Wichita/Environmental Health First: Address: 455 N. Main Street or Rural Address where well is located: North right-of-way on E. 14th St. N west of N Emporia Ave. Wichita, KS

3 LOCATE WELL WITH "X" IN SECTION BOX: N W E S 1 mile

4 DEPTH OF COMPLETED WELL: 38.5 ft. Depth(s) Groundwater Encountered: 1) 11 ft. 2) ... 3) ... 4) Dry Well WELL'S STATIC WATER LEVEL: 11.7 ft. below land surface, measured on (mo-day-yr) 3/17/20

5 Latitude: 37.70996 (decimal degrees) Longitude: 97.33386 (decimal degrees) Horizontal Datum: WGS 84 GPS (unit make/model: Garmin c60)

6 Elevation: ... ft. Source: Land Survey GPS Topographic Map Other

7 WELL WATER TO BE USED AS: 1. Domestic: Household Lawn & Garden Livestock Irrigation Feedlot Industrial 2. Public Water Supply: well ID ... 3. Dewatering: how many wells? ... 4. Aquifer Recharge: well ID ... 5. Monitoring: well ID NMW-638 6. Environmental Remediation: well ID ... 7. Oil Field Water Supply: lease ... 8. Test Hole: well ID ... 9. Geothermal: how many bores? ... 10. Closed Loop Horizontal Vertical 11. Open Loop Surface Discharge Inj. of Water 12. Other (specify): ...

Was a chemical/bacteriological sample submitted to KDHE? No If yes, date sample was submitted: ...

8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded Casing diameter: 1.25 in. to 2.35 ft. Diameter: ... in. to ... ft. Diameter: ... in. to ... ft. Casing height above land surface: 20.9 in. Weight: ... lbs./ft. Wall thickness or gauge No. Sch. 40

TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel Fiberglass PVC Other (Specify) Brass Galvanized Steel Concrete tile None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify) Louvered Shutter Key Punched Wire Wrapped Saw Cut None (Open Hole) SCREEN-PERFORATED INTERVALS: From 23.5 ft. to 38.5 ft. GRAVEL PACK INTERVALS: From 19.5 ft. to 38.5 ft.

9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From 2 ft. to 19.5 ft. From ... ft. to ... ft. From ... ft. to ... ft.

Nearest source of possible contamination: Septic Tank Lateral Lines Pit Privy Livestock Pens Insecticide Storage Sewer Lines Cess Pool Sewage Lagoon Fuel Storage Abandoned Water Well Watertight Sewer Lines Seepage Pit Feedyard Fertilizer Storage Oil Well/Gas Well Other (Specify) Direction from well? Distance from well? ft.

Table with 6 columns: 10 FROM TO LITHOLOGIC LOG FROM TO LITHO. LOG (cont.) or PLUGGING INTERVALS. Rows: 0-7 Silty clay; 7-38 Sand w/ clay lens at 15', 21', 30'; 38- shale

Notes: Lithologic log based on Electrical Conductivity logging data.

11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo-day-yr) 7/24/20 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 710 This Water Well Record was completed on (mo-day-yr) 4/11/20 under the business name of Below Ground Surface, Inc. Signature

Mail 1 white copy along with a fee of \$5.00 for each constructed well to: Kansas Department of Health and Environment, Bureau of Water, GWTS Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Mail one to Water Well Owner and retain one for your records. Telephone 785-296-5524. Visit us at http://www.kdheks.gov/waterwell/index.html KSA 82a-1212 Revised 7/10/2015