	WATER WE	LL RECORD 1	orm WV	VC-5 K	SA 82a-121			
1 LOCATION OF WATER WELL:	FRACTION	ATTAL CO		TION NUMBE			RANGE NU	
Sedgwick		NW 1/4 SE	1/4	25	T 27	S	R 1E	E/W
Distance and direction from nearest town	-	_						
620 S. Waverly	Wichita, Ka	insas						
	SHARP HOMES 2131 N. Collective S	40 # A				Board of Agri	culture, Division of Wa	ater Resource
	Wichita, Kansas	ote #A	71	P CODE: 6	7206	Application Num	ibar:	
		ZNED OVELL: 3	4	P CODE: 4		Application Num	ibei.	
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF POMES	.,			ELEVATION:	•		
N N	Depth of groundwater E		ft.			ft.	- 14 m	ft.
	WELL'S STATIC WAT			W LAND SI	JRFACE MEASU			20
NW NE		test data: Well wa			ft. after		of pumping @	gpn
W W E	Est. Yield:	gpm Well wa			ft. after		of pumping @	gpn
5 W	Bore Hole Diameter WELL WATERUDE BE	in.	to	ft	. and	in.	to	ft.
swse	•	eedlot 5. Public wa	iter supply	7. Lawn	and garden only	9. Dewaterii	_	
T i		dustrial 6. Oil field v				10. Monitorin	12. Other (Spage well	ecity below
S		ogical sample submitted to		YES	NO	; If yes, v	vhat mo/day/yr wa	as sample
	submitted				Water Well Disinfe	ected?	YES N	0
5 TYPE OF CASING USED:	5. Wrought Ire	on 7. Fiberglass	9. Of	her (Specif	y below) CASI	NG JOINTS:	Glued	Threaded
	PM (SR)	-					Welded	Clamped
2. PVC 4. A			ille					
Blank casing diameter	5 in. to	ft., Dia.	in.	to	ft., [Dia.	in. to	ft.
Casing height Downard surface	e: 2 in.,	Weight:	It	os. / ft.	Wall this	ckness or gaug	je No.	
TYPE OF SCREEN OR PERFOR								
1. Steel 3. Stainless S	Steel 5. Fiberglass	7. PVC	9. A	BS	11. Oth	er (specify)		
2. Brass 4. Galvanized	6. Concrete Tile	8. RMP (SR)	10. A	sbestos-Ce	ment 12. Nor	ne used (open	hole)	
SCREEN OR PERFORATION OF	PENINGS ARE:							
1. Continuous slot 3.	Mill slot 5. Ga	uzed wrapped	7. To	rch cut	9. Drille	d holes	11. None (o _i	en hole)
2. Louvered shutter 4.	Key punched 6. Wi	re wrapped	8. Sa	w cut	10. Othe	r (specify)		
SCREEN - PERFORATION INTER		ft. to		ft.,	From	ft.	to	ft.
	From	ft. to)	ft.,	From	ft.	to	ft.
GRAVEL PACK INTERV	ALS: From	ft. to	0	ft.,	From	ft.	to	ft.
	From	ft, to)	ft.,	From	ft.	to	ft.
6 GROUT MATERIALS: (1	. Neat cement	2. Cement Grout	(3	Bentonite		Other		
Grout Intervals: From	6 ft. to	7 ft., From	7 ft.	to	26 ft.,	From	ft. to	ft.
What is the nearest source of poss		NA	10. Livestoc		,			
1. Septic tank 4. I				• 5	13. Insectio	ide storage	15. Oil well/Ga	
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specific						city below)		
3. Watertight sewer line 6.	Seepage pit 9. F	eed yard	12. Fertilizei	storage				
Direction from well?					How ma			
From To	LITHOLOGIC	LOG	From	То		LITHOLO	GIC LOG	
			0	3	concrete floor back			
			3	26	bentonite ho			
			26	34	chlorinated ;	gravel		
			-					
					 			
			-					
7 Carradad i i i	0-15-1							
Contractor's or Landowner's	C 14 T 10 0 0 0	ell was 1. constructed	a 2. re	constructe	d or 3. p	lugged	under my jurisdiction	on and
was completed on (mo/day/yea	(r) 6/15/2020	and this record	is true to the	best of my	knowledge and b	elief.		
Kansas Water Well Contractor's	License No. 236	This water w	ell record wa	s completed	d on (mo/day/year	6/16	/2020	
under the business name of	Iarn Well and Pumr	Service	bv (sid	gnature)	7.	2.55	11000	
1	P · · · · · · · · · · · · · · · · ·	, 501 1100	-7 (5%	/	10	ruu S	. Harp	