

1 LOCATION OF WATER WELL:		Fraction* SE 1/4 NE 1/4 1/4		Section Number 4	Township Number T 27 S	Range Number R 1 EW
County: Sedgwick						
Distance and direction from nearest town or city street address of well if located within city? 2645 New York Ave., Wichita, Ks						
2 WATER WELL OWNER:		Union Pacific Railroad				
RR#, St. Address, Box # :		1416 Dodge St.				
City, State, ZIP Code :		Omaha Ne 68179				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 25.0 ft. ELEVATION: 1318.49				
		Depth(s) Groundwater Encountered 1 16.65 ft. 2 . ft. 3 . ft.				
		WELL'S STATIC WATER LEVEL 16.65 ft. below land surface measured on mo/day/yr				
		Pump test data: Well water was . ft. after . hours pumping . gpm				
		Est. Yield . gpm Well water was N/A ft. after . hours pumping . gpm				
		Bore Hole Diameter . in. to 25 . ft., and . in. to . ft.				
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well				
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)				
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well				
		Was a chemical/bacteriological sample submitted to Department? Yes . No X; If yes, mo/day/yr sample was submitted				
5 TYPE OF BLANK CASING USED:		Water Well Disinfected? Yes . No X				
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued . Clamped .						
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded .						
Blank casing diameter . in. to 13.5 . ft., Dia . in. to . ft., Dia . in. to . ft.		Threaded . X				
Casing height above land surface . in., weight 169 . lbs./ft. Wall thickness or gauge No. .						
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement				
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) .						
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:		8 Saw cut 11 None (open hole)				
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes						
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) .						
SCREEN-PERFORATED INTERVALS: From 13.5 ft. to 23.5 ft., From . ft. to . ft.						
GRAVEL PACK INTERVALS: From 11 ft. to 25 ft., From . ft. to . ft.						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other .						
Grout Intervals: From 0 ft. to 9 ft., From 9 ft. to 11 ft., From . ft. to . ft.						
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well				
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well						
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)						
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage						
Direction from well? rail yard		How many feet? .				
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	
		please see attached log				
0	3	Gravel & clinkers				
3	9	Clay				
9	12	Silt				
12	25	Sand				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/6/94 and this record is true to the best of my knowledge and belief. Kansas						
Water Well Contractor's License No. 581 This Water Well Record was completed on (mo/day/yr) 7/11/94						
under the business name of Layne, Inc. by (signature) Steven R. Mitchell						
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.						