

Copy - CP

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SEDGWICK		NE 1/4 SW 1/4 SE 1/4	4	T 27 S	R 1E E/W
Distance and direction from nearest town or city street address of well if located within city?					
50 FEET NORTH OF 21st STREET AND 780 FEET WEST OF CLEVELAND				WELL #32	
2 WATER WELL OWNER: DERBY REFINING COMPANY					
RR#, St. Address, Box # : P. O. BOX 1030			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : WICHITA, KANSAS 67201			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 37 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 11.5 ft. below land surface measured on mo/day/yr 1-15-83			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 14 in. to 38 ft., and in. to ft.			
TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
<input checked="" type="checkbox"/> 1 Steel		<input checked="" type="checkbox"/> Welded			
2 PVC		Threaded			
3 RMP (SR)		5 Wrought iron			
4 ABS		6 Asbestos-Cement			
		7 Fiberglass			
Blank casing diameter 10 in. to 7 ft., Dia in. to ft., Dia in. to ft.		8 Concrete tile			
Casing height above land surface 18 in., weight lbs./ft. Wall thickness or gauge No. 250		9 Other (specify below)			
TYPE OF SCREEN OR PERFORATION MATERIAL:		10 Asbestos-cement			
1 Steel		11 Other (specify)			
2 Brass		12 None used (open hole)			
<input checked="" type="checkbox"/> 4 Galvanized steel		5 Gauzed wrapped			
3 Stainless steel		6 Concrete tile			
5 Fiberglass		8 Saw cut			
8 RMP (SR)		11 None (open hole)			
9 ABS		10 Other (specify)			
SCREEN OR PERFORATION OPENINGS ARE:		12 None used (open hole)			
1 Continuous slot		5 Wire wrapped			
3 Mill slot		6 Torch cut			
2 Louvered shutter		7 Drilled holes			
4 Key punched		10 Other (specify)			
SCREEN-PERFORATED INTERVALS:		SCREEN-PERFORATED INTERVALS:			
From 7 ft. to 37 ft., From ft. to ft.		From ft. to ft., From ft. to ft.			
GRAVEL PACK INTERVALS:		GRAVEL PACK INTERVALS:			
From 7 ft. to 37 ft., From ft. to ft.		From ft. to ft., From ft. to ft.			
6 GROUT MATERIAL:		4 Other			
1 Neat cement		3 Bentonite			
<input checked="" type="checkbox"/> 2 Cement grout		4 Other			
Grout Intervals: From 0 ft. to 7 ft., From ft. to ft.		Grout Intervals: From ft. to ft., From ft. to ft.			
What is the nearest source of possible contamination:		10 Livestock pens			
1 Septic tank		14 Abandoned water well			
4 Lateral lines		15 Oil well/Gas well			
2 Sewer lines		16 Other (specify below)			
5 Cess pool		8 Sewage lagoon			
3 Watertight sewer lines		9 Feedyard			
6 Seepage pit		11 Fuel storage			
Direction from well? NORTHWEST		12 Fertilizer storage			
		13 Insecticide storage			
		How many feet? 450			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0.0	0.83	GRAVEL AND CLAY			
0.8	5.0	SILTY CLAY AND FILL			
5.0	13.0	SILTY CLAY			
13.0	17.0	SILTY SANDY CLAY			
17.0	36.5	MEDIUM SAND			
36.5	38.0	GREEN SHALEY CLAY			
38.0		BOTTOM OF HOLE			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <input checked="" type="checkbox"/> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-15-83 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 415 This Water Well Record was completed on (mo/day/yr) 3-24-83 by (signature) Daniel W. Daniels					
under the business name of Daniels Drilling Company					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

27

R

DW

SEC.

4

NE 1/4

SW 1/4

SE 1/4

NE 1/4

SW 1/4

SE 1/4